

SAFETY DATA SHEET

SMOOTH MASONRY PAINT STRONG BASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SMOOTH MASONRY PAINT STRONG BASE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Professional use Consumer use				
	Uses advised against			
None				

Product use : Waterborne coating for exterior use.

1.3 Details of the supplier of the safety data sheet

ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K.

Tel.: +44 (0) 333 222 70 70 www.armsteadtrade.co.uk

e-mail address of person responsible for this SDS

: armstead.advice@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +44 (0)344 892 0111

<u>Supplier</u>

Telephone number : T +44 (0) 1753 550000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision: 27-1-2024Version: 1Date of previous issue: No previous validation1/19AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 2: Hazards identification

2.2 Label elements

Signal word : No signal word.

Hazard statements: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General: P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Supplemental label

elements

: Contains 1,2-benzisothiazol-3(2H)-one and CMIT/MIT(3:1). May produce an allergic

reaction.

: Not applicable.

: Not applicable.

Annex XVII - Restrictions

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according

to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤0.3	Eye Irrit. 2, H319	-	[1] [2]
bronopol (INN)	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg M [Acute] = 10	[1]
1,2-benzisothiazol-3(2H)-	EC: 220-120-9	<0.05	Acute Tox. 4, H302	ATE [Oral] = 500	[1]

Date of issue/Date of revision : 27-1-2024 Version : 1

Date of previous issue : No previous validation 2/19 AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

			STRONG BASE		
SECTION 3: Con	nposition/informati	ion on in	gredients		
one	CAS: 2634-33-5		Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	
IPBC	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
isoproturon (ISO)	EC: 251-835-4 CAS: 34123-59-6 Index: 006-044-00-7	≤0.05	Carc. 2, H351 STOT RE 2, H373 (blood) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 10 M [Chronic] = 10	[1]
terbutryn	EC: 212-950-5 CAS: 886-50-0	≤0.016	Acute Tox. 4, H302 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 100 M [Chronic] = 100	[1]
CMIT/MIT(3:1)	REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: 0.06% $\le C < 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: 0.06% $\le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.	, , ,	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>ı ype</u>

- [1] Substance classified with a physical, health or environmental hazard
- [2] Substance with a workplace exposure limit

 Date of issue/Date of revision
 : 27-1-2024
 Version
 : 1

 Date of previous issue
 : No previous validation
 3/19
 AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses if easy to do. Get medical

attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision : 27-1-2024 Version : 1

Date of previous issue : No previous validation 4/19

SMOOTH MASONRY PAINT STRONG BASE

SECTION 5: Firefighting measures

Hazards from the substance or mixture In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

: 27-1-2024 Date of issue/Date of revision Version : 1

AkzoNobel Date of previous issue : No previous validation 5/19

SMOOTH MASONRY PAINT STRONG BASE

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available. Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes.
	TWA: 67.5 mg/m³ 8 hours.
	STEL: 101.2 mg/m³ 15 minutes.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

: 27-1-2024 Date of issue/Date of revision Version : 1 **AkzoNobel** Date of previous issue : No previous validation 6/19

SMOOTH MASONRY PAINT STRONG BASE

SECTION 8: Exposure controls/personal protection

ONEL ONEL ONEL ONEL	Long term Oral Long term Inhalation Short term Inhalation Short term Dermal	6.25 mg/ kg bw/day 67.5 mg/m³		Systemic Local
ONEL	Inhalation Short term Inhalation	67.5 mg/m ³ 101.2 mg/	Workers	Local
ONEL	Inhalation Short term Inhalation	101.2 mg/		Local
ONEL	Short term Inhalation			
ONEL	Inhalation			
			Workers	Local
	Short term Dermal	m³		
ONEL		0.004 mg/	General	Local
ONEL		cm²	population	
	Long term Dermal	0.004 mg/	General	Local
		cm ²	population	
DNEL	Short term Dermal	0.008 mg/	Workers	Local
		cm ²		
DNEL	Long term Dermal	0.008 mg/	Workers	Local
		cm ²		
NEL	Long term Oral	0.18 mg/	General	Systemic
		kg bw/day	population	
NEL	Short term Oral	0.5 mg/kg	General	Systemic
		bw/day	population	-
DNEL	Short term	0.6 mg/m ³	General	Local
	Inhalation		population	
DNEL	Long term	0.6 mg/m³	General	Systemic
	Inhalation		population	
DNEL	Long term Dermal	0.7 mg/kg	General	Systemic
			population	
DNEL		1.8 mg/m³		Systemic
DNEL	Long term Dermal		Workers	Systemic
		•		
DNEL	Short term Dermal			Systemic
DNEL		2.5 mg/m³	Workers	Local
DNEL		2.5 mg/m ³	Workers	Local
		3.5 mg/m ³	Workers	Systemic
NEL	Short term Dermal		Workers	Systemic
	01 11		147 1	
NEL		10.5 mg/m ³	vvorkers	Systemic
		0.045	0 1	
NEL	Long term Dermal			Systemic
, I	Lammatanii D			0
NEL	Long term Dermal		vvorkers	Systemic
NIE!	l and tarm		Conoral	Cyctors:
JNEL	0	ı.∠ mg/m³		Systemic
ואורי		6 01 m = /3		Cyntomic
JNEL		o.o i mg/m ³	vvoikeis	Systemic
ואו⊏י		0.022 ma/	Markers	Systemia
JINEL			VVOIKEIS	Systemic
ואו⊏ו			Workers	Systemic
JINEL		0.07 Hig/III°	MACIVEIZ	Systerric
VIE!		1 16 ma/m3	Morkors	Local
JNEL		1. 10 mg/m ³	vvoikers	Local
ואורי		1 16	Morkers	Loos
JNEL		i. io mg/m ³	vvorkers	Local
l		2 mg/kg	Workers	Systemic
10/16-1	Long torm Dormal	2 1111 1/K/11	VVUIKEIS	LOVSIEHHIC:
DNEL	Long term Dermal	bw/day		7,5.511110
	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	NEL Short term Oral NEL Short term Inhalation NEL Cong term Dermal NEL Short term Inhalation NEL Short term Inhalation NEL Short term Dermal NEL Short term Dermal NEL Short term Dermal NEL Short term Inhalation NEL Short term Inhalation NEL Short term Inhalation NEL Cong term Dermal NEL Short term Dermal NEL Cong term Dermal NEL Short term Dermal NEL Short term Dermal NEL Cong term Inhalation	DNEL Long term Oral 0.18 mg/kg bw/day 0.5 mg/kg bw/day 0.5 mg/kg bw/day 0.6 mg/m³ Inhalation 0.7 mg/kg bw/day 0.7 mg/kg bw/day 0.8 mg/m³ Inhalation 0.7 mg/kg bw/day 0.8 mg/m³ Inhalation 0.7 mg/kg bw/day 0.8 mg/m³ Inhalation 0.8 mg/m³ Inhala	Consider Moral Consider May be widely population of General popula

Date of issue/Date of revision: 27-1-2024VersionDate of previous issue: No previous validation7/19

AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 8: Exposure controls/personal protection						
CMIT/MIT(3:1)	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local	
	DNEL	Long term Inhalation	0.02 mg/m ³		Local	
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local	
	DNEL	Short term Inhalation	0.04 mg/m ³	Workers	Local	
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic	
	DNEL	Short term Oral	0.11 mg/	General	Systemic	

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

kg bw/day

population

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision: 27-1-2024Version: 1Date of previous issue: No previous validation8/19AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 8: Exposure controls/personal protection

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust

ventilation, suitable respiratory protective equipment should be used.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Color : Yellow.

Odor : Characteristic.

Odor threshold : Not available.

Melting point/freezing point : Not available.

Boiling point, initial boiling : 100°C (212°F)

point, and boiling range

Flamma billita

Flammability
Lower and upper explosion

: Not available.

limit

iiriit

: Not available.

Flash point

: Not available.

Auto-ignition temperature

Ingredient name	°C	°F	Method
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794
2-(2-methoxyethoxy)ethanol	215	419	DIN 51794
2,2' -oxybisethanol	229	444.2	DIN EN 14522-S

Decomposition temperature: Not available.

pH : 8 [Conc. (% w/w): 100%] [DIN EN 1262]

Viscosity : Kinematic (room temperature): 555 mm²/s [DIN EN ISO 3219]

Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Solubility(ies) :

Media	Result
cold water	Soluble [OESO (TG 105)]

Partition coefficient: n-octanol/: Not applicable.

water

Vapor pressure :

Date of issue/Date of revision: 27-1-2024Version: 1Date of previous issue: No previous validation9/19AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 9: Physical and chemical properties

	V	Vapor Pressure at 20°C			apor pres	sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ammonia	360.03	48				
methyl methacrylate	27.75	3.7				
glyoxal	15.15	2	EU A.4			

Density : 1.262 g/cm³ [DIN EN ISO 2811-1]

: 0

Vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10

μm

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1). May produce an allergic reaction.

Acute toxicity

 Date of issue/Date of revision
 : 27-1-2024
 Version
 : 1

 Date of previous issue
 : No previous validation
 10/19
 AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Intraperitoneal	Mouse	850 mg/kg	-
	LD50 Oral	Guinea pig	2 g/kg	-
	LD50 Oral	Guinea pig	2000 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	_
	LD50 Oral	Mouse	6050 mg/kg	_
	LD50 Oral	Mouse	4500 mg/kg	_
	LD50 Oral	Mouse	4500 mg/kg	_
	LD50 Oral	Rabbit	2200 mg/kg	_
	LD50 Oral	Rat	5660 mg/kg	_
	LD50 Oral	Rat	4500 mg/kg	_
	LD50 Oral	Rat	6050 mg/kg	_
	LD50 Oral	Rat	6050 mg/kg	_
	LD50 Route of exposure	Mouse	6050 mg/kg	_
	unreported	Wiodsc	0000 mg/kg	
	LD50 Route of exposure	Rat	4500 mg/kg	_
	unreported	Ital	4500 mg/kg	_
bronopol (INN)	LC50 Inhalation Dusts and	Rat	800 mg/m³	4 hours
bronopor (IIVIV)	mists	INAL	ooo mg/m	4 110015
	LD50 Dermal	Mouse	4750 mg/kg	
	LD50 Dermal	Rat	64 mg/kg	_
	LD50 Definal	Mouse	32.8 mg/kg	_
		Mouse	15500 µg/kg	_
	LD50 Intraperitoneal	Rat		-
	LD50 Intraperitoneal		22 mg/kg	-
	LD50 Intraperitoneal	Rat	26 mg/kg	-
	LD50 Intravenous	Mouse	48 mg/kg	-
	LD50 Intravenous	Rat	37400 µg/kg	-
	LD50 Oral	Mouse	270 mg/kg	-
	LD50 Oral	Mouse	194 mg/kg	-
	LD50 Oral	Rabbit	190 mg/kg	-
	LD50 Oral	Rat	180 mg/kg	-
	LD50 Oral	Rat	267 mg/kg	-
	LD50 Oral	Rat	254 mg/kg	-
	LD50 Oral	Rat	342 mg/kg	-
	LD50 Subcutaneous	Mouse	116 mg/kg	-
	LD50 Subcutaneous	Rat	170 mg/kg	-
	LD50 Subcutaneous	Rat	200 mg/kg	-
1,2-benzisothiazol-3(2H)-	LD50 Oral	Mouse	1150 mg/kg	-
one	L DEC Orol	Pot	1020 mg/kg	
IDDC	LD50 Oral LD50 Oral	Rat	1020 mg/kg	-
IPBC		Rat	1470 mg/kg	-
terbutryn	LD50 Dermal	Rabbit	>10200 mg/kg	-
	LD50 Intraperitoneal	Mouse	554 mg/kg	-
	LD50 Intraperitoneal	Rat	699 mg/kg	-
	LD50 Oral	Mouse	3884 mg/kg	-
	LD50 Oral	Rat	2045 mg/kg	-

Conclusion/Summary

: Not available.

Acute toxicity estimates

Date of issue/Date of revision : 27-1-2024 Version : 1 **AkzoNobel** Date of previous issue 11/19 : No previous validation

SMOOTH MASONRY PAINT STRONG BASE

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
bronopol (INN)	500	1100	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	500	N/A	N/A	N/A	0.05
IPBC	500	N/A	N/A	N/A	0.5
terbutryn	500	N/A	N/A	N/A	N/A
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Eyes - Severe irritant	Rabbit	-	20 mg	-
bronopol (INN)	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Rabbit	-	80 mg	-
terbutryn	Eyes - Moderate irritant	Rabbit	-	76 mg	-
	Skin - Mild irritant	Rabbit	-	380 mg	-

Conclusion/Summary

Sensitization

Conclusion/Summary

: Not available.

: Not available.

Mutagenicity

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

Teratogenicity
Conclusion/Summar

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bronopol (INN)	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
IPBC	Category 1	-	larynx
isoproturon (ISO)	Category 2	-	blood

Aspiration hazard

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact : No known significant effects or critical hazards.Inhalation : No known significant effects or critical hazards.

Date of issue/Date of revision : 27-1-2024 Version : 1

Date of previous issue : No previous validation 12/19 AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 11: Toxicological information

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
2-(2-butoxyethoxy)ethanol		Fish - Lepomis macrochirus	96 hours
	Acute LC50 2000000 µg/l Marine water	Fish - Menidia beryllina	96 hours
bronopol (INN)	Acute EC50 0.02 ppm Fresh water	Algae - Desmodesmus subspicatus	96 hours
	Acute EC50 0.41 ppm Fresh water	Algae - Navicula pelliculosa	96 hours
	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.18 ppm Marine water Acute EC50 1.6 ppm Fresh water	Algae - Skeletonema costatum Daphnia - Daphnia magna	96 hours 48 hours

Date of previous issue : No previous validation 13/19 AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

	SMOOTH MASONRY PAINT STRONG BASE				
S	ECTION 12: Ecologi	ical information			
		Acute LC50 36 ppm Fresh water	Fish - Lepomis macrochirus	96 hours	
		Acute LC50 11.17 ppm Fresh water	Fish - Lepomis macrochirus	96 hours	
		Acute LC50 41.5 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 20 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 26.4 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days	
		Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days	
	1,2-benzisothiazol-3(2H)-one	• •	Daphnia - Daphnia magna	48 hours	
	,	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours	
		_	dubia		
		Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours	
		Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
	IPBC	Acute EC50 956 ppb Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute EC50 0.16 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours	
		Acute LC50 2920 ppb Marine water	Crustaceans - Neomysis mercedis - Adult	48 hours	
		Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute LC50 95 ppb Marine water	Fish - Oncorhynchus kisutch -	96 hours	
			Juvenile (Fledgling, Hatchling, Weanling)		
		Acute LC50 100 ppb Fresh water	Fish - Oncorhynchus mykiss -	96 hours	
			Juvenile (Fledgling, Hatchling,		
			Weanling)		
		Acute LC50 72 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 67 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours	
		Acute LC50 67 μg/l Fresh water	Fish - Oncorhynchus mykiss -	96 hours	
			Juvenile (Fledgling, Hatchling, Weanling)		
		Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days	
	terbutryn	Acute EC50 3.1 µg/l Marine water	Algae - Dunaliella tertiolecta	96 hours	
		Acute EC50 0.1 μg/l Fresh water	Algae - Fragilaria capucina ssp. rumpens	96 hours	
		Acute EC50 2 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours	
		Acute EC50 3.3 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours	
		Acute EC50 2.7 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours	
		Acute EC50 2.66 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute EC50 7100 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
		Acute LC50 579.3 mg/l Fresh water	Crustaceans - Pacifastacus	48 hours	
			leniusculus - Juvenile (Fledgling, Hatchling, Weanling)		
		A	Fig. 6	00.1	

Conclusion/Summary

: Not available.

Acute LC50 1400 µg/l Fresh water

Acute LC50 1.5 ppm Marine water

Acute LC50 2.4 ppm Fresh water

Acute LC50 0.82 ppm Fresh water

Acute LC50 1800 µg/l Fresh water

12.2 Persistence and degradability

Date of issue/Date of revision	: 27-1-2024	Version :1	
Date of previous issue	: No previous validation	14/19	AkzoNobel

96 hours

96 hours

96 hours

96 hours

96 hours

Fish - Carassius carassius

Fish - Cyprinodon variegatus

Fish - Oncorhynchus mykiss

Fish - Oncorhynchus mykiss

Fish - Oncorhynchus mykiss

SMOOTH MASONRY PAINT STRONG BASE

SECTION 12: Ecological information

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	low
bronopol (INN)	0.18	-	low
isoproturon (ISO)	2.87	-	low
terbutryn	3.74	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue/Date of revision	: 27-1-2024	Version :1	
Date of previous issue	: No previous validation	15/19	AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 13: Disposal considerations

Disposal considerations

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

: This material and its container must be disposed of in a safe way. Care should be Special precautions

taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations

Date of issue/Date of revision : 27-1-2024 Version : 1

AkzoNobel Date of previous issue : No previous validation 16/19

SMOOTH MASONRY PAINT STRONG BASE

SECTION 15: Regulatory information

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

VOC for Ready-for-Use

Mixture

: Not available.

Industrial emissions

(integrated pollution prevention and control) -

: Not listed

Air

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Biocidal products regulation

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety

Assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

Date of issue/Date of revision : 27-1-2024 Version : 1

Date of previous issue : No previous validation 17/19 AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 16: Other information

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

	1
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
	EXPOSURE) - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
	EXPOSURE) - Category 2
1	, , , , , , , , , , , , , , , , , , , ,

Date of issue/Date of revision : 27-1-2024 Version : 1

Date of previous issue : No previous validation

18/19

AkzoNobel

SMOOTH MASONRY PAINT STRONG BASE

SECTION 16: Other information

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

Date of printing : 27-1-2024 Date of issue/ Date of : 27-1-2024

revision

Date of previous issue : No previous validation

Version : ´

Unique ID : DA7DF488320C1EEEAF931BEB6DB8C33D

Notice to reader

Date of issue/Date of revision : 27-1-2024 Version : 1

Date of previous issue : No previous validation 19/19 AkzoNobel