

# **SAFETY DATA SHEET**

VINYL SILK WHITE

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : VINYL SILK WHITE

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Consumer use
Uses advised against
None

Product use

: Waterborne coating for interior use.

#### 1.3 Details of the supplier of the safety data sheet

ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 70 70 www.armsteadtrade.co.uk

e-mail address of person : armstead.advice@akzonobel.com responsible for this SDS

#### 1.4 Emergency telephone number

#### National advisory body/Poison Center

 Telephone number
 : +44 (0)344 892 0111

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Date of issue/Date of revision	: 8-11-2024	Version : 2	
Date of previous issue	: 26-1-2024	1/15	AkzoNobel

VINYL SILK WHITE

SECTION 2: Hazards identification				
Signal word	:	No signal word.		
Hazard statements	:	No known significant effects or critical hazards.		
Precautionary statements				
General	:	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.		
Prevention	:	P262 - Do not get in eyes, on skin, or on clothing.		
Response	:	P312 - Call a doctor if you feel unwell.		
Storage	:	Not applicable.		
Disposal	:	₱501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.		
Supplemental label elements	:	Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1) and 2-methyl-2H-isothiazol- 3-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.		
Special packaging requirem	er	<u>its</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.		
Tactile warning of danger	:	Not applicable.		
2.3 Other hazards				
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		
Other hazards which do not result in classification	:	None known.		

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

#### : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤15	Carc. 2, H351 (inhalation)	-	[1] [*]
1,2-benzisothiazol-3(2H)- one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = $0.05$ mg/l Skin Sens. 1, H317: C $\ge 0.05\%$ M [Acute] = 1	[1]
CMIT/MIT(3:1)	REACH #:	<0.0015	Acute Tox. 3, H301	ATE [Oral] = 100	[1]
Date of issue/Date of revision	: 8-11-2024		Version : 2		
Date of previous issue	: 26-1-2024		2/15	Akzo	Nobe

		VINYL SILK WH	IITE		
<b>SECTION 3: Compo</b>	sition/informati	on on in	gredients		
	01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5		Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	$\begin{array}{l} mg/kg \\ ATE [Dermal] = 50 \\ mg/kg \\ ATE [Inhalation \\ (dusts and mists)] \\ = 0.05 mg/l \\ Skin Corr. 1C, \\ H314: C ≥ 0.6\% \\ Skin Irrit. 2, H315: \\ 0.06\% \le C < 0.6\% \\ Eye Dam. 1, H318: \\ C ≥ 0.6\% \\ Eye Irrit. 2, H319: \\ 0.06\% \le C < 0.6\% \\ Skin Sens. 1, H317: \\ C ≥ 0.0015\% \\ M [Acute] = 100 \\ M [Chronic] = 100 \end{array}$	
2-methyl-2H-isothiazol- 3-one	REACH #: 01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = $0.05$ mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 10 M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a physical, health or environmental hazard

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix. Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures** 

#### 4.1 Description of first aid measures

Eye contact	eyelids. Check for and	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs.			
Inhalation		emove victim to fresh air and keep at rest in a position comfortable for breathing. et medical attention if symptoms occur.			
Skin contact		ush contaminated skin with plenty of water. Remove contaminated clothing and oes. Get medical attention if symptoms occur.			
Ingestion	person is conscious, g	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.			
Protection of first-aiders	: No action shall be take	en involving any personal risk or witho	out suitable training.		
Date of issue/Date of revision	: 8-11-2024	Version : 2			
Date of previous issue	: 26-1-2024	3/15	AkzoNobel		

VINYL SILK WHITE

# **SECTION 4: First aid measures**

	Over-exposure signs/symptoms					
Eye contact	: No specific data.					
Inhalation	: No specific data.					
Skin contact	: No specific data.					
Ingestion	: No specific data.					
4.3 Indication of any immedia	ate medical attention and special treatment needed					
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.					
Specific treatments	: No specific treatment.					
SECTION 5: Firefight	ting measures					
5.1 Extinguishing media						
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.					
Unsuitable extinguishing media	: None known.					
5.2 Special hazards arising fi	rom the substance or mixture					
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.					
substance or mixture Hazardous combustion	<ul> <li>In a fire or if heated, a pressure increase will occur and the container may burst.</li> <li>Decomposition products may include the following materials:</li> </ul>					
substance or mixture	<ul> <li>In a fire or if heated, a pressure increase will occur and the container may burst.</li> <li>Decomposition products may include the following materials: carbon dioxide</li> </ul>					
substance or mixture Hazardous combustion	<ul> <li>In a fire or if heated, a pressure increase will occur and the container may burst.</li> <li>Decomposition products may include the following materials:</li> </ul>					
substance or mixture Hazardous combustion products	<ul> <li>In a fire or if heated, a pressure increase will occur and the container may burst.</li> <li>Decomposition products may include the following materials: carbon dioxide carbon monoxide</li> </ul>					
substance or mixture Hazardous combustion products	<ul> <li>In a fire or if heated, a pressure increase will occur and the container may burst.</li> <li>Decomposition products may include the following materials: carbon dioxide carbon monoxide</li> </ul>					
substance or mixture Hazardous combustion products 5.3 Advice for firefighters Special protective actions	<ul> <li>In a fire or if heated, a pressure increase will occur and the container may burst.</li> <li>Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides</li> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident in there is a fire. No action shall be taken involving any personal risk or without</li> </ul>					

For non-emergency personnel	:	No action shall be taken involving any p Evacuate surrounding areas. Keep un entering. Do not touch or walk through protective equipment.	necessa	ry and unprotected	d personnel from
For emergency responders	:	If specialized clothing is required to dea information in Section 8 on suitable and information in "For non-emergency per	d unsuita		
6.2 Environmental precautions	:	Avoid dispersal of spilled material and drains and sewers. Inform the relevant environmental pollution (sewers, water	t authorit	ies if the product h	
Date of issue/Date of revision		: 8-11-2024	Version	:2	
Date of previous issue		: 26-1-2024	4/15		AkzoNobel

## **SECTION 6: Accidental release measures**

#### 6.3 Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

<b>Recommended monitoring</b> <b>procedures</b> : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectivenes of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such a the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace	Recommended monitoring procedures
---	-----------------------------------

Date of issue/Date of revision	: 8-11-2024	Version : 2	
Date of previous issue	: 26-1-2024	5/15	AkzoNobe

VINYL SILK WHITE

## **SECTION 8: Exposure controls/personal protection**

atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.2 mg/m <sup>3</sup>	General	Systemic
		Inhalation	$6.01 m g/m^{3}$	population	Sustamia
	DNEL	Long term Inhalation	6.81 mg/m <sup>3</sup>	vvorkers	Systemic
CMIT/MIT(3:1)	DNEL	Long term	0.02 mg/m <sup>3</sup>	General	Local
	DINLL	Inhalation	0.02 mg/m	population	LUCAI
	DNEL	Long term	0.02 mg/m <sup>3</sup>		Local
	DITE	Inhalation	0.02 mg/m		Loodi
	DNEL	Short term	0.04 mg/m <sup>3</sup>	General	Local
		Inhalation	<b>-</b> -	population	
	DNEL	Short term	0.04 mg/m <sup>3</sup>	Workers	Local
		Inhalation	_		
	DNEL	Long term Oral	0.09 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term Oral	0.11 mg/	General	Systemic
			kg bw/day	population	
2-methyl-2H-isothiazol-3-one	DNEL	Long term	0.021 mg/	General	Local
		Inhalation	$m^3$	population	
	DNEL	Long term Inhalation	0.021 mg/ m³	Workers	Local
	DNEL	Long term Oral	0.027 mg/	General	Systemic
	DINLL	Long term Oral	kg bw/day	population	Systemic
	DNEL	Short term	0.043 mg/	General	Local
		Inhalation	m <sup>3</sup>	population	2000
	DNEL	Short term	0.043 mg/	Workers	Local
		Inhalation	m <sup>3</sup>		
	DNEL	Short term Oral	0.053 mg/	General	Systemic
			kg bw/day	population	

#### PNECs

No PNECs available.

#### 8.2 Exposure controls

Appropriate engineering<br/>controls: Good general ventilation should be sufficient to control worker exposure to airborne<br/>contaminants.

#### Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



	VINYL SILK WHITE
SECTION 8: Exposur	e controls/personal protection
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness $\geq$ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness $\geq$ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Wear a Approved/certified disposable particulate dust mask.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: White.
Odor	: Characteristic.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)

Date of issue/Date of revision	: 8-11-2024	Version : 2	
Date of previous issue	: 26-1-2024	7/15	AkzoNobel

# SECTION 9: Physical and chemical properties

÷

Flammability	: Not available.
Lower and upper explosion limit	: Not available.
Flash point	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
рН	: 8 [Conc. (% w/w): 100%] [DIN EN 1262]
Viscosity	: Kinematic (room temperature): 619 mm²/s [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

#### Solubility(ies)

Solubility(les)	•
Media	Result
cold water	Soluble [OECD (TG 105)]
Partition coefficient: n-octa	ol/ : Not applicable.
Vapor pressure	: Not available.
Relative density	: 1.135
Vapor density	: Not available.
Particle characteristics	
Median particle size	: Not applicable.
Percentage of particles wit aerodynamic diameter ≤ 10 µm	: 0
Minimum ignition energy (m	J) : Not available.
Fundamental burning veloc	
SADT	: Not available.
Heat of combustion	: Not available.
Aerosol product	
Type of aerosol	: Not applicable.
SECTION 10: Stabilit	and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

VINYL SILK WHITE

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
√,2-benzisothiazol-3(2H)- one	LD50 Oral	Mouse	1150 mg/kg	-
	LD50 Oral	Rat	1020 mg/kg	-

**Conclusion/Summary** : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
√2-benzisothiazol-3(2H)-one	500	N/A	N/A	N/A	0.05
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.05

#### Irritation/Corrosion

Conclusion/Summary	: Not available.
<b>Sensitization</b>	
<b>Conclusion/Summary</b>	: Not available.
<u>Mutagenicity</u>	
<b>Conclusion/Summary</b>	: Not available.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.
Specific target organ toxici	<u>ity (single exposure)</u>
Not available.	

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

#### Information on the likely : Not available. routes of exposure

# Potential acute health effectsEye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision	: 8-11-2024	Version : 2	
Date of previous issue	: 26-1-2024	9/15	AkzoNobel

VINYL SILK WHITE

<b>SECTION 11: Toxico</b>	logical information
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Date of issue/Date of revision	: 8-11-2024	Version :2	
Date of previous issue	: 26-1-2024	10/15	AkzoNobel

2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.3 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 0.19 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

**Conclusion/Summary** : Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

#### 12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
<ul> <li>Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.</li> </ul>
: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

	Waste code	Waste designation		
	EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11		
Da	te of issue/Date of revision	: 8-11-2024	Version : 2	
Da	te of previous issue	: 26-1-2024	11/15	AkzoNobel

# SECTION 13: Disposal considerations

Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	<ul> <li>Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.</li> </ul>
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not applicable.
according to IMO	
instruments	

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB) /REACH</u>

Annex XIV - List of substances subject to authorization

#### <u>Annex XIV</u>

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

VINYL SILK WHITE

## **SECTION 15: Regulatory information**

CECTION 10. Regula		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles <u>Other EU regulations</u>	: Not applicable.	
VOC	: Not available.	
VOC for Ready-for-Use Mixture	: Not applicable.	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed	
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed	
Ozone depleting substances (1005/2009/EU) Not listed.		
Prior Informed Consent (PIC) (649/2012/EU) Not listed.		
Persistent Organic Pollutants Not listed.		
Seveso Directive		
This product is not controlled	I under the Seveso Directive.	
Biocidal products regulation	on	
Active substances		
Ingredient name		
7,2-benzisothiazol-3(2H)-o	ne	
bronopol 2,2-dibromo-2-cyanoaceta	mide	
ethanol		
CMIT/MIT(3:1) 2-methyl-2H-isothiazol-3-or	ne	
International regulations		

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.



VINYL SILK WHITE

## **SECTION 15: Regulatory information**

15.2 Chemical Safety Assessment

: No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.			
Abbreviations and	: ATE = Acute Toxicity Estimate		
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]		
	DMEL = Derived Minimal Effect Level		
	DNEL = Derived No Effect Level		
	EUH statement = CLP-specific Hazard statement		
	N/A = Not available		
	PBT = Persistent, Bioaccumulative and Toxic		
	PNEC = Predicted No Effect Concentration		
	RRN = REACH Registration Number		
	SGG = Segregation Group		
	vPvB = Very Persistent and Very Bioaccumulative		

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
Full text of classifications [CLP/0	<u>HS]</u>
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A		SERIOUS ETE DAMAGE/ ETE IRRITATION - SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A	B C
Date of printing	: 8-11-2024		
Date of issue/ Date of revision	: 8-11-2024		
Date of previous issue	: 26-1-2024		
Version	: 2		
Date of issue/Date of revision	: 8-11-2024	Version : 2	
Date of previous issue	: 26-1-2024	14/15	AkzoNobel

# **SECTION 16: Other information**

Unique ID

: BB61C204F4D31EEFA7B819D13954C75C

#### Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

