

SAFETY DATA SHEET

MOULDSHIELD FUNGICIDAL MATT LIGHT BASE

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: MOULDSHIELD FUNGICIDAL MATT LIGHT BASE

1.2 Relevant identified uses of the substance or mixture and uses advised against

	-
	Identified uses
Professional use Consumer use	
	Uses advised against
None	
Product use	: Waterborne coating for interior use.
.3 Details of the supplier of	the safety data sheet
ICI Paints AkzoNobe Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 www.duluxtrade.co.u	2 70 70
e-mail address of person responsible for this SDS	: duluxtrade.advice@akzonobel.com
.4 Emergency telephone nu	Imber
National advisory body/Poi	son Center
Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	:Emergency Telephone : Slough +44 (0) 1753 550000



SECTION 2: Hazards identification

2.1 Classification of the subs	ance or mixture
Product definition	: Mixture
Classification according to Aquatic Chronic 3, H412	Regulation (EC) No. 1272/2008 [CLP/GHS]
The product is classified as h	zardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the full tex	of the H statements declared above.
See Section 11 for more deta	ed information on health effects and symptoms.
2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
General	: P102 - Keep out of reach of children.
	P101 - If medical advice is needed, have product container or label at hand.
Prevention	: P273 - Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Contains 3-iodo-2-propynyl butylcarbamate and CMIT/MIT(3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
Special packaging requiren	ents
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.
SECTION 3: Compos	ition/information on ingredients

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture



MOULDSHIELD FUNGICIDAL MATT LIGHT BASE

SECTION 3: Composition/information on ingredients Specific Conc. % Product/ingredient name Identifiers Classification Туре Limits, M-factors and ATEs ≥10 - ≤15 Carc. 2, H351 titanium dioxide REACH #: [1] [*] 01-2119489379-17 (inhalation) EC: 236-675-5 CAS: 13463-67-7 **IPBC** ≤0.3 Acute Tox. 4, H302 ATE [Oral] = 500 EC: 259-627-5 [1] Acute Tox. 3, H331 CAS: 55406-53-6 mg/kg ATE Inhalation Index: 616-212-00-7 Eye Dam. 1, H318 Skin Sens. 1, H317 (dusts and mists)] STOT RE 1, H372 = 0.5 mg/lM [Acute] = 10 (larynx) Aquatic Acute 1, H400 M [Chronic] = 1 Aquatic Chronic 1, H410 ≤0.1 bronopol (INN) EC: 200-143-0 Acute Tox. 4, H302 ATE [Oral] = 500 [1] Acute Tox. 4, H312 mg/kg CAS: 52-51-7 Skin Irrit. 2, H315 ATE [Dermal] = Index: 603-085-00-8 Eye Dam. 1, H318 1100 mg/kg STOT SE 3, H335 M [Acute] = 10 Aquatic Acute 1, H400 < 0.0015 Acute Tox. 3, H301 CMIT/MIT(3:1) REACH #: ATE [Oral] = 100 [1] 01-2120764691-48 Acute Tox. 2, H310 mg/kg Acute Tox. 2, H330 ATE [Dermal] = 50 EC: 911-418-6 Skin Corr. 1C, H314 mg/kg CAS: 55965-84-9 Index: 613-167-00-5 Eye Dam. 1, H318 ATE [Inhalation Skin Sens. 1A, H317 (dusts and mists)] Aquatic Acute 1, H400 = 0.05 mg/lAquatic Chronic 1, Skin Corr. 1C, H410 H314: C ≥ 0.6% EUH071 Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

[1] Substance classified with a physical, health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision	: 26-1-2024	Version :1	
Date of previous issue	: No previous validation	3/17	AkzoNobel

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate, CMIT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the	:	In a fire or if heated, a pressure increase will occur and the container may burst.
substance or mixture		This material is harmful to aquatic life with long lasting effects. Fire water
		contaminated with this material must be contained and prevented from being
		discharged to any waterway, sewer or drain.

Date of issue/Date of revision	: 26-1-2024	Version : 1	
Date of previous issue	: No previous validation	4/17	AkzoNobel

		MOULDSHIELD FUNGICIDAL MATT LIGHT BASE
SECTION 5: Firefight	in	g measures
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
SECTION 6: Accident	ta	l release measures
6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materials fo	r c	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

	· · · · · · · · · · · · · · · · · · ·
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from
	upwind. Prevent entry into sewers, water courses, basements or confined areas.
	Wash spillages into an effluent treatment plant or proceed as follows. Contain and
	collect spillage with non-combustible, absorbent material e.g. sand, earth,
	vermiculite or diatomaceous earth and place in container for disposal according to
	local regulations. Dispose of via a licensed waste disposal contractor.
	Contaminated absorbent material may pose the same hazard as the spilled product.

: See Section 1 for emergency contact information. 6.4 Reference to other See Section 8 for information on appropriate personal protective equipment. sections See Section 13 for additional waste treatment information.

licensed waste disposal contractor.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be bazardous. Do not reuse container
	containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date of revision	: 26-1-2024	Version :1	-
Date of previous issue	: No previous validation	5/17	AkzoN



SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective
	equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3	Specific	end	use(s)
-----	----------	-----	--------

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	е Туре	Exposure	Value	Population	Effects
IPBC	DNEL	Long term Inhalation	0.023 mg/ m ³	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m ³	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
bronopol (INN)	DNEL	Short term Dermal	0.004 mg/ cm²	General population	Local
	DNEL	Long term Dermal	0.004 mg/ cm²	General population	Local
	DNEL	Short term Dermal	0.008 mg/	Workers	Local
te of issue/Date of revision	: 26-1-2024		Version	:1	
te of previous issue	: No previous va	lidation	6/17		AkzoNobel

SECTION 8: Exposure controls/personal protection cm² DNEL Long term Dermal 0.008 mg/ Workers Local cm² DNEL 0.18 mg/ General Systemic Long term Oral kg bw/day population DNEL Short term Oral 0.5 mg/kg Systemic General bw/day population 0.6 mg/m³ DNEL Short term General Local Inhalation population DNEL Long term 0.6 mg/m³ Systemic General Inhalation population DNEL Long term Dermal 0.7 mg/kg General Systemic bw/day population Short term 1.8 mg/m³ DNEL General Systemic Inhalation population DNEL Long term Dermal 2 mg/kg Workers Systemic bw/dav DNEL Short term Dermal 2.1 mg/kg General Systemic bw/day population DNEL Short term 2.5 mg/m³ Workers Local Inhalation DNEL Long term 2.5 mg/m³ Workers Local Inhalation DNEL Long term 3.5 mg/m³ Workers Systemic Inhalation DNEL Short term Dermal 6 mg/kg Workers Systemic bw/day DNEL Short term 10.5 mg/m³ Workers Systemic Inhalation DNEL CMIT/MIT(3:1) Long term Local 0.02 mg/m³ General Inhalation population Workers DNEL Long term Local 0.02 mg/m³ Inhalation DNEL 0.04 mg/m³ Short term General Local Inhalation population Workers DNEL Short term 0.04 mg/m³ Local Inhalation DNEL Long term Oral 0.09 mg/ General Systemic kg bw/day population DNEL Short term Oral 0.11 mg/ General Systemic kg bw/day population

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.
	Wash contaminated clothing before reusing. Ensure that eyewash stations and
	safety showers are close to the workstation location.



SECTION 8: Exposur	ontrols/personal protection			
Eye/face protection	Safety eyewear complying with an approved standard should be used when a riassessment indicates this is necessary to avoid exposure to liquid splashes, migases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses side-shields.	ists,		
Skin protection				
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard sh be worn at all times when handling chemical products if a risk assessment indic this is necessary. Considering the parameters specified by the glove manufact check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	cates turer,		
	When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness \geq 0.38 mm When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness \geq 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glomaterial.	r		
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.			
	The user must check that the final choice of type of glove selected for handling product is the most appropriate and takes into account the particular conditions use, as included in the user's risk assessment.			
Body protection	Personal protective equipment for the body should be selected based on the ta being performed and the risks involved and should be approved by a specialist before handling this product.			
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should approved by a specialist before handling this product.	be		
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importances of use. Dry sanding, flame cutting and/or welding of the dry paint film vigive rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhavementilation, suitable respiratory protective equipment should be used.	rtant will		
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation In some cases, fume scrubbers, filters or engineering modifications to the proce equipment will be necessary to reduce emissions to acceptable levels.			

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Date of issue/Date of revision Date of previous issue	: 26-1-2024 : No previous validation	Version : 1 8/17	AkzoNobel
Melting point/freezing point	: Not available.		
Odor threshold	: Not available.		
Odor	: Characteristic.		
Color	: White.		
Physical state	: Liquid.		
<u>Appearance</u>			

MOULDSHIELD FUNGICIDAL MATT LIGHT BASE

Boiling point, initial boiling point, and boiling range	: 1(00°C (212°F)		
Flammability	: N	ot available.		
Lower and upper explosion limit		reatest known rar ith 2,2,4-trimethyl		Jpper: 4.2% (isobutyric acid, monoester
Flash point	: N	ot available.		
Auto-ignition temperature	:			
Ingredient name		°C	°F	Method
2-ethylhexyl acrylate		252	485.6	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol		393	739.4	
methyl methacrylate		400	752	DIN 51794
Decomposition temperature	: N	ot available.		
рН	: 8	[Conc. (% w/w): 1	00%] [DIN EN 126	2]
Viscosity	: Kinematic (room temperature): 509 mm²/s [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]			

Solubility(ies)

Solubility(ies	:
Media	Result
cold water	Soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

:

water

Vapor pressure

	V	apor Press	ure at 20°C	re at 20°C Vapor pressure at 5		sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ammonia	360.03	48				
methyl methacrylate	27.75	3.7				
m-xylene	6	0.8				
Relative density	: 1.37	77				
Vapor density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				
Percentage of particles with aerodynamic diameter \leq 10 μ m	n :0					

SECTION 10: Stability and reactivity

Date of issue/Date of revision	: 26-1-2024	Version :1	AkzoNobel
10.4 Conditions to avoid	: No specific data.		
10.3 Possibility of hazardous reactions	: Under normal conditions of st	orage and use, hazardous reac	tions will not occur.
10.2 Chemical stability	: The product is stable.		
10.1 Reactivity	: No specific test data related t	o reactivity available for this pro	duct or its ingredients.

SECTION 10: Stability and reactivity

10.5 Incompatible materials : No specific data.

10.6 Hazardous: Under normal conditions of storage and use, hazardous decomposition productsdecomposition productsshould not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate, CMIT/MIT(3:1). May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
IPBC	LD50 Oral	Rat	1470 mg/kg	-
bronopol (INN)	LC50 Inhalation Dusts and mists	Rat	800 mg/m³	4 hours
	LD50 Dermal	Mouse	4750 mg/kg	-
	LD50 Dermal	Rat	64 mg/kg	-
	LD50 Intraperitoneal	Mouse	32.8 mg/kg	-
	LD50 Intraperitoneal	Mouse	15500 µg/kg	-
	LD50 Intraperitoneal	Rat	22 mg/kg	-
	LD50 Intraperitoneal	Rat	26 mg/kg	-
	LD50 Intravenous	Mouse	48 mg/kg	-
	LD50 Intravenous	Rat	37400 µg/kg	-
	LD50 Oral	Mouse	270 mg/kg	-
	LD50 Oral	Mouse	194 mg/kg	-
	LD50 Oral	Rabbit	190 mg/kg	-
	LD50 Oral	Rat	180 mg/kg	-
	LD50 Oral	Rat	267 mg/kg	-
	LD50 Oral	Rat	254 mg/kg	-
	LD50 Oral	Rat	342 mg/kg	-
	LD50 Subcutaneous	Mouse	116 mg/kg	-
	LD50 Subcutaneous	Rat	170 mg/kg	-
	LD50 Subcutaneous	Rat	200 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates



SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	N/A	N/A	N/A	N/A	248.8
IPBC	500	N/A	N/A	N/A	0.5
bronopol (INN)	500	1100	N/A	N/A	N/A
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bronopol (INN)	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Rabbit	-	80 mg	-
Conclusion/Summary	: Not available.				
<u>Sensitization</u>					
Conclusion/Summary	: Not available.				
Mutagenicity					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
Teratogenicity					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>y (single exposure)</u>				

Product/ingredient name	Category	Route of exposure	Target organs
bronopol (INN)	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
IPBC	Category 1	-	larynx

Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
-------------	---------------------

Date of issue/Date of revision	: 26-1-2024	Version :1	
Date of previous issue	: No previous validation	11/17	AkzoNobel

SECTION 11: Toxicological information			
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delayed and immediate effect	ts and also chronic effects from short and long term exposure		
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
<u>Long term exposure</u>			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health eff	ects		
Not available.			
Conclusion/Summary	: Not available.		
General	: No known significant effects or critical hazards.		
Carcinogenicity	: No known significant effects or critical hazards.		

: No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Mutagenicity

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
IPBC	Acute EC50 956 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.16 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 2920 ppb Marine water	Crustaceans - Neomysis mercedis - Adult	48 hours
	Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 95 ppb Marine water	Fish - Oncorhynchus kisutch - Juvenile (Fledgling, Hatchling, Weanling)	
	Acute LC50 100 ppb Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	
	Acute LC50 72 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 µg/l Fresh water	Fish - Oncorhynchus mykiss -	96 hours
Date of issue/Date of revision	: 26-1-2024	Version : 1	
Date of previous issue	: No previous validation	12/17	AkzoNobel

SECTION 12: Ecological information

	•		
		Juvenile (Fledgling, Hatchling,	
		Weanling)	
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days
bronopol (INN)	Acute EC50 0.02 ppm Fresh water	Algae - Desmodesmus	96 hours
		subspicatus	
	Acute EC50 0.41 ppm Fresh water	Algae - Navicula pelliculosa	96 hours
	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella	96 hours
		subcapitata	
	Acute EC50 0.18 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 36 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 11.17 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 41.5 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 20 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 26.4 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days
	Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary	: Not available.
--------------------	------------------

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
bronopol (INN)	0.18	-	low

12.4 Mobility	in soil
---------------	---------

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product



SECTION 13: Disposal considerations

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. 	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 14: Transport information

14.7 Transport in bulk: Not applicable.according to IMOinstruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB) /REACH</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

None of the components a	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: Not available.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substanc Not listed.	<u>es (1005/2009/EU)</u>
Prior Informed Consent (P Not listed.	IC) (649/2012/EU)
Persistent Organic Polluta Not listed.	<u>nts</u>
Seveso Directive This product is not controlled Biocidal products regulation International regulations	d under the Seveso Directive. <u>on</u>
	ion List Schedules I, II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on F	Persistent Organic Pollutants

Date of issue/Date of revision	: 26-1-2024	Version :1	
Date of previous issue	: No previous validation	15/17	AkzoNobel

MOULDSHIELD FUNGICIDAL MATT LIGHT BASE

SECTION 15: Regulatory information

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety : No Chemical Safety Assessment has been carried out. **Assessment**

 SECTION 16: Other information Indicates information that has changed from previously issued version. 		

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.	
H226	Flammable liquid and vapor.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H310	Fatal in contact with skin.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H372	Causes damage to organs through prolonged or repeated	
	exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH071	Corrosive to the respiratory tract.	
	- 1 /	

Full text of classifications [CLP/GHS]



MOULDSHIELD FUNGICIDAL MATT LIGHT BASE

SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1	
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1	
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3	
Carc. 2	CARCINOGENICITY - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2	
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITIZATION - Category 1	
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A	
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED	
	EXPOSURE) - Category 1	
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -	
	Category 3	
Date of printing	: 26-1-2024	
Date of issue/ Date of	: 26-1-2024	
revision		
Date of previous issue	: No previous validation	
Version	: 1	
Unique ID	: DA7DF488320C1EEEAF8AB2721A3142FA	
Notice to reader		

