

SAFETY DATA SHEET

VINYL SOFT SHEEN MEDIUM BASE

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: VINYL SOFT SHEEN MEDIUM BASE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use	
Uses advised against	
None	

Product use

: Waterborne coating for interior use.

1.3 Details of the supplier of the safety data sheet

ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 70 70 www.duluxtrade.co.uk e-mail address of person : duluxtrade.advice@akzonobel.com

e-mail address of person : duluxtrade.advice@akzonobel.con responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +44 (0)344 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 1-7-2024	Version : 2	
Date of previous issue	: 28-1-2024	1/15	AkzoNobel

SECTION 2: Hazards identification

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
General	:	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	:	P262 - Do not get in eyes, on skin, or on clothing.
Response	:	P312 - Call a doctor if you feel unwell.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
Supplemental label elements	:	Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1) and 2-methyl-2H-isothiazol- 3-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤15	Carc. 2, H351 (inhalation)	-	[1] [*]
1,2-benzisothiazol-3(2H)- one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C $\ge 0.05\%$ M [Acute] = 1	[1]
Date of issue/Date of revision	: 1-7-2024		Version : 2		
Date of previous issue	: 28-1-2024		2/15	Akzol	Nobe

VINYL SOFT SHEEN MEDIUM BASE

SECTION 3: Compo	SECTION 3: Composition/information on ingredients					
CMIT/MIT(3:1)	REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: 0.06% $\le C < 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: 0.06% $\le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]	
3(2H)-Isothiazolone, 2-methyl-	REACH #: 01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 10 M [Chronic] = 1	[1]	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a physical, health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs. Remove victim to fresh air and keep at rest in a position comfortable for breathing.		
	Get medical attention if symptoms occ		
Skin contact :	Flush contaminated skin with plenty of shoes. Get medical attention if sympton	water. Remove contaminated clothing and oms occur.	
Ingestion :		I has been swallowed and the exposed ies of water to drink. Do not induce vomiting rsonnel. Get medical attention if symptoms	
Date of issue/Date of revision	: 1-7-2024	Version : 2	
Date of previous issue	: 28-1-2024	3/15 AkzoNobel	

VINYL SOFT SHEEN MEDIUM BASE

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

:	Use an extinguishing agent suitable for the surrounding fire.
:	None known.
om	the substance or mixture
:	In a fire or if heated, a pressure increase will occur and the container may burst.
:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
	: om :



VINYL SOFT SHEEN MEDIUM BASE

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for
	chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro-	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Date of issue/Date of revision	: 1-7-2024	Version : 2	
Date of previous issue	: 28-1-2024	5/15	AkzoNobel

VINYL SOFT SHEEN MEDIUM BASE

SECTION 7: Handling and storage

Recommendations : Not available. Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness procedures of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	6.81 mg/m ³	Workers	Systemic
		Inhalation			
CMIT/MIT(3:1)	DNEL	Long term	0.02 mg/m ³		Local
		Inhalation		population	
	DNEL	Long term	0.02 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Short term	0.04 mg/m ³		Local
		Inhalation		population	
	DNEL	Short term	0.04 mg/m ³	Workers	Local
	DNE	Inhalation	0.00	0	Our tamaia
	DNEL	Long term Oral	0.09 mg/	General	Systemic
		Charttern Oral	kg bw/day	population	Curatamia
	DNEL	Short term Oral	0.11 mg/	General	Systemic
3(2H)-Isothiazolone, 2-methyl-	DNEL	Long torm	kg bw/day 0.021 mg/	population General	Local
3(2H)-ISOUIIAZOIONE, 2-MEUTyi-	DINEL	Long term Inhalation	0.02 i ilig/ m ³	population	LUCAI
	DNEL	Long term	0.021 mg/	Workers	Local
	DINLL	Inhalation	0.02 i ilig/ m ³	VVUIKEIS	LUCAI
	DNEL	Long term Oral	0.027 mg/	General	Systemic
	DINEL	Long tonn ordi	kg bw/day	population	Cysternie
	DNEL	Short term	0.043 mg/	General	Local
	DITLE	Inhalation	m ³	population	Loodi
	DNEL	Short term	0.043 mg/	Workers	Local
		Inhalation	m ³		
	DNEL	Short term Oral	0.053 mg/	General	Systemic
e of issue/Date of revision :	1-7-2024		Version	:2	
e of previous issue :	28-1-2024		6/15		AkzoNob

Date of previous issue :28-1-2024 6/15

SECTION 8: Exposur			-	-			
					kg bw/day	population	
<u>PNECs</u>							
No PNECs available.							
8.2 Exposure controls							
Appropriate engineering controls		Good gen contamina		l ventilation should b	e sufficient to	o control worker e	xposure to airborne
Individual protection measu	res						
Hygiene measures		before ea Appropria Wash cor	ting te t itar	forearms and face t , smoking and using echniques should be ninated clothing befor rs are close to the w	the lavatory a used to remove reusing.	and at the end of ove potentially co Ensure that eyewa	the working period. ntaminated clothing
Eye/face protection	:	assessme gases or o	ent dus e as	ar complying with ar ndicates this is nece ts. If contact is poss sessment indicates	ssary to avoi	d exposure to liqu wing protection sh	uid splashes, mists, nould be worn,
Skin protection							
Hand protection			t al	istant, impervious gl times when handlin ary.			
		protection recomme When onl (breakthro Recomme	cla nde y bi oug end	ged or frequently rep iss of 6 (breakthroug d. Recommended g ief contact is expect n time >30 minutes a ed gloves: Nitrile, thi d be replaced regula	h time >480 i loves: Viton (ed, a glove w according to E ckness ≥ 0.12	minutes according ® or Nitrile, thickn ith protection clas EN374) is recomn 2 mm.	g to EN374) is less ≥ 0.38 mm. lss of 2 or higher nended.
				ance or effectiveness nage and poor maint		may be reduced	by physical/
		product is	the	st check that the fina e most appropriate a ded in the user's risk	nd takes into	account the partie	
Body protection		being per	orr	ective equipment for ned and the risks inv ng this product.			
Other skin protection	:	selected b	as	ootwear and any add ed on the task being a specialist before h	performed ar	nd the risks involv	
Respiratory protection		Based on appropria respirator aspects o Dry sanc and/or ha exposure respirator	the tes fus ling car car	hazard and potentia tandard or certification otection program to	I for exposure on. Respirato ensure prope r welding of t nding/flatting the provision o should be use	e, select a respira ors must be used or fitting, training, a he dry paint film v should be used w f local exhaust ve	according to a and other important will give rise to dust herever possible. If entilation, suitable
Environmental exposure controls	:	Emissions ensure the In some c	s fro ey o ase	om ventilation or wor comply with the requi es, fume scrubbers, f	k process equination equinations of en rements of en ilters or engir	nvironmental prot neering modificati	ection legislation. ons to the process
		equipmen	tw	Il be necessary to re	duce emissio	ins to acceptable	levels.
Date of issue/Date of revision		equipmen	tw	If be necessary to re	duce emissio	•	levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>				
Physical state	: Liquid			
Color	: White			
Odor	: Chara	cteristic.		
Odor threshold	: Not av	vailable.		
Melting point/freezing point	: Not av	ailable.		
Boiling point, initial boiling point, and boiling range	: 100°C	(212°F)		
Flammability	: Not av	vailable.		
Lower and upper explosion limit			ge: Lower: 0.6% U entane-1,3-diol)	oper: 4.2% (isobutyric acid, monoester
Flash point	: Not av	vailable.		
Auto-ignition temperature	:			
Ingredient name		°C	°F	Method
isobutyric acid, monoester with		393	739.4	

2,2,4-trimethylpentane-1,3-diol	
Decomposition temperature	Not available.
рН	8 [Conc. (% w/w): 100%] [DIN EN 1262]
Viscosity	: Kinematic (room temperature): 547 mm²/s [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
Solubility(ies)	

Media Result cold water Soluble [OECD (TG 105)]

Partition coefficient: n-octanol/ : Not applicable. water

:

Vapor pressure

	Vapor Pressure at 20°C			V	Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	0.0098	0.0013	EU A.4				

Relative density	:	1.281
Vapor density	:	Not available.
Particle characteristics		
Median particle size	:	Not applicable.
Percentage of particles with aerodynamic diameter ≤ 10 µm	:	0



SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)- one	LD50 Oral	Mouse	1150 mg/kg	-
	LD50 Oral	Rat	1020 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one	500	N/A	N/A	N/A	0.05
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05
3(2H)-Isothiazolone, 2-methyl-	100	300	N/A	N/A	0.05
witation/Correction	*	•	•	•	*

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Date of issue/Date of revision	: 1-7-2024	Version : 2	
Date of previous issue	: 28-1-2024	9/15	AkzoNobel

SECTION 11: Toxicological information

Reproductive toxicity	: No known significant e	ffects or critical hazards.
	No known oigraifiaaut -	ffooto or oritical hozarda
WILLAGENICITY	. NO KHOWH SIGNIICANT e	ffects or critical hazards.
Carcinogenicity Mutagenicity	-	ffects or critical hazards.
General Consistences in the	-	ffects or critical hazards.
Conclusion/Summary	: Not available.	f
Potential chronic health eff Not available.	<u>ects</u>	
Potential delayed effects	: Not available.	
effects	.	
Potential immediate	: Not available.	
Long term exposure		
effects Potential delayed effects	: Not available.	
<u>Short term exposure</u> Potential immediate	: Not available.	
•	cts and also chronic effec	ts from short and long term exposur
Ingestion	: No specific data.	
Skin contact	: No specific data.	
Inhalation	: No specific data.	
Eye contact	: No specific data.	
Symptoms related to the phy		ological characteristics
Ingestion	: No known significant e	neole of onliver hezelus.
	U U	
Skin contact	: No known significant e	
Eye contact Inhalation	 No known significant e No known significant e 	
Potential acute health effects	-	ffacta ar aritical bazarda
Information on the likely routes of exposure	: Not available.	
Not available.		
Aspiration hazard		
Specific target organ toxici Not available.	<u>ty (repeated exposure)</u>	
Not available.		
Specific target organ toxici	<u>ty (single exposure)</u>	
Conclusion/Summary	: Not available.	
<u>Teratogenicity</u>		
<u>Reproductive toxicity</u> Conclusion/Summary	: Not available.	
Conclusion/Summary	: Not available.	
Carcinogenicity		
Conclusion/Summary	: Not available.	



SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
		dubia	
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
3(2H)-Isothiazolone, 2-methyl-	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.3 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 0.19 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil				
Soil/water partition coefficient (Koc)	: Not available.			
Mobility	: Not available.			

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Date of issue/Date of revision	: 1-7-2024	Version : 2	
Date of previous issue	: 28-1-2024	11/15	AkzoNobel

VINYL SOFT SHEEN MEDIUM BASE

SECTION 12: Ecological information

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
Europoan wasto catalogu	

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
Date of issue/Date of revi	sion : 1-7-2024	Version : 2
Date of previous issue : 28-1-2024		12/15 AkzoNobel

SECTION 14: Transport information

	•	
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in
		the event of an accident or spillage.

14.7 Transport in bulk	:	Not applicable.
according to IMO		
instruments		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB) /REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.			
Other EU regulations					
VOC	:	The provisions of Directive 2004/42/E product label and/or technical data sh			ict. Refer to the
VOC for Ready-for-Use Mixture	:	Not available.			
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed			
Ozone depleting substand	:es	<u>(1005/2009/EU)</u>			
Not listed.					
Prior Informed Consent (P Not listed.	PIC)	<u>(649/2012/EU)</u>			
Persistent Organic Polluta Not listed.	<u>int</u>	2			
Seveso Directive					
Date of issue/Date of revision		: 1-7-2024	Version	:2	
Date of previous issue		: 28-1-2024	13/15		AkzoNobel

VINYL SOFT SHEEN MEDIUM BASE

SECTION 15: Regulatory information

This product is not controlled under the Seveso Directive.

Biocidal products regulation

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Not classified.		

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 1-7-2024	Version : 2	
Date of previous issue	: 28-1-2024	14/15	AkzoNobel

VINYL SOFT SHEEN MEDIUM BASE

SECTION 16: Other information

Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Carc. 2	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 CARCINOGENICITY - Category 2	
Eye Dam. 1 Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A	
Date of printing	: 1-7-2024	
Date of issue/ Date of revision	: 1-7-2024	
Date of previous issue	: 28-1-2024	
Version	: 2	
Unique ID	: DA7DF488320C1EEEAF86D2930A5E418E	
Nation to reader		

Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

