

SAFETY DATA SHEET

SILK MEDIUM BASE

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

 1.1 Product identifier

 Product name
 : SILK MEDIUM BASE

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses | | |
|----------------------------------|--|--|
| Professional use Consumer use | | |
| Uses advised against | | |
| None | | |

Product use

: Waterborne coating for interior use.

1.3 Details of the supplier of the safety data sheet

ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 71 71 www.dulux.co.uk

e-mail address of person : dulux.advice@akzonobel.com responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +44 (0)344 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

| Date of issue/Date of revision | : 26-1-2024 | Version : 1 | |
|--------------------------------|--------------------------|-------------|-----------|
| Date of previous issue | : No previous validation | 1/15 | AkzoNobel |

SILK MEDIUM BASE

| SECTION 2: Hazards | i | lentification |
|---|----|---|
| Signal word | : | No signal word. |
| Hazard statements | : | No known significant effects or critical hazards. |
| Precautionary statements | | |
| General | : | P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand. |
| Prevention | : | P262 - Do not get in eyes, on skin, or on clothing. |
| Response | : | P312 - Call a doctor if you feel unwell. |
| Storage | : | Not applicable. |
| Disposal | : | P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations. |
| Supplemental label elements | : | Contains 1,2-benzisothiazol-3(2H)-one and CMIT/MIT(3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | |
| Special packaging requirem | er | <u>its</u> |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do | : | None known. |

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|----------------------------------|--|-----------|--|---|---------|
| titanium dioxide | REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 | ≥15 - ≤20 | Carc. 2, H351 (inhalation) | - | [1] [*] |
| 1,2-benzisothiazol-3(2H)- one | EC: 220-120-9 CAS: 2634-33-5 | <0.05 | Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 | ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C $\geq 0.05\%$ M [Acute] = 10 | [1] |
| CMIT/MIT(3:1) | REACH #: | <0.0015 | Acute Tox. 3, H301 | ATE [Oral] = 100 | [1] |
| Date of issue/Date of revision | : 26-1-2024 | • | Version :1 | | |
| Date of previous issue | : No previous valida | ation | 2/15 | Akzo | Nobe |

SILK MEDIUM BASE

SECTION 3: Composition/information on ingredients

| C | 1-2120764691-48 | Acute Tox. 2, H310 | mg/kg |
|---|--------------------|------------------------|---|
| E | C: 911-418-6 | Acute Tox. 2, H330 | ATE [Dermal] = 50 |
| 0 | AS: 55965-84-9 | Skin Corr. 1C, H314 | mg/kg |
| 1 | ndex: 613-167-00-5 | Eye Dam. 1, H318 | ATE [Inhalation |
| | | Skin Sens. 1A, H317 | (dusts and mists)] |
| | | Aquatic Acute 1, H400 | = 0.05 mg/l |
| | | Aquatic Chronic 1, | Skin Corr. 1C, |
| | | H410 | H314: C ≥ 0.6% |
| | | EUH071 | Skin Irrit. 2, H315: |
| | | | $0.06\% \le C < 0.6\%$ |
| | | | Eye Dam. 1, H318: |
| | | | $C \ge 0.6\%$ |
| | | | Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% |
| | | | Skin Sens. 1, H317: |
| | | | $C \ge 0.0015\%$ |
| | | | M [Acute] = 100 |
| | | | M [Chronic] = 100 |
| | | See Section 16 for | |
| | | the full text of the H | |
| | | statements declared | |
| | | above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Туре</u>

[1] Substance classified with a physical, health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs. |
|----------------------------|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. |
| Ingestion | : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. |

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with

| Date of issue/Date of revision | : 26-1-2024 | Version : 1 | |
|--------------------------------|--------------------------|-------------|-----------|
| Date of previous issue | : No previous validation | 3/15 | AkzoNobel |

SECTION 4: First aid measures

SILK MEDIUM BASE

| the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption | | | | |
|---|--|--|--|--|
| through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. | | | | |
| This takes into account, where known, delayed and immediate effects and also chronic effects of components from | | | | |
| short-term and long-term expo | short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. | | | |
| Contains 1,2-benzisothiazol-3 | (2H)-one, CMIT/MIT(3:1). May produce an allergic reaction. | | | |
| Over-exposure signs/sympt | oms | | | |
| Eye contact | : No specific data. | | | |
| Inhalation | : No specific data. | | | |
| Skin contact | : No specific data. | | | |
| Ingestion | : No specific data. | | | |
| 4.3 Indication of any immedia | ate medical attention and special treatment needed | | | |
| Notes to physician | : Treat symptomatically. Contact poison treatment specialist immediately if large | | | |
| | quantities have been ingested or inhaled. | | | |
| Specific treatments | : No specific treatment. | | | |
| SECTION 5: Firefight | ing measures | | | |
| 5.1 Extinguishing media | | | | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | | | |
| Unsuitable extinguishing media | : None known. | | | |
| 5.2 Special hazards arising fr | om the substance or mixture | | | |
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. | | | |
| Hazardous combustion | : Decomposition products may include the following materials: | | | |
| products | carbon dioxide | | | |
| | carbon monoxide metal oxide/oxides | | | |
| 5.3 Advice for firefighters | | | | |
| Special protective actions | : Promptly isolate the scene by removing all persons from the vicinity of the incident if | | | |
| for fire-fighters | there is a fire. No action shall be taken involving any personal risk or without suitable training. | | | |
| Special protective | : Fire-fighters should wear appropriate protective equipment and self-contained | | | |
| equipment for fire-fighters | breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) | | | |
| | conforming to European standard EN 469 will provide a basic level of protection for | | | |
| | chemical incidents. | | | |
| SECTION 6: Accidental release measures | | | | |
| 6.1 Personal precautions, pro | otective equipment and emergency procedures | | | |

| For non-emergency personnel | Evacuate surrounding areas. | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. | | |
|--------------------------------|-------------------------------|--|-----------|--|
| For emergency responders | information in Section 8 on s | specialized clothing is required to deal with the spillage, take note of any formation in Section 8 on suitable and unsuitable materials. See also the formation in "For non-emergency personnel". | | |
| Date of issue/Date of revision | : 26-1-2024 | Version :1 | | |
| Date of previous issue | : No previous validation | 4/15 | AkzoNobel | |

SECTION 6: Accidental release measures

| 6.2 Environmental precautions | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). | |
|---------------------------------|--|--|
| 6.3 Methods and materials for | or containment and cleaning up | |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. | |
| Large spill | : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. | |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. | |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

| 7.3 Specific end use(s) | |
|----------------------------|------------------|
| Recommendations | : Not available. |
| Industrial sector specific | : Not available. |
| solutions | |

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

| Date of issue/Date of revision | | | |
|--------------------------------|--|--|--|
| Date of previous issue | | | |



SECTION 8: Exposure controls/personal protection

| the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace | Recommended monitoring procedures | : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory |
|--|-----------------------------------|---|
| of exposure to chemical and biological agents) European Standard EN 482 | | the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be |

DNELs/DMELs

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|------------------------------|------|--------------------------|------------------------|-----------------------|----------|
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Dermal | 0.345 mg/ kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.966 mg/ kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 1.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 6.81 mg/m³ | Workers | Systemic |
| CMIT/MIT(3:1) | DNEL | Long term Inhalation | 0.02 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 0.02 mg/m³ | | Local |
| | DNEL | Short term Inhalation | 0.04 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 0.04 mg/m ³ | | Local |
| | DNEL | Long term Oral | 0.09 mg/ kg bw/day | General population | Systemic |
| | DNEL | Short term Oral | 0.11 mg/ kg bw/day | General population | Systemic |

PNECs

No PNECs available.

8.2 Exposure controls

| Appropriate engineering controls | : Good general ventilation should be sufficient to control worker exposure to airborne contaminants. |
|----------------------------------|---|
| Individual protection meas | Ires |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. |
| Skin protection | |



| SECTION 8: Exposure controls/personal protection | | | | | |
|--|---|--|--|--|--|
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. | | | | |
| | When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness \geq 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness \geq 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material. | | | | |
| | The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. | | | | |
| | The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. | | | | |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | | | | |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | | | | |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If | | | | |
| | exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Wear a Approved/certified disposable particulate dust mask. | | | | |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. | | | | |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| Date of previous issue | : No previous validation | 7/15 | AkzoNobel |
|--------------------------------|--------------------------|-------------|-----------|
| Date of issue/Date of revision | : 26-1-2024 | Version : 1 | |
| Auto-ignition temperature | : | | |
| Flash point | : Not available. | | |
| limit | | | |
| Lower and upper explosion | Not available. | | |
| Flammability | : Not available. | | |
| point, and boiling range | | | |
| Boiling point, initial boiling | : 100°C (212°F) | | |
| Melting point/freezing point | : Not available. | | |
| Odor threshold | : Not available. | | |
| Odor | : Characteristic. | | |
| Color | : White. | | |
| Physical state | : Liquid. | | |
| <u>Appearance</u> | | | |

SILK MEDIUM BASE

SECTION 9: Physical and chemical properties

| Ingredient name | °C | °F | Method | |
|---|-----------------------|------------------|-----------|--|
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | 393 | 739.4 | | |
| vinyl acetate | 402 | 755.6 | | |
| ethanol | 455 | 851 | DIN 51794 | |
| Decomposition temperature | : Not available. | | | |
| рН | : 8 [Conc. (% w/w): 1 | 00%] [DIN EN 126 | 2] | |

: Kinematic (room temperature): 542 mm²/s [DIN EN ISO 3219] Viscosity Kinematic (40°C): Not applicable. [DIN EN ISO 3219] Solubility(ies) ÷

| Media | Result |
|------------|-------------------------|
| cold water | Soluble [OESO (TG 105)] |

Partition coefficient: n-octanol/ : Not applicable. water

÷

Vapor pressure

| | Vapor Pressure at 20°C | | v | Vapor pressure at 50°C | | |
|---|------------------------|-------------|--------|------------------------|-----|--------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| ammonia | 360.03 | 48 | | | | |
| methanol | 126.96 | 16.9 | | | | |
| vinyl acetate | 84.76 | 11.3 | | | | |
| Relative density | : 1.29 |)4 | | | | |
| /apor density | : Not | available. | | | | |
| Particle characteristics | | | | | | |
| Median particle size | : Not | applicable. | | | | |
| Percentage of particles with aerodynamic diameter ≤ 10 µm | : 0 | | | | | |

SECTION 10: Stability and reactivity

| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. | |
|--|--|--|
| 10.2 Chemical stability | : The product is stable. | |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. | |
| 10.4 Conditions to avoid | : No specific data. | |
| 10.5 Incompatible materials | : No specific data. | |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. | |

| Date of issue/Date of revision | : 26-1-2024 | Version : 1 | |
|--------------------------------|--------------------------|-------------|-----------|
| Date of previous issue | : No previous validation | 8/15 | AkzoNobel |

SILK MEDIUM BASE

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1). May produce an allergic reaction.

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|----------------------------------|-----------|---------|------------|----------|
| 1,2-benzisothiazol-3(2H)- one | LD50 Oral | Mouse | 1150 mg/kg | - |
| | LD50 Oral | Rat | 1020 mg/kg | - |

Conclusion/Summary : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|------------------------------|------------------|-------------------|--------------------------------|----------------------------------|--|
| 1,2-benzisothiazol-3(2H)-one | 500 | N/A | N/A | N/A | 0.05 |
| CMIT/MIT(3:1) | 100 | 50 | N/A | N/A | 0.05 |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|------------------------------|------------------------|---------|-------|--------------|-------------|
| titanium dioxide | Skin - Mild irritant | Human | - | 72 hours 300 | - |
| | | | | ug l | |
| 1,2-benzisothiazol-3(2H)-one | | Human | - | 48 hours 5 % | - |
| CMIT/MIT(3:1) | Skin - Severe irritant | Human | - | 0.01 % | - |
| Conclusion/Summary | : Not available. | | | | |
| <u>Sensitization</u> | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| <u>Mutagenicity</u> | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| <u>Carcinogenicity</u> | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| Reproductive toxicity | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| <u>Teratogenicity</u> | | | | | |
| Conclusion/Summary | : Not available. | | | | |

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Date of issue/Date of revision | : 26-1-2024 | Version :1 | |
|--------------------------------|--------------------------|------------|-----------|
| Date of previous issue | : No previous validation | 9/15 | AkzoNobel |

SILK MEDIUM BASE

SECTION 11: Toxicological information

Not available.

Aspiration hazard

Not available.

| Information on the likely routes of exposure | : | Not available. |
|--|-----|--|
| Potential acute health effects | | |
| Eye contact | | No known significant effects or critical hazards. |
| Inhalation | | No known significant effects or critical hazards. |
| Skin contact | : | No known significant effects or critical hazards. |
| Ingestion | : | No known significant effects or critical hazards. |
| Symptoms related to the phys | eid | al, chemical and toxicological characteristics |
| Eye contact | | No specific data. |
| Inhalation | : | No specific data. |
| Skin contact | : | No specific data. |
| Ingestion | | No specific data. |
| ingestion | • | No specific data. |
| Delayed and immediate effect | ts | and also chronic effects from short and long term exposure |
| <u>Short term exposure</u> | | |
| Potential immediate effects | : | Not available. |
| Potential delayed effects | : | Not available. |
| <u>Long term exposure</u> | | |
| Potential immediate effects | : | Not available. |
| Potential delayed effects | : | Not available. |
| Potential chronic health effe | ct | <u>s</u> |
| Not available. | | |
| Conclusion/Summary | : | Not available. |
| General | : | No known significant effects or critical hazards. |
| Carcinogenicity | : | No known significant effects or critical hazards. |
| Mutagenicity | : | No known significant effects or critical hazards. |
| Reproductive toxicity | : | No known significant effects or critical hazards. |
| | | |

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Not available.

11.2.2 Other information

No additional information.



SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

| Product/ingredient name | Result | Species | Exposure |
|------------------------------|--------------------------------------|-------------------------------------|----------|
| titanium dioxide | Acute LC50 >1000 mg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| 1,2-benzisothiazol-3(2H)-one | Acute EC50 97 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 2.24 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 3.7 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 1.1 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 2 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 10 to 20 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia | 48 hours |
| | Acute LC50 540 ppb Fresh water | Fish - Lepomis macrochirus | 96 hours |
| | Acute LC50 167 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 0.75 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 1.8 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 1.6 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

| 12.4 Mobility in soil | |
|-----------------------|------------------|
| Soil/water partition | : Not available. |
| coefficient (Koc) | |
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

| Date of issue/Date of revision | |
|--------------------------------|--|
| Date of previous issue | |



SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

| <u>Product</u> | |
|-------------------------|---|
| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste | : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC. |
| Disposal considerations | Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. |

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation |
|-------------------------|---|
| EWC 08 01 12 | waste paint and varnish other than those mentioned in 08 01 11 |
| Packaging | |
| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
| Disposal considerations | : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. |
| Special precautions | : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

| | ADR/RID | IMDG |
|------------------------------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - |
| 14.3 Transport hazard class(es) | - | - |
| 14.4 Packing group | - | - |
| 14.5 Environmental hazards | No. | No. |

| Date of issue/Date of revision | : 26-1-2024 | Version : 1 |
|--------------------------------|--------------------------|-------------|
| Date of previous issue | : No previous validation | 12/15 |



SECTION 14: Transport information

| 14.6 Special precautions for user | | premises: always transport in cl e that persons transporting the p ⁻ spillage. | |
|---|--|--|--------------|
| 14.7 Transport in bulk according to IMO instruments | : Not applicable. | | |
| SECTION 15: Regula | tory information | | |
| UK (GB) /REACH | onmental regulations/legisla | tion specific for the substance | ∍ or mixture |
| Annex XIV | | <u>1</u> | |
| None of the components a | are listed. | | |
| Substances of very high None of the components a | | | |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. | | |
| Other EU regulations | | | |
| VOC VOC for Ready-for-Use Mixture | Not available.Not applicable. | | |
| Industrial emissions (integrated pollution prevention and control) - Air | : Not listed | | |
| Industrial emissions (integrated pollution prevention and control) - Water | : Not listed | | |
| Ozone depleting substanc Not listed. | <u>es (1005/2009/EU)</u> | | |
| Prior Informed Consent (P Not listed. | <u>IC) (649/2012/EU)</u> | | |
| Persistent Organic Polluta Not listed. | <u>nts</u> | | |
| Biocidal products regulati International regulations | d under the Seveso Directive. <u>on</u> ion List Schedules I, II & III C | <u>hemicals</u> | |
| Montreal Protocol | | | |
| Date of issue/Date of revision | : 26-1-2024 | Version :1 | |
| Date of previous issue | : No previous validation | 13/15 | AkzoNobel |

SILK MEDIUM BASE

SECTION 15: Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

| 15.2 Chemical Safety | : No Chemical Safety Assessment has been carried out. |
|----------------------|---|
|----------------------|---|

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Abbreviations and acronyms | ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group |
|----------------------------|--|
| | vPvB = Very Persistent and Very Bioaccumulative |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-----------------|---------------|
| Not classified. | |

Full text of abbreviated H statements

| H301 | Toxic if swallowed. |
|--------|---|
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H351 | Suspected of causing cancer. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

| Date of issue/Date of revision |
|--------------------------------|
| Date of previous issue |



SILK MEDIUM BASE

SECTION 16: Other information

| Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic 2 | ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 | |
|---|--|--|
| Aquatic Chronic 2 Carc. 2 Eye Dam. 1 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A | AQUATIC HAZARD (LONG-TERM) - Category 2 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A | |
| Date of printing | : 14-4-2024 | |
| Date of issue/ Date of revision | : 26-1-2024 | |
| Date of previous issue | : No previous validation | |
| Version | : 1 | |
| Unique ID | : A6FD275CC10C1EEEAF867EF4F2F440A2 | |

Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

