

## **PRODUCT**

## ACRYLIC SIZE

## **DESCRIPTION**

An Acrylic adhesive with an extended open time for bonding metal leaf to a variety of surfaces.

## **APPLICATION**

Seal porous surfaces

Ensure Acrylic size is well mixed. Ensure all surfaces are clean and free from grease, oil, dirt and contaminants. Apply 1 coat using a good quality brush. Leave until the coating turns clear, minimum of 15 minutes. Apply the metal leaf

## <u>USES</u>

Furniture. Woodwork. Plaster work. Non Ferrous metals.

## **COVERAGE**

Approx. 15 sq. m per litre 160 sq. ft per US qt

## SHEEN LEVEL N/A

CONTAINERS 500ml, 1L, 1 US Pint, US Quart.

## No OF COATS 1 coat

## DRYING TIME

15mins-1 hr, depending on temperature

## RECOAT TIME N/A

<u>CURING</u> Does not dry, remains tacky.

## **CLEANING**

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

**FLAMMABILITY** No fire hazard before or during use, or in the cured state.

**<u>STORAGE</u>** Protect from extremes of temperature during storage and application.

## HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best if our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to access the suitability of the product on a test area before application

Further information may be obtained from:

POLYVINE LIMITED Severn Distribution Park Sharpness, Berkeley, Gloucestershire. GL13 9UQ United Kingdom

Telephone No. International	0845 017 1671 +44 845 017 1671
Fax:	0845 017 1672
Email	info@polyvine.co.uk

# **MATERIAL SAFETY DATA SHEET**

#### **1. IDENTIFICATION OF PRODUCT AND COMPANY**

#### PRODUCT

## SIZE

COMPANY:	Polyvine Limited, Severn Distribut	tion Park, Sharpness, Berkeley, Glos. GL13 9UQ UK
	Emergency Telephone 0845 017 1671	International +44 845 017 1671

#### 2. COMPOSITION

Water based dispersion of methacrylic esters, and surfactants with no hazard classificationChemical characterisation:AcrylicCAS N o:Names:Conc.:

#### 3. HAZARDS IDENTIFICATION

On available data this product has no hazard classification according to 88/379/EEC.

#### 4. FIRST AID MEASURES

**GENERAL**: Immediately remove all contaminated clothing. In all cases of doubt, or when symptoms persist, seek proper medical attention. Never give anything by mouth to an unconscious person.

**INHALATION**: Remove to fresh air, keep patient warm and at rest if breathing is irregular or stopped, administer artificial respiration. Giving nothing by mouth. If unconscious place in recovery position and seek medical advice.

**EYE CONTACT**: Holding eyelids apart, flush copiously with clean, fresh water for at least 10 minutes and seek medical advice. **SKIN CONTACT**: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleaner. **DO NOT use solvents or thinners.** 

**INGESTION**: If accidentally swallowed obtain medical attention. Keep at rest. DO NOT induce vomiting.

#### **5. FIRE-FIGHTING MEASURES**

Aqueous dispersions will not burn. Dried films are combustible and may emit noxious fumes. Water, foam, carbon dioxide or dry powder extinguishers are all suitable. Wear breathing apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

Spillage should not be washed into any drain. Spillage should be soaked up with an inert absorbent (e.g. sand) for disposal.

#### 7. HANDLING AND STORAGE

## HANDLING

This product should be handled in accordance with good safety and hygiene practices. Small levels of volatile organic compounds may accumulate in the headspace of containers, which should be opened in ventilated surroundings. **STORAGE** Sealed containers should be stored between 5 C and 40C. Bulk tanks should be externally vented.

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **EXPOSURE CONTROLS**

Local exhaust ventilation may be required in circumstances where the product is sprayed, heated or dried. **PERSONAL PROTECTION** 

Respiratory	-	Masks, when spraying
Hand	-	Gloves, if risk of skin contact
Eye	-	Goggles, if risk of splashing
Skin	-	Standard industrial overalls if splashing
O.E.L.		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	-	Coloured liquid
Odour	-	Mild
PH	-	8.0
Boiling point	-	Approx. 100C (as water)
Flammability and	d	
Autoignition tem	ıp	N/A
Vapour pressure	e -	23 mbar as water
Water solubility	-	Fully miscible
Relative density	-	Approx. 1.03 at 20 C (ISO 8962)

#### **10. STABILITY AND REACTIVITY**

This product is stable under normal conditions of use.

#### 11. TOXICOLOGICAL INFORMATION

INHALATION - May be irritating to respiratory system INGESTION - May be harmful if swallowed SKIN CONTACT- may cause skin irritation LONG TERM EXPOSURE - No information available

#### 12. ECOLOGICAL INFORMATION

Do not empty into waters and drains.

#### 13. DISPOSAL INFORMATION

Product recommendation: Do not allow into drains or watercourses.

Empty containers are to be disposed according to official rules.

Contaminated packaging recommendation: Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to approved recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

#### 14. TRANSPORT INFORMATION

This product is not classified hazardous for transportation.

#### **15. REGULATORY INFORMATION**

EEC Hazard Classification - None The product contains only substances, which are on the European Inventory of Existing Chemical Substances (EINECS).

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is based on data provided by sources considered to be reliable. This data is intended to enable safety assessment to be made and should not be construed as guaranteeing specific properties. Users are recommended to consult technical information sheets for advice on specific applications. Further information may be obtained from:

#### POLYVINE LIMITED

Severn Distribution Park Sharpness, Berkeley, Gloucestershire. GL13 9UQ United Kingdom

Telephone No.	0845 017 1671
International	+44 845 017 1671
Fax:	0845 017 1670
Email	info@polyvine.co.uk

Date of issue: October 2012