

Classified as hazardous according to criteria of Dangerous Preparations Directive (1999/45/EC)



Material Safety Data Sheet

Easycoat Low Sheen

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: TAUBMANS EASYCOAT LOW SHEEN

Product Use: For interior Walls and Ceiling

Details of the Supplier of this safety sheet:

AkzoNobel (PNG) Ltd
Vakari Street, Tarumana Ave,
Gerehu Stage 6,
PO Box 1264 Boroko,
NCD, PNG

Emergency Tel: +675 7192 1000 in PNG (24hr) OR 000

Telephone/Fax Number:

Tel: +675 7192 1001/02/03
Fax: +675 7031 8440/8441

Recommended Use:

Intended for use in the decoration of building surfaces. Taubmans Easycoat Low Sheen is suitable for all interior walls and ceilings. Refer to product label for more details of areas of use and methods of application.

Other Information:

Note: Users should verify currency of this data sheet if more than 5 years old. The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in the material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

2. HAZARDS IDENTIFICATION

This product has been assessed under the Dangerous Preparations Directive (1999/45/EC) and is classified as follows.

Indication(s) of Danger: None

Symbol Letter(s): N

Category (ies) of Danger: None

Risk Phrase(s): None

Date of Issue/Date of Revision: February 2014

Information on Occupational Exposure Limits is given in Section 8.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a physico-chemical, health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or which are assigned occupational exposure limits.

EC No.	CAS No.	HAZARDOUS INGREDIENTS	%	CLASSIFICATION
	6846-50-0	TRIMETHYLPENTANEDIOL DIISOBUTYRATE		2.5-10
200-338-0	57-55-6	PROPYLENE GLYCOL	1.0-2.5	

Note: The text for R phrase codes shown above (if any) is given in section 16.

Note: 'EC Number' if quoted is the EINECS or ELINCS number.

4. FIRST AID MEASURES

In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

EYE CONTACT: Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

SKIN CONTACT: Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION: If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Recommended - alcohol resistant foam, CO₂, powders. Not to be used - water jet.

Recommendations: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Fire fighters should wear self-contained breathing apparatus.
Closed containers exposed to fire should be cooled with water. Do not allow run-off from fire-fighting to enter drains or water-courses.

Hazchem Code: 3[Y]

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal:

Exclude non-essential personnel.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in section 8. Contain and collect spillage with non-combustible absorbent materials, eg sand, earth, vermiculite or diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Handling Conditions:

Prevent air-borne concentrations higher than the occupational exposure limits. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Avoid skin and eye contact. Avoid inhalation of vapour. Smoking, eating and drinking should be prohibited in storage and use areas. For personal protection, see Section 8. Always keep in containers made of the same material as the supply container, or in containers that are compatible with the product.

Conditions for Safe Storage:

Observe the label precautions. Store in a cool, dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Do not use or store any paint container by hanging on a hook.

If this product has a flash point below 32 degrees Celsius, it must be stored in accordance with the Petroleum (Safety Measures) Act 1984.

Specific Use(s):

Where applicable refer to the product label and literature for the application and use instructions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

HAZARDOUS INGREDIENT	LTEL (8hr TWA) mg/m ³	STEL (15 mins) Ppm	STEL (15 mins) mg/m ³	Notes
PROPYLENE GLYCOL	150	470		WEL

OEL - Occupational Exposure Limits WEL - Workplace Exposure Limit

SUP - Manufacturer's recommended Limit

LTEL - Long-term Exposure Limit.

TWA - Time weighted Average

STEL - Short term Exposure Limit (15mins)

sk - Risk of absorption through unbroken skin

sen - Respiratory sensitizer
rd - Figure quoted is for Respirable dust
id - Figure quoted is for Inhalable dust

Further guidance on WELs and OELs and on occupational exposure to harmful materials (including mixed exposures) is given in HSE Guidance Note EH40.

EXPOSURE CONTROLS:

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of local regulations.

RESPIRATORY PROTECTION:

Avoid the inhalation of vapour, particulates and spray mist. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general ventilation. If this is not sufficient to maintain concentrations of particulates and solvent vapour below the occupational exposure limit, respiratory protection must be worn.

The selection of respiratory equipment should be in accordance with local regulations.

When spray applying, suitable respiratory equipment with positive air supply should be used in cases of insufficient ventilation or where operational procedures demand it. Ensure compliance with local regulations.

HAND PROTECTION:

Wear suitable gloves for protection against materials in section 3.

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed.

EYE PROTECTION:

Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

ENVIRONMENTAL EXPOSURE CONTROLS: See section 12 for detailed information.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Flash Point:	NON FLASH°C
Specific Gravity:	1.359

Water Miscibility:	Yes	
pH:	8.75	
Viscosity (KU-1):	N/A	(ISO 6mm Range)

10. STABILITY AND REACTIVITY

Conditions to Avoid:

Extremes of temperature.

Materials To Avoid:

Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.

Hazardous Decomposition Products:

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke and oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. The product has been assessed following the conventional method in the Dangerous Preparations Directive and is classified for toxicological hazards accordingly.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. See Sections 2 and 15 for details of the resulting hazard classification.

Over-exposures of vapour are irritating to eyes and respiratory system. Excessive concentrations may produce effects on the central nervous system including drowsiness. In extreme cases loss of consciousness may result. Long term exposure to vapour concentrations in excess of quoted OELs may result in adverse health effects. Splashes entering the eye will cause discomfort and possible damage. Prolonged contact with the skin may have a defatting effect which may lead to skin irritation and in some cases dermatitis.

12. ECOLOGICAL INFORMATION

There is no specific data available on the product itself.

The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

Products classified as Marine Pollutants are indicated as such under Transport section 14.

Products classified as Dangerous For the Environment are indicated as such in sections 2 and 15.

Any substances in the product that are classified as Dangerous for the Environment, present at concentrations above those requiring listing are given in section 3.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations:

Wastes, include emptied containers, should be disposed of in accordance with national regulations

EUROPEAN WASTE CATALOGUE CODES (See 2000/532/EC)

Product Disposal:

Container Disposal:

14. TRANSPORT INFORMATION

Transport within user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport to be in accordance with ADR for road, IMDG for sea. The transport classifications provided in this section are not valid for transport by Air. Please call the number in section 1 of this safety data sheet to obtain more information on this products classification for Air transport.

ADR Classification Information

UN Number : 0000

Proper Shipping Name : NOT APPLICABLE

Hazard Class : EX

Sub-Hazard Class :

Packing Group : EX

Technical Name
(NOS only) :

Ltd Qty Code :

Packing
Instructions :

IMDG Classification Information

UN Number : 0000

Proper Shipping
Name : NOT APPLICABLE

Hazard Class : EX

Sub-Hazard Class :

Packing Group : EX

Technical Name
(NOS only) :

Ltd Qty Maximum :

Packing
Instructions :

Marine Pollutant
if indicated here: *

Emergency Schedule
No :

Flashpoint : NON-FLASH

15. REGULATORY INFORMATION

This product has been assessed under the Dangerous Preparations Directive (1999/45/EC) and is classified as follows:

Named Substances:

Contains:

No substances are required to be named in this section

Indications(s) Of Danger: None

Symbols Letter(s): N

Warning Label Phrases:

- S2 Keep out of the reach of children.
- S23 Do not breathe solvent vapour
or spray
- S51 Use only in well ventilated
areas
- J17 Safety data sheet available for user
On request

Where 'J' and/or 'P' phrases are denoted, these are AkzoNobel or paint industry reference codes to additional phrases.

16. OTHER INFORMATION

Text for R Phrases shown in section 3 describing each ingredient:

-no R Phrases are present in section 3

The information in this safety data sheet is required in pursuant to national regulations implementing Directive 91/155/EEC and its amendments (Directive 93/112/EC and Directive 2001/58/EC).

The information on this sheet is not a specification: it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

We will be pleased to answer any specific enquiries regarding the safe use, storage and handling of our products

Contact Person/Point:

Attn: Stephen Woodcock

**AkzoNobel (PNG) Ltd,
P O Box 1264,
Tel.: +675 7192 1001/02/03,
Fax: +675 7031 8440/8441
Vakari Street,
Gerehu Stage 6,
Port Moresby,
Papua New Guinea**

**Emergency Contact: +675 7192 1000 (24 hr.)
Fire Ambulance: 110 or 000 (PNG)**

End of MSDS