

Classified as hazardous according to criteria of Dangerous Preparations Directive (1999/45/EC)



# Material Safety Data Sheet

## Prep Right 3-IN-1 Primer

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** TAUBMANS PREPRIGHT 3-IN-1 PRIMER

**Product Use:** For timber, wallboard & steel

**Details of the Supplier of this safety sheet:** AkzoNobel (PNG) Ltd  
Vakari Street, Tarumana Ave,  
Gerehu Stage 6,  
PO Box 1264 Boroko,  
NCD, PNG

**Emergency Tel:** 000/ 110 OR +675 7192 1000 in PNG

**Telephone/Fax Number:** Tel: +675 7192 1001/02/03  
Fax: +675 7031 8440/8441

**Recommended Use:** Interior surfaces as an undercoat directly over bare timber, as a sealer for wallboards or as a primer for galvanized steel. Taubmans Prepright 3-IN-1 Primer is particularly recommended for repaint over aged enamel to provide a sound bond for other water based topcoats. Suitable for exterior applications when used as a primer for timber or on previously painted surfaces. Taubmans Prepright 3-IN-1 Primer can also be used in "high humidity" areas- bathrooms, laundries, kitchens, etc. under both water based finishes and oil based enamels.  
Refer to product label for more details of areas of use and methods of application.

**Other Information:** Note: Users should verify currency of this data sheet if more than 5 years old. The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in the material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

### 2. HAZARDS IDENTIFICATION

This product has been assessed under the Occupational Safety and Health (Classification, Packaging & Labelling of Hazardous Chemicals) Regulations 1997, and is classified as follows.

**Indication(s) of Danger:** Dangerous for the Environment.

**Date of issue/Date of Revision:** March 2014

**Symbol Letter(s):** N

**Category(ies) of Danger:** Flammable, Dangerous For The Environment

**Risk Phrase(s):** R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information on Occupational Exposure Limits is given in Section 8.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a physico-chemical, health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or which are assigned occupational exposure limits.

EC No.	CAS No.	HAZARDOUS INGREDIENTS	%	CLASSIFICATION
238-877-9	14807-96-6	TALC, MAGNESIUM SILICATE	2.5-10	
231-944-3	7779-90-0	ZINC PHOSPHATE PIGMENT	2.5-10	N R50/53
200-338-0	57-55-6	PROPYLENE GLYCOL	2.5-10	
231-555-9	7632-00-0	SODIUM NITRITE	< 1.0	N,O,T R25-50-8

Note: The text for R phrase codes shown above (if any) is given in section 16.

Note: 'EC Number' if quoted is the EINECS or ELINCS number.

### 4. FIRST AID MEASURES

In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

**EYE CONTACT:** Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

**SKIN CONTACT:** Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

**Date of issue/Date of Revision:** March 2014

**INGESTION:**

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:**

Recommended - alcohol resistant foam, CO<sub>2</sub>, powders.  
Not to be used - water jet.

**Recommendations:**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.  
Fire fighters should wear self-contained breathing apparatus.  
Closed containers exposed to fire should be cooled with water. Do not allow run-off from fire-fighting to enter drains or water-courses.

**Hazchem Code:**

3[Y]

## 6. ACCIDENTAL RELEASE MEASURES

**Spills & Disposal:**

Exclude non-essential personnel.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in section 8. Contain and collect spillage with non-combustible absorbent materials, eg sand, earth, vermiculite or diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

## 7. HANDLING AND STORAGE

**Handling Conditions:**

Prevent air-borne concentrations higher than the occupational exposure limits. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Avoid skin and eye contact. Avoid inhalation of vapour. Smoking, eating and drinking should be prohibited in storage and use areas. For personal protection, see Section 8. Always keep in containers made of the same material as the supply container, or in containers that are compatible with the product.

**Conditions for Safe Storage:**

Observe the label precautions. Store in a cool, dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Do not use or store any paint container by hanging on a hook.

If this product has a flash point below 32 degrees Celcius, it must be stored in accordance with the Petroleum (Safety Measures) Act 1984.

**Specific Use(s):**

Where applicable refer to the product label and literature for the application and use instructions.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	TLV-TWA ppm	TLV-TWA mg/m3	STEL (15min) ppm	STEL (15min) mg/m3	Notes
PROPYLENE GLYCOL	150	470			WEL
TALC, MAGNESIUM SILICATE	2				A4
SODIUM NITRITE	2				SUP

TLV-TWA - Time Weighted Average Threshold Limit Values

STEL - Short Term Exposure Limit

C - Ceiling Value

SUP - Manufacturer's recommended limit

Sk - Risk of absorption through unbroken skin

rd - As respirable dust

id - As inhalable dust

rq - As respirable quartz

Pb - As Lead

Cr - As Chromium

SEN - Potential for worker sensitisation as a result of dermal contact.

Further guidance on exposure limits and assessment of occupational exposure to harmful materials (including mixed exposures) is given in TLVs and BEIs, available from ACGIH worldwide.

### EXPOSURE CONTROLS:

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of local regulations.

### RESPIRATORY PROTECTION:

Avoid the inhalation of vapour, particulates and spray mist. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general ventilation. If this is not sufficient to maintain concentrations of particulates and solvent vapour below the occupational exposure limit, respiratory protection must be worn.

The selection of respiratory equipment should be in accordance with local regulations.

When spray applying, suitable respiratory equipment with positive air supply should be used in cases of insufficient ventilation or where operational procedures demand it. Ensure compliance with local regulations.

#### **HAND PROTECTION:**

Wear suitable gloves for protection against materials in section 3.

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed.

#### **EYE PROTECTION:**

Eye protection designed to protect against liquid splashes should be worn.

#### **SKIN PROTECTION:**

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

#### **FLATTING:**

Protective gloves should be worn to avoid the risk of skin irritation. When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960. Where possible wet flattening or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry flattening cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of Occupational Safety and Health (Use and Standard of Exposure of Chemicals Hazardous to Health) Regulations 2000, taking into account the occupational hygiene exposure standard for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

The UK Control of Lead at Work approved code of practice 1998 (ISBN 0 71 7615065) might be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations.

All scrapings, dust, etc. should be disposed of by the professional painting contractor as Special (Hazardous) Waste, with the relevant documentation under the Environmental Quality (Scheduled Wastes) Regulations 1989.

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**ENVIRONMENTAL EXPOSURE CONTROLS:** See section 12 for detailed information.

EXPOSURE LIMIT VALUES

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State :</b>	Liquid
<b>Flash Point :</b>	NON FLASH°C
<b>Specific Gravity :</b>	1.340kg/L
<b>Water Miscibility :</b>	Yes
<b>pH :</b>	7
<b>Viscosity (KU-1):</b>	<b>CHECK ON SERVERKU</b>

## 10. STABILITY AND REACTIVITY

<b>Conditions to Avoid:</b>	Extremes of temperature.  To prevent the creation of flammable concentrations of vapour in air, good natural ventilation, and if necessary, local exhaust ventilation, should be provided. The accumulation of dry overspray, contaminated rags, etc may result in spontaneous combustion. Good housekeeping standards plus the regular and safe removal of waste materials will minimise the risk.
<b>Materials To Avoid:</b>	Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.
<b>Hazardous Decomposition Products:</b>	When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke and oxides of nitrogen.

## 11. TOXICOLOGICAL INFORMATION

There is no experimental data available on the product itself. However, it has been assessed according to the Occupational Safety and Health (Classification, Packaging & Labelling of Chemicals) Regulations 1997 and classified for toxicological hazards. See Section 15 for these details, including associated risk and safety phrases.

Over-exposures of vapour are irritating to eyes and respiratory system. Excessive concentrations may produce effects on the central nervous system including drowsiness. In extreme cases loss of consciousness may result. Long term exposure to vapour concentrations in excess of quoted OELs may result in adverse health effects. Splashes entering the eye will cause discomfort and possible damage. Prolonged contact with the skin may have a defatting effect which may lead to skin irritation and in some cases dermatitis.

## 12. ECOLOGICAL INFORMATION

**Ecological Information:** Harmful to marine organisms. Avoid release to drains and waterways.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

Products classified as Marine Pollutants are indicated as such under Transport (section 14).

Products classified as Dangerous For the Environment are indicated as such in sections 2 and 15.

Any substances in the product that are classified as Dangerous for the Environment, present at concentrations above those requiring listing are given in section 3.

## 13. DISPOSAL CONSIDERATIONS

**Disposal Considerations:** Waste material and containers must be treated as a fire hazard and disposed of in accordance with local, state and national regulations.

**Product Disposal:** Do not pour unwanted paint down the drain. Keep unwanted paint in sealed containers for disposal via special chemical waste collections.

**Container Disposal:** Empty paint cans should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel recycling programs. Check with your local council for details.

## 14. TRANSPORT INFORMATION

**Transport Information:** Transport within user's premises:  
Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.  
Transport to be in accordance with ADR for road, IMDG for sea. The transport classifications provided in this section are not valid for transport by Air. Please call the number in section 1 of this safety data sheet to obtain more information on this products classification for Air transport.

### ADR Classification Information

UN Number : 1263

### IMDG Classification Information

UN Number : 1263

Proper Shipping Name : PAINT

Hazard Class : 3

Sub-Hazard Class :

Packing Group : III

Technical Name (NOS only) :

Ltd Qty Code : LQ7

Packing Instructions : P001

Proper Shipping Name : PAINT

Hazard Class : 3

Sub-Hazard Class :

Packing Group : III

Technical Name (NOS only) :

Ltd Qty Maximum : 18.0 litres

Packing Instructions : P001

Marine Pollutant if indicated here: \* MARINE POLLUTANT \*

Emergency Schedule No : F-E,S-E

Flashpoint : NON-FLASH

## 15. REGULATORY INFORMATION

This product has been assessed under the Dangerous Preparations Directive (1999/45/EC) and is classified as follows:

### Indications(s) Of Danger: Dangerous For The Environment

R10	Flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R66	Repeated exposure may cause skin dryness or cracking.
S2	Keep out of the reach of children.
S17	Keep away from combustible material.
S24	Avoid contact with skin.
S29	Do not empty into drains.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S61	Avoid release to the environment. Refer to special instructions/Safety data sheet.
S43(A)	In case of fire use foam, dry powder, AAF, CO2 - Never use water.

Where 'J'and/or 'P' phrases are denoted, these are AkzoNobel or paint industry reference codes to additional phrases.

**Symbols Letter(s):** N

### Warning Label Phrases:

**Date of issue/Date of Revision:** March 2014



## 16. OTHER INFORMATION

Text for R Phrases shown in section 3 describing each ingredient:

R10	Flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

The information given in this data sheet is required pursuant to the Occupational Safety and Health (Classification, Packaging & Labelling of Hazardous Chemicals) Regulations 1997 - Regulation 9.

### Other Reference:

Occupational Safety and Health (Use and Standard of Exposure of Chemicals Hazardous to Health) Regulations 2000.

The information on this sheet is not a specification: it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

**Contact Person/Point:**      **Attn: Stephen Woodcock**

**AkzoNobel (PNG) Ltd,  
P O Box 1264,  
Tel.: +675 7192 1001/02/03,  
Fax: +675 7031 8440/8441  
Vakari Street,  
Gerehu Stage 6,  
Port Moresby,  
Papua New Guinea**

**Emergency Contact: +675 7192 1000 (24 hr.)  
Fire Ambulance: 110 or 000 (PNG)**

**Date of issue/Date of Revision: March 2014**

**Other Information:**

Principal toxic properties of this product are due to the solvent composition and vapour inhalation hazards.

Abbreviations: N/A - Not Applicable N/AV - Not Available

**End of MSDS**