

# Dulux Ambiance Marble Special Effects Paint 536

<b>Product Description</b>	<b>Dulux Ambiance Marble Special Effects Paint</b> is inspired by the beauty of stone, create the luxurious touch of marble finish on your walls. Compose your own symphony of breathtaking marble colours and special effects to personalize your interior walls.
<b>Typical Uses</b>	For use on new or previously painted interior masonry surface such as brickwork, plaster, cement and rendering.
<b>Finish</b>	Marble finish
<b>Advantages</b>	<ul style="list-style-type: none"> <li>• Luxurious touch of marble finish</li> <li>• Ready to use, low VOC and no added heavy metal</li> <li>• Water resistance &amp; Mould resistance</li> <li>• Stylish colours, available in 92 shades</li> <li>• Optimized rheology and open time for better application</li> </ul>
<b>Pack Size</b>	1Kg
<b>Colour Range</b>	92 Tinting Colours
<b>Composition (Nominal)</b>	Pigment : Non-lead pigment Binder : Acrylate Copolymer Solvent : Water Additives
<b>Volume Solids</b>	45% (nominal)
<b>Drying Time</b> - <i>Touch Dry</i> - <i>Recoat</i>	Single coat at standard thickness (25°C, 50% R.H.) 1-2 hour 4-8 hours Drying times will vary depending on temperature and humidity
<b>Wet Film Thickness</b>	330 um
<b>Dry Film Thickness</b>	150 um
<b>Storage</b>	Always store in a cool (0-40°C) and dry place. Avoid rain and sun exposure and freezing (not below 0°C).
<b>Theoretical Coverage</b>	Theoretically, 1 Kg of this product can cover 3 sqm in one coat. Coverage will vary considerably depending on application methods and surface roughness and porosity.
<b>Application</b>	<ul style="list-style-type: none"> <li>• Apply 3 coats of this product in required colour with trowel, no dilution is needed.</li> <li>• For the first coat, ensure uniform deposition completely hiding the surface. For the second coat, apply a thin layer of the product in a random manner.</li> <li>• For the last coat, apply a very thin layer of the product smoothing it at the same time onto the surface with the blade of the trowel. Buff to attain satin or gloss finish.</li> <li>• Sand the surface after the first and second coat. Do not sand the final coat of paint.</li> </ul>
<b>Cleaning Up</b>	Clean all equipment with clean water immediately after use
<b>Surface Preparation</b>	Surfaces must be thoroughly clean, dry and free from all loose dirt, chalk or powder. New surfaces such as plaster and concrete should be fully dry before painting, with moisture content less than 14% and pH value below 10.
- <i>New Wall</i>	<ol style="list-style-type: none"> <li>1. Fresh concrete must cure at least 30 days and meet application requirement before plastering</li> <li>2. The plaster must not be too soft. Sand and dust off after dry.</li> <li>3. To resist alkalis and to obtain best results first apply 1 coat of <b>Dulux Eco-sense All in 1 Primer A931-65834</b></li> </ol>
- <i>Previously Painted Surface</i>	<ol style="list-style-type: none"> <li>1. Remove powdery or flaking paint by scraping followed by using a suitable abrasive paper and dusting off</li> <li>2. Fill the defects with proper filler</li> <li>3. To seal powdery surfaces and to obtain best results first apply 1 coat of <b>Dulux Eco-sense All in 1 Primer A931-65834</b></li> </ol>



Online Tutorial

# Dulux Ambiance Marble Special Effects Paint 536

## - Fungus Growth Wall

1. Remove all fungus by scraping followed by using a suitable abrasive paper and dusting off, or use **Polycell Mould Killer**.
2. To resist alkalis and to obtain the best results, first apply 1 coat of **Dulux Eco-sense All in 1 Primer A931-65834**.

## Notes for use

1. Read the application instruction thoroughly before use
2. Stir well before use
3. Thin with clean water when necessary. Do not over dilute.
4. Do not hold too much paint on paint brush or roller
5. Do not pour the diluted paint back to the original pack
6. Recommend to use up opened paint quickly
7. Suggest closing the window and turn on the dehumidifier when encounters the high humidity or larger temperature difference situation

## Typical Painting System

SURFACE	SYSTEM
Normal, Sound Surfaces	Primer: Dulux Eco-sense All in 1 Primer A931-65834 (1 coat) Finish: Dulux Ambiance Marble Special Effects Paint 536 (3 Coats)

## Application Precautions

- Do not sand the final coat of paint. If sanding is done on the first coat and second coat of finish, ensure that the second coat of finish is applied evenly over the first.
- Apply above 10°C (surface temperature) in dry condition. Do not apply when R.H. is 85% or above.

## Safety, Health and Environmental Information

- Keep container tightly close and out of the reach of children
- A suitable cartridge mask should be worn when rubbing down
- Ensure good ventilation during application and drying
- Do not breathe vapour/spray
- In case of insufficient ventilation during spraying wear suitable respiratory equipment
- Keep away from food and drink
- All respiratory equipment must meet (NOISH/MSHA) approved standard
- When applying paint it is advisable to wear suitable eye protection and gloves
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin: use soap and water or a recognised skin cleaner.
- If swallowed seek medical advice immediately and show this container or label
- Care must be taken when transporting paint. Keep container in a secure upright position.
- Protect from extremes of temperature. Store in a cool place.
- In the event of an accident, contain and collect spillage using sand or earth. Do not empty into drains or water courses. Dispose of any paint waste in accordance with local environmental regulations.

(PLEASE REQUEST PRODUCT SAFETY DATA SHEET FROM PRODUCT DEALER AND REFER TO IT BEFORE USE.)

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: [Flat coatings]  
VOC content (ready to use) not exceeding 11 g/litre

**LIMITATION OF LIABILITY** The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

For further information or if you have any concerns about using this product, please contact our Sales Department.

Any advice, recommendations, information, assistance or service provided by AkzoNobel in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel is provided without expressed or implied warranties.

Imported from:

**Akzo Nobel Paints (Malaysia) Sdn Bhd**

Lot 5827, Kawasan Perindustrian Nilai, 71800 Nilai, Negeri Sembilan Darul Khusus, Malaysia

Distributed by:

**Akzo Nobel Paints Limited**

Tel: 2823 1388 Fax: 2866 3232

Website: www.akzonobel.com