

| | |
|---|--|
| Product Description | Dulux Waterborne Enamel (Gloss) adopts low odour formulation that provides all round protection for wood or metal surfaces in both interior and exterior. It provides tough coats with strong opacity and fungus resistance; it also dries quickly to ensure high efficiency at work, helping you to bring out the best in enamel. |
| Typical Uses | Suitable for use on wood or metal in both interior and exterior. |
| Finish | High Gloss; above 60 units @ 60 degree. |
| Advantages | <ul style="list-style-type: none"> • Low Odour • Tough coats • Quick drying • Anti-rust with strong opacity • Excellent fungus & bacteria resistance • Special anti UV formulation with excellent weathering resistance |
| Pack Size | <ul style="list-style-type: none"> • 1L • 3L |
| Colour Range | White & Colour Palette 5 colours. |
| Composition (Nominal) | Water-Borne synthetic latex, Titanium Dioxide, Pigment, Anti-mildew & Anti-bacterial agent, Water. |
| Thinner | Water |
| Volume Solids | White 35.5% (nominal), other colours will vary. |
| Drying Time - <i>Touch Dry</i> - <i>Recoat</i> | <p>Single coat at standard thickness (29°C, 60% R.H.) Around 1 hour 1-2 hours Drying times will vary depending on temperature and humidity. Generally, the paints can dry thoroughly in 7 days.</p> |
| Wet Film Thickness | 100 um |
| Dry Film Thickness | 35.5 um |
| Theoretical Coverage | Theoretically 1 litre of this product can cover 8-10 sqm in one coat. Coverage will vary considerably depending on application methods, colour and surface roughness & porosity. |
| Application |  |
| Thinning | <ul style="list-style-type: none"> • No thinning is required for application by brush or roller. Thin with less than 10% of water for conventional spray and stir thoroughly before use. (Thinning this product will affect the film thickness and opacity, which you might need to apply more coats than normal and reserve more time for drying.) |
| Cleaning Up | Clean all equipment with clean water immediately after use. |
| General Surface Preparation | All surfaces must be sound, dry, clean and free of mildew, oil, grease, wax, polish, form release agents, curing compounds, efflorescence, loose and flaking paint and other foreign substances. Sand smooth, dust clean and cover any cracks before applying the paints. |
| Previously Painted Surface | Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint, scrub defect areas until the bare surface exposed, prime bare areas with primer. |

Dulux Waterborne Enamel (Gloss) A722

Notes for use

1. Read the application instruction thoroughly before use.
2. Stir well before use.
3. Thin with clean water when necessary. Do not over dilute.
4. Do not hold too much paint on paint brush or roller.
5. Do not pour the diluted paint back to the original pack.
6. Recommend to use up opened paint quickly.

Typical Painting System

| SURFACE | SYSTEM |
|---------|---|
| Wood | Primer: Dulux Stain Block Sealer A931N (1 coat) Finish: Dulux Waterborne Enamel (Gloss) A722 (2 coats) |
| Metal | Primer: Dulux Pro Devflex Waterborne Primer 4020 (1 coat) Finish: Dulux Waterborne Enamel (Gloss) A722 (2 coats) |

Safety, Health and Environmental Information

- Keep container tightly close and out of the reach of children.
- A suitable cartridge mask should be worn when rubbing down.
- Ensure good ventilation during application and drying.
- Do not breathe vapour/spray.
- In case of insufficient ventilation during spraying wear suitable respiratory equipment.
- All respiratory equipment must meet (NOISH/MSHA) approved standard.
- Keep away from food and drink.
- When applying paint it is advisable to wear suitable eye protection and gloves.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin: use soap and water or a recognised skin cleaner.
- If swallowed seek medical advice immediately and show this container or label.
- Care must be taken when transporting paint. Keep container in a secure upright position.
- Protect from extremes of temperature. Store in a cool place.
- In the event of an accident, contain and collect spillage using sand or earth.
- Do not empty into drains or water courses.
- Dispose of any paint waste in accordance with local environmental regulations.
- Contains no added lead and mercury.

(PLEASE REQUEST PRODUCT SAFETY DATA SHEET FROM PRODUCT DEALER AND REFER TO IT BEFORE USE.)

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: [Quick dry enamel]
香港空氣污染管制(揮發性有機化合物)條例下受規管漆料的類別: [快乾磁漆]
VOC content (ready to use) = 54 gm/litre 揮發性有機化合物含量(即用狀態) = 54克/公升

LIMITATION OF LIABILITY The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

For further information or if you have any concerns about using this product, please contact our Sales Department.

Manufactured by:

Akzo Nobel Taiwan Paints Ltd.

52 Tong Yuan Road, Chung-Li,
Taoyuan County 32063,
Taiwan

Distributed by:

Akzo Nobel Swire Paints Limited

Tel: 2823 1388 Fax: 2866 3232 Website: www.akzonobel.com

Any advice, recommendations, information, assistance or service provided by AkzoNobel in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel is provided without expressed or implied warranties.