

Product Description	Dulux BioCare Emulsion Paint is an eco-friendly, high performance biobased paint certified by USDA's BioPreferred® Program. Inspired by nature, sustainable plant-based ingredients are used to replace parts of the petroleum-based raw materials. With its "Additive-free formula" and international eco-certificates, ensuring the product is odourless and environmentally safe. Other all-round functions include anti-formaldehyde, 99.9% anti-bacteria, mould resistance, superb washability, water resistance, high opacity and covering hairline cracks, providing a comfortable and green living space for you and your family.
Typical Uses	For use on new or previously painted interior masonry surface such as brickwork, plaster, cement and rendering.
Finish	Matt
Advantages	<ul style="list-style-type: none"> • Inspired by nature, it is sourced from natural ingredients such as corn and cassava, certified as biobased products by USDA. • "Natural active bamboo charcoal factor", efficiently purify formaldehyde, benzene, TVOC and other harmful substances in the air. • Kill 99.9% germs and bacteria on walls, such as E. coli, Staphylococcus aureus, and K. pneumoniae. • Innovative "Additive-free formula", promises no formaldehyde, benzene or other volatile organic compounds (VOCs) are added in the raw materials, product formulation and production process. Ensure the product is odourless, extremely low VOCs and environmentally safe! • Obtained "GREENGUARD Gold Certification" and "French VOC Emission Class A+ Label", which are the most stringent tests for Indoor Air Quality in the industry, making it suitable for sensitive individuals (such as children and the elderly). • All-round functions include mould resistance, superb washability, water resistance, high opacity and covering hairline cracks.
Composition (Nominal)	Pigment : Non-lead pigment Binder : Acrylate Copolymer Solvent : Water Additives
Volume Solids	White 43% (Nominal), other colours will vary.
Drying Time - Touch dry - Recoat	Single coat at standard thickness (25°C, 50% R.H.) 0.5-1 hour 2-3 hours Drying times will vary depending on temperature and humidity.
Film Thickness	Wet Film : 80 µm, Dry Film : 34 µm
Colour Range	White & Selective Colour Palette 5 colours
Pack Size	1L & 5L
Storage	Always store in cool & dry places and avoid freezing.
Theoretical Coverage	Theoretically 1 liter of this product can cover 13-16 sqm in one coat. Coverage will vary considerably depending on application methods and surface roughness & porosity.
Application	
Thinning - Brush or Roller - Conventional Spray - Airless Spray	Thin up to 20% water depend on different application methods & temperature. Do not over thin by adding more than 30% water. For sealing new or bare surfaces thin with up to 1 part of clean water to 5-10 parts of paint (10-20%). Add up to 1 part of clean water to 5 parts of paint (20%). Ready for use.
Spray Recommendations - Conventional Spray - Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq inch) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
Cleaning Up	Clean all equipment with clean water immediately after use.
Surface Preparation	Surfaces must be thoroughly clean, dry and free from all loose dirt, chalk or powder. New surfaces such as plaster and concrete should be fully dry before painting, with moisture content less than 14% and pH value below 10.

Dulux BioCare Emulsion Paint A8125

- New Wall

1. Fresh concrete must cure at least 30 days and meet application requirement before plastering.
2. The plaster must not be too soft. Sand and dust off after dry.
3. To resist alkalis and to obtain the best results, first apply 1 coat of **Dulux Eco-sense All-in-1 Primer A931-65834**.

- Previously Painted Surface

1. Remove powdery or flaking paint by scraping followed by using a suitable abrasive paper and dusting off.
2. Fill the defects with proper filler.
3. To seal powdery surfaces and to obtain the best results, first apply 1 coat of **Dulux Eco-sense All-in-1 Primer A931-65834**.

- Fungus Growth Wall

1. Remove all fungus by scraping followed by using a suitable abrasive paper and dusting off, or use **Ploycell Mould Killer**.
2. To resist alkalis and to obtain the best results, first apply 1 coat of **Dulux Eco-sense All-in-1 Primer A931-65834**.

Notes for Use

1. Read the application instruction thoroughly before use.
2. Stir well before use.
3. Thin with clean water when necessary. Do not over dilute.
4. Do not hold too much paint on paint brush or roller.
5. Do not pour the diluted paint back to the original pack.
6. Recommend to use up opened paint quickly.

Typical Painting System

SURFACE	SYSTEM
Normal, Sound Surfaces	Primer: Dulux Eco-sense All-in-1 Primer A931-65834 (1 Coat) Finish: Dulux BioCare Emulsion Paint A8125 (2 Coats)

Application Precautions

- Do not sand the final coat of paint. If sanding is done on the first coat of finish, ensure that the second coat of finish is applied evenly over the first.
- Apply above 10°C (surface temperature) in dry condition. Don Not apply when R.H. is 85% or above.
- When applying deep or bright colour, please control the dilution ratio within 5%. You will need to apply more coats than normal for opacity. (Please refer to Deep/Bright colour application guide.)

Safety, Health and Environmental Information

- Keep container tightly closed and out of the reach of children.
- A suitable cartridge mask should be worn when rubbing down.
- Ensure good ventilation during application and drying.
- Do not breathe vapour/spray.
- In case of insufficient ventilation during spraying, wear suitable respiratory equipment.
- All respiratory equipment must meet an appropriate (NOISH/MSHA) approved standard.
- Keep away from food, drink and animal feeding stuff.
- When applying paint, it is advisable to wear eye protection and suitable gloves.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin by using soap and water or a recognized skin cleaner.
- Care must be taken when transporting paint; keep container in a secure upright position.
- In the event of an accident, contain and collect spillage using sand or earth.
- Do not empty into drains or water courses.
- Dispose of any paint waste in accordance with appropriate local environmental regulations.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- If swallowed, seek medical advice immediately and show this container or label.
- Contains no added lead and mercury.

(PLEASE REFER TO PRODUCT SAFETY DATA SHEET FROM DEALER AND REFER TO IT BEFORE USE.)

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: [Flat coatings]
VOC content (ready to use) = 15 gm/litre

LIMITATION OF LIABILITY The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

For further information or if you have any concerns about using this product, please contact our Sales Department.

Any advice, recommendations, information, assistance or service provided by AkzoNobel in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel is provided without expressed or implied warranties.

Manufactured by:
Akzo Nobel Swire Paints (Guangzhou) Limited
Bei Wei Ind. Dist., Guangzhou E&T Development Zone, PRC.

Distributed by:
Akzo Nobel Swire Paints Limited
Tel: 2823 1388 Fax: 2866 3232
Website: www.akzonobel.com