

Product Description	Dulux Total Effect Odorless Primer is a super premium quality interior water-based primer. It possesses the features of super adhesion, super penetration, high opacity and alkali resistance, which effectively prevent the wall from various problems. The innovated odorless tech to make the product more environmental friendly as well. It can enhance the benefits of Dulux Super Premium emulsion and help to achieve the best end result.
Typical Uses	For use on new or previously painted interior masonry surface such as brickwork, plaster, cement and rendering.
Finish	Matt
Advantages	<ul style="list-style-type: none"> • Super adhesion • Super penetration • High opacity • Alkali resistance • Innovated odorless tech • Environmental friendly
Pack Size	5L
Colour Range	White
Composition (Nominal)	Pigment : Non-lead pigment Binder : Acrylate Copolymer Solvent : Water Additives
Volume Solids	White 30% (nominal), other colours will vary.
Drying Time - <i>Touch Dry</i> - <i>Recoat</i>	Single coat at standard thickness (25°C, 50% R.H.) 0.5-1 hour 2-3 hours Drying times will vary depending on temperature and humidity.
Wet Film Thickness	80 µm
Dry Film Thickness	24 µm
Storage	Always store in cool & dry places and avoid freezing
Theoretical Coverage	Theoretically 1 litre of this product can cover 10-12 sqm in one coat. Coverage will vary considerably depending on application methods and surface roughness & porosity.
Application	
Thinning - <i>Brush or Roller</i> - <i>Conventional Spray</i> - <i>Airless Spray</i>	Thin up to 20% water depend on different application methods & temperature. Do not over thin by adding more than 30% water. For sealing new or bare surfaces thin with up to 1 part of clean water to 5-10 parts of paint (10-20%). Add up to 1 part of clean water to 5 parts of paint (20%). Ready for use.
Spray Recommendations - <i>Conventional Spray</i> - <i>Airless Spray</i>	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
Cleaning Up	Clean all equipment with clean water immediately after use.
Surface Preparation - <i>New Wall</i>	Surfaces must be thoroughly clean, dry and free from all loose dirt, chalk or powder. New surfaces such as plaster and concrete should be fully dry before painting, with moisture content less than 14% and pH value below 10. 1. Fresh concrete must cure at least 30 days and meet application requirement before plastering. 2. The plaster must not be too soft. Sand and dust off after dry.

Dulux Total Effect Odorless Primer A931-65968

- Previously Painted Surface

1. Remove powdery or flaking paint by scraping followed by using a suitable abrasive paper and dusting off.
2. Fill the defects with proper filler.

- Fungus Growth Wall

1. Remove all fungus by scraping followed by using a suitable abrasive paper and dusting off, or use **Ploycell Mould Killer**.

Notes for use

1. Read the application instruction thoroughly before use.
2. Stir well before use.
3. Thin with clean water when necessary. Do not over dilute.
4. Do not hold too much paint on paint brush or roller.
5. Do not pour the diluted paint back to the original pack.
6. Recommend to use up opened paint quickly.

Typical Painting System

SURFACE	SYSTEM
Normal, Sound Surfaces	Primer: Dulux Total Effect Odorless Primer A931-65968 (1 coat) Finish: Dulux All Round Guard Superior Emulsion Paint H8112 (2 coats) Dulux Trade Diamond Matt Emulsion Paint 447 (2 coats) Dulux Gold Anti-formaldehyde Emulsion Paint A607 (2 coats) Dulux Odourless Supreme Plus Emulsion Paint H8874 (2 coats) Dulux Pentalite Upgrade Emulsion Paint H8661 (2 coats)

Application Precautions

- Do not sand the final coat of paint. If sanding is done on the first coat of finish, ensure that the second coat of finish is applied evenly over the first.
- Apply above 10°C (surface temperature) in dry condition. Don Not apply when R.H. is 85% or above.

Safety, Health and Environmental Information

- Keep container tightly close and out of the reach of children.
- A suitable cartridge mask should be worn when rubbing down.
- Ensure good ventilation during application and drying.
- Do not breathe vapour/spray.
- In case of insufficient ventilation during spraying, wear suitable respiratory equipment.
- All respiratory equipment must meet an appropriate (NOISH/MSHA) approved standard.
- Keep away from food, drink and animal feeding stuff.
- When applying paint, it is advisable to wear suitable eye protection and gloves.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin by using soap and water or a recognized skin cleaner.
- If swallowed, seek medical advice immediately and show this container or label.
- Care must be taken when transporting paint. Keep container in a secure upright position.
- Protect from extremes of temperature. Store in a cool place.
- In the event of an accident, contain and collect spillage using sand or earth.
- Do not empty into drains or water courses.
- Dispose of any paint waste in accordance with appropriate local Environmental Regulations.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible respiratory protective equipment should be used.
- Contains no added lead and mercury.

(PLEASE REFER TO PRODUCT SAFETY DATA SHEET FROM DEALER AND REFER TO IT BEFORE USE.)

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: [Primers, sealers and undercoaters] 香港空氣污染管制(揮發性有機化合物)條例下受規管漆料的類別: [底漆、封固底劑及中層底漆]
VOC content (ready to use) = 27 gm/litre 揮發性有機化合物含量(即用狀態) = 27 克/公升

LIMITATION OF LIABILITY The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

For further information or if you have any concerns about using this product, please contact our Sales Department.

Any advice, recommendations, information, assistance or service provided by AkzoNobel in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel is provided without expressed or implied warranties.

Manufactured by:
Akzo Nobel Swire Paints (Guangzhou) Limited
Bei Wei Ind. Dist., Guangzhou E&T Development Zone, PRC.

Distributed by:
Akzo Nobel Swire Paints Limited
Tel: 2823 1388 Fax: 2866 3232
Website: www.akzonobel.com