

Dulux Odourless Anti-mould 5in1 Emulsion Paint H8851

Product Description

Dulux Odourless Anti-mould 5in1 Emulsion Paint is specially formulated with odourless function to ensure the home environment fresher and safer. Its excellent matt finish combined with five outstanding functions of odourless; mould & alkali resistant; moisture & water proof; washability and cover hair-line cracks, which provides all-round protection for interior walls. Moreover, it is easy to apply with high opacity and comes with a wide range of colours for selection, definitely your ideal choice for interior decorative paint!

Typical Uses

For use on new or previously painted interior masonry surface such as brickwork, plaster, cement and rendering.

Finish

Matt

Advantages

- Odourless
- Mould & alkali resistant
- Moisture & water proof
- Washability
- Covers hairline cracks
- High opacity
- Very matt & easy to apply

Composition (Nominal)

Acrylate Copolymer, Non-lead pigment, Additives & Water.

Volume Solids

White 40% (nominal), other colours will vary.

Drying Time

- Touch dry
- Recoat

Single coat at standard thickness (25°C, 50% R.H.):
0.5-1 hour
2-3 hours
Drying times vary depending on temperature and humidity.

Wet Film Thickness

80 µm

Dry Film Thickness

32 µm

Colour Range

White & Colour Palette 5 Colours

Pack Size

1L & 5L

Storage

Always store in cool & dry places and avoid freezing.

Theoretical Coverage

Theoretically 1 litre of this product covers 13~16 sqm in one coat. Coverage will vary considerably depending on application methods and surface roughness & porosity.

Application



Thinning

- Brush or Roller

Thin up to 20% (volume ratio) depend on different application methods & temperature. Do not over thin by adding more than 30% (volume ratio) of water. Stir well before use.

- Conventional Spray

For sealing new or bare surfaces thin with up to 1 part of clean water to 5-10 parts of paint (10-20%, volume ratio).

- Airless Spray

Add up to 1 part of clean water to 5 parts of paint (20%, volume ratio).

Ready for use.

Cleaning Up

Clean all equipment with clean water immediately after use.

Surface Preparation

Surfaces must be thoroughly clean, dry and free from all loose dirt, chalk or powder. New surfaces such as plaster and concrete should be fully dry before painting, with moisture content less than 14% and pH value below 10.

- New Wall

1. Fresh concrete must cure at least 30 days and meet application requirement before plastering.
2. The plaster must not be too soft. Sand and dust off after dry.
3. To resist alkalis and to obtain best results, first apply 1 coat of **Dulux Total Effect Odorless Primer A931-65968**.

- Previously Painted Surface

1. Remove powdery or flaking paint by scraping followed by using a suitable abrasive paper and dusting off.
2. Fill the defects with proper filler.
3. To resist alkalis and to obtain best results, first apply 1 coat of **Dulux Total Effect Odorless Primer A931-65968**.

Dulux Odourless Anti-mould 5in1 Emulsion Paint H8851

- Fungus Growth Wall

1. Remove all fungus by scraping followed by using a suitable abrasive paper and dusting off, or use **Polycell Mould Killer**.
2. To resist alkalis and to obtain best results, first apply 1 coat of **Dulux Total Effect Odorless Primer A931-65968**.

Notes for Use

1. Read the application instruction thoroughly before use.
2. Stir well before use.
3. Thin with clean water when necessary. Do not over dilute.
4. Do not hold too much paint on paint brush or roller.
5. Do not pour the diluted paint back to the original pack.
6. Recommended to use up opened paint quickly.

Typical Painting System

SURFACE	SYSTEM
Normal, Sound Surfaces	Primer: Dulux Total Effect Odorless Primer A931-65968K (1 coat) Finish: Dulux Odourless Anti-mould 5in1 Interior Emulsion Paint H8851 (2 coats)

Application Precautions

- Apply above 10°C (surface temperature) in dry condition. Do not apply when relative humidity is 85% or above.
- Suggest closing the window and turn on the dehumidifier when counters the high humidity or larger temperature difference issue.
- When applying deep or bright colours, please control the dilution ratio within 5% (volume ratio). You will need to apply more coats than normal for opacity.

Safety, Health and Environmental Information

- Keep container tightly close and out of reach of children.
- A suitable cartridge mask should be worn when rubbing down.
- Ensure good ventilation during application and drying.
- Do not breathe vapour/spray.
- In case of insufficient ventilation during spraying wear suitable respiratory equipment.
- All respiratory equipment must meet (NOISH/MSHA) approved standard.
- When applying paint, it is advisable to wear suitable eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin: use soap and water or a recognized skin cleaner.
- If swallowed, seek medical advice immediately and show this container or label.
- Care must be taken when transporting paint. Keep container in a secure upright position.
- Protect from extremes of temperature. Store in a cool place.
- In the event of an accident, contain and collect spillage using sand or earth. Do not empty into drains or water courses. Dispose of any paint waste in accordance with local environmental regulations.

(PLEASE REQUEST PRODUCT SAFETY DATA SHEET FROM PRODUCT DEALER AND REFER TO IT BEFORE USE.)

Note: The product performance and application materials listed above are obtained under laboratory conditions, but the actual use environment of the product is various and not subject to our constraints. If you are unclear, please contact us. The right to interpret and amend the product's instruction manual is reserved.

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: [Flat coatings]
VOC content (ready to use) = 5 gm/litre

LIMITATION OF LIABILITY The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

For further information or if you have any concerns about using this product, please contact our Sales Department.

Any advice, recommendations, information, assistance or service provided by AkzoNobel in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel is provided without expressed or implied warranties.

Manufactured by:
Akzo Nobel Swire Paints (Guangzhou) Limited
Bei Wei Ind. Dist., Guangzhou E&T Development Zone, PRC.

Distributed by:
Akzo Nobel Swire Paints Limited
Tel: 2823 1388 Fax: 2866 3232
Website: www.akzonobel.com