

# DULUX AMBIANCE MARBLE



<b>Product Name</b>	Dulux Ambiance Marble
<b>Description and Usage</b>	<p>Dulux Ambiance Special Effects Paints include the finest featured finishes and textures to create endless unique combinations to personalise your world.</p> <p>Dulux Ambiance Marble is inspired by the natural beauty of rock, creating the luxurious look of marble finish on your walls.</p>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Ready-to-use; trowel applied emulsion paint</li><li>• Luxurious marble/stone effect depending on the way of application</li><li>• Optimized rheology and open time for better application</li></ul>
<b>Pack Size</b>	Available only in 1 kg pack
<b>Colour Range</b>	See appropriate Colour Card
<b>Film Properties</b>	
<i>Water Resistance</i>	Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.
<b>Composition (nominal)</b>	<p>Pigment : Light-fast non-lead/chrome pigment and mineral extenders</p> <p>Binder : Waterborne Polymer</p> <p>Solvent : Water</p>
<b>Drying Times</b>	Single coat at standard thickness:
<i>Touch Dry</i>	1-2 hours
<i>Recoat</i>	4-8 hours
	Drying time may vary according to temperature and humidity.
<b>Theoretical Coverage</b>	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 3 m <sup>2</sup> /kg/coat.
<b>Application</b>	Trowel
<b>Dilution</b>	Ready to use. No dilution
<b>Cleaning Up</b>	Clean all equipment with clean water immediately after use.
<b>Surface Preparation</b>	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with Fungicidal Wash. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.

# DULUX AMBIANCE MARBLE



## Recommended Application Conditions

- Dulux Ambiance Marble is recommended for interior walls only.
- Avoid windy conditions in the room.
- Room temperature should ideally be between 20°C and 35°C.
- Very hot, dry conditions are to be avoided.
- Use of any other paint apart from the specially formulated Dulux Ambiance Marble may deviate from the desired finish and make it hard to recondition.

## Primer

Prime surface with a coat of appropriate Dulux Interior Primer first.

## Dulux Ambiance Marble

Apply 3 coats of Dulux Ambiance Marble in required colour with trowel. For the first coat, ensure uniform deposition completely hiding the surface. For the second coat, apply a thin layer of the product in a random manner. For the last coat, apply a very thin layer of the product smoothening it at the same time onto the surface with the blade of the trowel. Buff to attain satin or gloss finish. Sand the surface between the 3 coats with appropriate emery paper. Ensure 4 -6 hours drying time between coats. This effect finish is not washable. Please use dry cloth to clean the wall if needed.

## System Information

*Powdery and Alkaline Surfaces*

Sealer (1 coat)

Special effect (3 coats)

Dulux Interior Primer SB

Dulux Ambiance Marble

*New, Normal, Sound Surfaces*

Dulux Interior Primer WB

## Health, Safety and Environment Information

Product Safety Data Sheet available upon request.

**For further information or if you have any concerns about using this product, contact us at:**

### Akzo Nobel Decorative Paints L.L.C.

11<sup>th</sup> and 12<sup>th</sup> floor, Al Habtoor Business Tower  
Dubai, UAE  
Tel: (971)43990417  
Email: [dulu.arabia@akzonobel.com](mailto:dulu.arabia@akzonobel.com)  
Website: [www.duluxarabia.com](http://www.duluxarabia.com)

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.