


DULUX AMBIANCE MATT



Product Name	Dulux Ambiance Matt
Description and Usage	<p>Dulux Ambiance Matt is a premium interior emulsion paint especially formulated to provide anti-bacterial properties, outstanding washability and low odour.</p> <p>Dulux Ambiance Matt is suitable on new or previously painted masonry surfaces such as brickwork, plaster, cement, rendering and semi-permanent interior finishes.</p>
Benefits	<ul style="list-style-type: none"> • Anti-mould & anti-fungus properties • Anti-bacterial properties • Excellent coverage & strong hiding power • Superior washability • Long lasting & brighter colours • Smooth finish • Low VOC & low odour • No added lead & mercury
Pack Size	<p>1 & 4 Litre: White, Base A, Base B, Base C, Base D</p> <p>16.5 Litre: Base A, Base B; 17 Litre: Base C, Base D; 18 Litre: White</p>
Colour Range	See appropriate Colour Card
Film Properties	
<i>Chemical Resistance</i>	Resistant to mild atmospheric fume attack and to the salts in new mortar, rendering and similar surfaces.
<i>Water Resistance</i>	Resistant to the levels of atmospheric humidity normally experienced in exterior environment.
Composition (nominal)	<p>Pigment : Lightfast Non-lead Pigments</p> <p>Binder : Acrylic Emulsion</p> <p>Solvent : Water</p>
Volume Solids	White 38%, other colours will vary
Drying Times	Single coat at standard thickness:
<i>Touch Dry</i>	Dependent on temperature and humidity
<i>Recoat</i>	2 – 4 hours
Film Thickness	29 – 34 microns dry film thickness
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 11 – 13 m ² /litre.

Application



DULUX AMBIANCE MATT



Thinning	
<i>Brush or Roller</i>	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).
<i>Conventional Spray</i>	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 3 parts of paint (30%).
<i>Airless Spray</i>	Ready for use. Thinning is usually not required.

Spray Recommendations

<i>Conventional Spray</i>	Satisfactory through most equipment.
<i>Airless Spray</i>	A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² with a spray tip size 0.58mm and a spray tip angle 65°.

Cleaning Up

Clean all equipment with clean water immediately after use.

Surface Preparation

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with Fungicidal Wash. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.

System Information	Sealer (1 coat)	Finish (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Dulux Interior Primer SB	Dulux Ambiance Matt
<i>New, Normal, Sound Surfaces</i>	Dulux Interior Primer WB	

Health, Safety and Environment Information

Product Safety Data Sheet available upon request.

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.