

# DULUX EASYCLEAN SILK



<b>Product Name</b>	Dulux EasyClean Silk
<b>Description and Usage</b>	<p>Dulux EasyClean Silk is a premium quality washable acrylic paint for use on all interior walls where a subtle, elegant silk finish is required. It has the advantages of unmatched stain resistance and outstanding scrubability combined with low odour, non-yellowing, easy application and water clean-up.</p> <p>Dulux EasyClean Silk is suitable on new or previously painted masonry surfaces such as brickwork, plaster, cement, rendering and semi-permanent interior finishes.</p>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>• KidProof Technology, tough stain repellent</li> <li>• Anti-bacterial property</li> <li>• Washable &amp; easy cleaning</li> <li>• Outstanding scrub resistance</li> <li>• Long lasting &amp; brighter colours</li> <li>• Low VOC &amp; low odour</li> <li>• No added lead &amp; mercury</li> </ul>
<b>Pack Size</b>	<p>1 &amp; 4 Litre: White, Base A, Base B, Base C, Base D</p> <p>16.5 Litre: Base A, Base B; 17 Litre: Base C, Base D; 18 Litre: White</p>
<b>Colour Range</b>	See appropriate Colour Card
<b>Film Properties</b>	
<i>Water Resistance</i>	Resistant to the levels of atmospheric humidity normally experienced in interior environment.
<b>Composition (nominal)</b>	<p>Pigment : Lightfast Non-lead Pigments</p> <p>Binder : Acrylic Emulsion</p> <p>Solvent : Water</p>
<b>Volume Solids</b>	White 40%, other colours will vary
<b>Drying Times</b>	Single coat at standard thickness:
<i>Touch Dry</i>	Dependent on temperature and humidity
<i>Recoat</i>	2 – 4 hours
<b>Film Thickness</b>	30 – 36 microns dry film thickness
<b>Theoretical Coverage</b>	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 11 – 12 m <sup>2</sup> /litre.

## Application



# DULUX EASYCLEAN SILK



<b>How to remove stains</b>	<p>For the best performance of the KidProof technology, please ensure 1 – 2 weeks of proper curing on wall after application for paint film to dry completely</p> <ul style="list-style-type: none"> <li>• Stains are easier to remove if the wall surface is smooth</li> <li>• Stains are easier to remove when fresh, recommend cleaning immediately</li> <li>• Use a mild detergent solution or toilet soap solution on wet soft cotton cloth or sponge to clean stains</li> <li>• Wipe the stains gently without pressure</li> <li>• After cleaning the stains, wipe with a clean dry cloth while the surface is still wet</li> </ul>	
<b>Thinning</b>		
<i>Brush or Roller</i>	<p>For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).</p>	
<i>Conventional Spray</i>	<p>For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 3 parts of paint (30%).</p>	
<i>Airless Spray</i>	<p>Ready for use. Thinning is usually not required.</p>	
<b>Spray Recommendations</b>		
<i>Conventional Spray</i>	<p>Satisfactory through most equipment.</p>	
<i>Airless Spray</i>	<p>A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm<sup>2</sup> with a spray tip size 0.58mm and a spray tip angle 65°.</p>	
<b>Cleaning Up</b>	<p>Clean all equipment with clean water immediately after use.</p>	
<b>Surface Preparation</b>		
	<p>Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with Fungicidal Wash. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.</p>	
<b>System Information</b>	<p>Sealer (1 coat) <span style="float: right;">Finish (2 coats)</span></p>	
<i>Powdery and Alkaline Surfaces</i>	<p>Dulux Interior Primer SB <span style="float: right;">Dulux EasyClean Silk</span></p>	
<i>New, Normal, Sound Surfaces</i>	<p>Dulux Interior Primer WB</p>	
<b>Health, Safety and Environment Information</b>	<p>Product Safety Data Sheet available upon request.</p>	

For further information or if you have any concerns about using this product, contact us at:

**Akzo Nobel Decorative Paints L.L.C.**  
 11<sup>th</sup> and 12<sup>th</sup> floor, Al Habtoor Business Tower  
 Dubai, UAE  
 Tel: (971)43990417  
 Email: dulux.arabia@akzonobel.com  
 Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.