

DULUX INSPIRE INTERIOR SILK



Product Name	Dulux Inspire Interior Silk						
Description and Usage	<p>Dulux Inspire Interior Silk is high quality water-based emulsion paint for both new and (appropriately primed) previously painted interior masonry surfaces. It is specially formulated for durability and longer lasting colour.</p> <p>Dulux Inspire Interior Silk is suitable on new or previously painted masonry surfaces such as brickwork, plaster, cement, rendering and semi-permanent interior finishes.</p>						
Benefits	<ul style="list-style-type: none"> • Long lasting colour • Good coverage • Low odour and VOC 						
Pack Size	<p>1 & 4 Litre: White, Base A, Base B, Base C, Base D</p> <p>16.5 Litre: Base A, Base B; 17 Litre: Base C, Base D; 18 Litre: White</p>						
Colour Range	See appropriate Colour Card						
Film Properties							
<i>Water Resistance</i>	Resistant to the levels of atmospheric humidity normally experienced in interior environment.						
Composition (nominal)	<table border="0"> <tr> <td>Pigment</td> <td>: Non-lead Pigments</td> </tr> <tr> <td>Binder</td> <td>: Styrene-Acrylic Emulsion</td> </tr> <tr> <td>Solvent</td> <td>: Water</td> </tr> </table>	Pigment	: Non-lead Pigments	Binder	: Styrene-Acrylic Emulsion	Solvent	: Water
Pigment	: Non-lead Pigments						
Binder	: Styrene-Acrylic Emulsion						
Solvent	: Water						
Volume Solids	White 35 % ± 2, other colours will vary						
Drying Times	Single coat at standard thickness:						
<i>Touch Dry</i>	Dependent on temperature and humidity						
<i>Recoat</i>	1 - 2 hours						
Film Thickness	30 – 40 microns dry film thickness						
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 9 – 12 m ² /litre/coat.						
Application							

DULUX INSPIRE INTERIOR SILK



Thinning							
<i>Brush or Roller</i>	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).						
<i>Conventional Spray</i>	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 3 parts of paint (30%).						
<i>Airless Spray</i>	Ready for use. Thinning is usually not required.						
Surface Preparation							
<i>Conventional Spray</i>	Satisfactory through most equipment.						
<i>Airless Spray</i>	A typical set up for airless spray application would be minimum working pressure on paint of 140 kg/cm ² with a spray tip size 0.58 mm and a spray tip angle 65°.						
Cleaning Up	Clean all equipment with water immediately after use.						
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with Dulux Fungicidal Wash. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.						
System Information	<table border="1"> <tr> <td><i>Powdery and Alkaline Surfaces</i></td> <td>Sealer (1 coat) Dulux Interior Primer (SB)</td> <td>Finish (2 coats) Dulux Inspire Interior Silk</td> </tr> <tr> <td><i>New, Normal, Sound Surfaces</i></td> <td>Dulux Interior Primer (WB)</td> <td></td> </tr> </table>	<i>Powdery and Alkaline Surfaces</i>	Sealer (1 coat) Dulux Interior Primer (SB)	Finish (2 coats) Dulux Inspire Interior Silk	<i>New, Normal, Sound Surfaces</i>	Dulux Interior Primer (WB)	
<i>Powdery and Alkaline Surfaces</i>	Sealer (1 coat) Dulux Interior Primer (SB)	Finish (2 coats) Dulux Inspire Interior Silk					
<i>New, Normal, Sound Surfaces</i>	Dulux Interior Primer (WB)						
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.						

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
 11th and 12th floor, Al Habtoor Business Tower
 Dubai, UAE
 Tel: (971)43990417
 Email: dulux.arabia@akzonobel.com
 Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.