

Dulux Stucco Putty Exterior



Product Name	Dulux Stucco Putty Exterior
Description and Usage	<p>Dulux Stucco Putty Exterior is a lightweight, easy to use filler, specially formulated for use on wood, masonry, concrete etc. It can be used both inside and outside for marking good minor imperfections in the substrate.</p> <p>Dulux Stucco Putty Exterior is suitable for exterior decorative look and design finish. It hides irregularities on substrates such as plaster, concrete building boards, plywood etc.</p>
Benefits	<ul style="list-style-type: none">• Good filling• Smooth finish• No cracking
Pack Size	4 Litre and 18 Litre
Colour Range	White only
Film Properties	
<i>Water Resistance</i>	Will tolerate a slightly damp surface but is not suitable where the surface is saturated.
Composition (nominal)	Pigment : Non-lead Pigments Binder : Acrylic Co-polymer Emulsion Solvent : Water
Volume Solids	White 55% ± 2
Drying Times	Single coat at standard thickness: <i>Touch Dry</i> Dependent on temperature and humidity <i>Recoat</i> 8 - 10 hours
Film Thickness	75 – 132 microns dry film thickness
Theoretical Coverage	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 4 – 7 m ² /litre.
Application	Trowel or Putty knife
Thinning	Up to 3% clean water if required to achieve application consistency.
Cleaning Up	Clean all equipment with clean water immediately after use.

Dulux Stucco Putty Exterior



Surface Preparation	Dulux Stucco Putty Exterior should be applied on primed surfaces in new painting or previously painted surface. Sand the surface after it has completely dried and remove all loose powder. Overcoat the putty with a suitable primer.			
System Information	Sealer (1 coat)	Putty (1 coat)	Sealer (1 coat)	Finish (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Dulux Exterior Primer SB		Dulux Exterior Primer SB	
<i>New, Normal, Sound Surfaces</i>	Dulux Weathershield Primer WB	Dulux Stucco Putty Exterior	Dulux Weathershield Primer WB	Dulux exterior range of products
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.			

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.