



# SAFETY DATA SHEET

## SIDIROSTOKOS Comp.B

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : SIDIROSTOKOS Comp.B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Putty (ready mixed filler).

#### 1.3. Details of the supplier of the safety data sheet

VIVECHROM ,  
Thesi Vathi Pigadi,  
196 00 Mandra Attikis, Greece  
Tel. +30 210 5538700,  
Fax. +30 210 5550464,  
www.vivechrom.gr

**e-mail address of person responsible for this SDS** : HSE.GR@akzonobel.com

#### 1.4 Emergency telephone number

**Telephone number** : Emergency phone number of the Company  
Tel. +30(210) 5538700 (24 Hours/day, every day) & 801 11 55600 (8:00 - 16:00)  
Official advisory body (Greece)  
Tel. +30 (210) 7793 777, (24 Hours/day, every day)

**Version** : 13

**Date of previous issue** : 24-12-2018

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Org. Perox. E, H242

Eye Irrit. 2, H319

Skin Sens. 1, H317

Aquatic Acute 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

**Ingredients of unknown toxicity** : 0%

**Ingredients of unknown ecotoxicity** : 0%

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : H242 - Heating may cause a fire.  
H319 - Causes serious eye irritation.  
H317 - May cause an allergic skin reaction.  
H410 - Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

**General** : P102 - Keep out of reach of children.  
P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P220 - Keep away from clothing, incompatible materials and combustible materials.  
P234 - Keep only in original container.

**Response** : P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage** : P403 - Store in a well-ventilated area.  
P235 - Keep cool.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.

**Hazardous ingredients** : Dibenzoyl peroxide

**Supplemental label elements** : Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Special packaging requirements

**SIDIROSTOKOS Comp.B****SECTION 2: Hazards identification**

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

**2.3 Other hazards**

**Voluntary label element (CEPE)** : Not applicable.

**Other hazards which do not result in classification** : ☒ None known.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Dibenzoyl peroxide	REACH #: 01-2119511472-50 EC: 202-327-6 CAS: 94-36-0 Index: 617-008-00-0	≥45 - ≤65	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H410 (M=1)	[1] [2]
dimethyl phthalate	REACH #: 01-2119457857-21 EC: 203-872-2 CAS: 111-46-6 Index: 603-140-00-6	≥25 - ≤35	<i>Substance with a Community workplace exposure limit</i>	[1]
ethanediol	REACH #: 01-2119456816-28 EC: 203-328-4 CAS: 107-21-1	≥0.1 - ≤9.9	Acute Tox. 4, H302 STOT RE 2, H373 <b>See Section 16 for the full text of the H statements declared above.</b>	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- ☒ [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII  
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  
 [5] Substance of equivalent concern  
 [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**SECTION 4: First aid measures**

- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Wash clothing before reuse.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains dibenzoyl peroxide. May produce an allergic reaction.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

- Hazards from the substance or mixture** : Fire will produce dense black smoke. CAUTION: May re-ignite itself after fire is extinguished. Material supports combustion. In case of fire and/or explosion do not breathe fumes. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**5.3 Advice for firefighters**

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). The waste should NOT be confined. Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Avoid confinement. Do not allow to dry out. Avoid shock and friction. Explosive when dry.
- Information on fire and explosion protection**  
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use explosion-proof electrical (ventilating and lighting) equipment.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from reducing agents, heavy metal compounds and alkaline and acidic materials.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep only in the original container.

## SECTION 7: Handling and storage

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Dibenzoyl peroxide	Υπουργείο Εργασίας και Κοινωνικών Υποθέσεων (Greece, 2/2012). TWA: 5 mg/m <sup>3</sup> 8 hours.
Dimethyl phthalate	Υπουργείο Εργασίας και Κοινωνικών Υποθέσεων (Greece, 2/2012). TWA: 5 mg/m <sup>3</sup> 8 hours.

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

No DNELs/DMELs available.

#### PNECs

No PNECs available

### 8.2 Exposure controls

- Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. Use explosion-proof ventilation equipment.

#### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

#### Skin protection

## SECTION 8: Exposure controls/personal protection

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that the gloves are free from defects and that they are stored and used correctly.

- |  |   |
|--|---|
| <b>Body protection</b>                 | : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres. Wash clothing before reuse.   |
| <b>Other skin protection</b>           | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| <b>Respiratory protection</b>          | : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.  |
| <b>Environmental exposure controls</b> | : Do not allow to enter drains or watercourses.   |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

- |   |  |
|---|--|
| <b>Physical state</b>                               | : Solid.   |
| <b>Colour</b>                                       | : Various: See label.                                  |
| <b>Odour</b>  | : Not available.                                       |
| <b>Odour threshold</b>                              | : Not available.                                       |
| <b>pH</b>   | : Not available.                                       |
| <b>Melting point/freezing point</b>                 | : Not available.                                       |
| <b>Initial boiling point and boiling range</b>      | : 163°C  |
| <b>Flash point</b>                                  | : Closed cup: 62°C                                     |
| <b>Evaporation rate</b>                             | : Not available.                                       |
| <b>Upper/lower flammability or explosive limits</b> | : Not available.                                       |
| <b>Vapour pressure</b>                              | : Not available.                                       |
| <b>Vapour density</b>                               | : Not available.                                       |
| <b>Relative density</b>                             | : 1.2  |
| <b>Solubility(ies)</b>                              | : Insoluble in the following materials: cold water.    |
| <b>Partition coefficient: n-octanol/water</b>       | : Not available.                                       |
| <b>Auto-ignition temperature</b>                    | : Not available.                                       |
| <b>Decomposition temperature</b>                    | : Not available.                                       |
| <b>Viscosity</b>                                    | : Kinematic (room temperature): 700 cm <sup>2</sup> /s |



**SIDIROSTOKOS Comp.B****SECTION 9: Physical and chemical properties****Explosive properties** : Not available.**Oxidising properties** : Not available.**9.2. Other information****Solubility in water** : Not available.**SECTION 10: Stability and reactivity****10.1 Reactivity** : ☒ No specific test data related to reactivity available for this product or its ingredients.**10.2 Chemical stability** : Hazardous reactions or instability may occur under certain conditions of storage or use.**10.3 Possibility of hazardous reactions** : ☒ Under normal conditions of storage and use, hazardous reactions will not occur.**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
SADT (Self-Accelerating Decomposition Temperature) is the lowest temperature at which self-accelerating decomposition may occur with a substance in the packaging as used for transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at or above the SADT. Contact with incompatible substances can cause decomposition at or below the SADT.  
Avoid shock and friction.**10.5 Incompatible materials** : Keep away from rust, iron and copper. Contact with incompatible materials, such as acids, alkalis, heavy metal compounds and reducing agents, will result in hazardous decomposition. Do not mix with peroxide accelerators.**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains dibenzoyl peroxide. May produce an allergic reaction.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
<input checked="" type="checkbox"/> Dibenzoyl peroxide	LD50 Dermal	Rabbit	11890 mg/kg	-
	LD50 Intraperitoneal	Mouse	9719 mg/kg	-
	LD50 Intraperitoneal	Rat	7.7 g/kg	-
	LD50 Intravenous	Rat	6565 mg/kg	-
	LD50 Oral	Cat	3300 mg/kg	-
	LD50 Oral	Cat	3400 mg/kg	-
	LD50 Oral	Dog	9 g/kg	-
	LD50 Oral	Dog	9900 mg/kg	-
	LD50 Oral	Guinea pig	7800 mg/kg	-



## SIDIROSTOKOS Comp.B

**SECTION 11: Toxicological information**

LD50 Oral	Guinea pig	8000 mg/kg	-
LD50 Oral	Mouse	23700 mg/kg	-
LD50 Oral	Mouse	2300 mg/kg	-
LD50 Oral	Rabbit	26.9 g/kg	-
LD50 Oral	Rabbit	4400 mg/kg	-
LD50 Oral	Rat	12565 mg/kg	-
LD50 Oral	Rat	12000 mg/kg	-
LD50 Route of exposure unreported	Guinea pig	14 g/kg	-
LD50 Route of exposure unreported	Mouse	13300 mg/kg	-
LD50 Route of exposure unreported	Rabbit	2688 mg/kg	-
LD50 Route of exposure unreported	Rat	15650 mg/kg	-
LD50 Subcutaneous	Rat	18800 mg/kg	-
LDLo Intramuscular	Rabbit	4472 mg/kg	-
LDLo Intramuscular	Rat	7826 mg/kg	-
LDLo Intravenous	Rabbit	2236 mg/kg	-
LDLo Oral	Child	0.2 g/kg	-
LDLo Oral	Human	0.23 g/kg	-
LDLo Oral	Human	0.75 mg/kg	-
LDLo Subcutaneous	Mouse	5 g/kg	-
LDLo Subcutaneous	Mouse	5000 mg/kg	-
TDLo Oral	Child	2400 mg/kg	-
TDLo Oral	Man - Male	1.7 g/kg	-
TDLo Oral	Rat	16000 mg/kg	-
TDLo Route of exposure unreported	Mammal - species unspecified	6 mL/kg	-
TDLo Route of exposure unreported	Rat	10 g/kg	-
TDLo Route of exposure unreported	Rat	10000 mg/kg	-
TDLo Route of exposure unreported	Rat	2000 mg/kg	-

**Conclusion/Summary** : Not available.

**Acute toxicity estimates**

Route	ATE value
Oral	5000 mg/kg

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dibenzoyl peroxide	Eyes - Mild irritant Skin - Severe irritant	Rabbit Human	- -	- -	- - -

**Conclusion/Summary** : Not available.

**Sensitisation**

**Conclusion/Summary** : Not available.

**Mutagenicity**

**Conclusion/Summary** : Not available.

**SECTION 11: Toxicological information****Carcinogenicity**

Conclusion/Summary : Not available.

**Reproductive toxicity**

Conclusion/Summary : Not available.

**Teratogenicity**

Conclusion/Summary : Not available.

**Specific target organ toxicity (single exposure)**

Not available.

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Dibenzoyl peroxide	Category 2	Not determined	Not determined

**Aspiration hazard**

Not available.

Other information : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> Dibenzoyl peroxide	Acute EC50 0.06 mg/l Acute EC50 0.11 mg/l Acute LC50 0.06 mg/l	Algae Daphnia - Daphnia Magna Fish	72 hours 48 hours 96 hours

Conclusion/Summary : Not available.

**12.2 Persistence and degradability**

Conclusion/Summary : Not available.

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<input checked="" type="checkbox"/> Dibenzoyl peroxide	3.2	-	low

**12.4 Mobility in soil**Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

**12.5 Results of PBT and vPvB assessment**

PBT : Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.



## SECTION 14: Transport information

**Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.**

	ADR	IMDG
<b>14.1 UN number</b>	UN3108	UN3108
<b>14.2 UN proper shipping name</b>	ORGANIC PEROXIDE TYPE E, SOLID (Dibenzoyl peroxide)	ORGANIC PEROXIDE TYPE E, SOLID (Dibenzoyl peroxide). Marine pollutant (Dibenzoyl peroxide)
<b>14.3 Transport hazard class(es) Class</b>	5.2	5.2
<b>Subsidiary class</b>	-	-
<b>14.4 Packing group</b>	Not applicable.	Not applicable.

**SIDIROSTOKOS Comp.B**

**Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.**

14.5 Environmental hazards Marine pollutant  Marine pollutant substances	Yes.	Yes.  Dibenzoyl peroxide
14.6 Special precautions for user	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
HI/Kemler number  Emergency schedules (EmS)	Not applicable.	F-J, S-R
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code : Not applicable.		
Additional information	 The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Tunnel code</b> D	 The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-J, S-R

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not applicable.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Seveso Directive

SIDIROSTOKOS Comp.B

**SECTION 15: Regulatory information**

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

International regulationsChemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment**

: No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**CEPE code** : 6

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Org. Perox. E, H242 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H410	Expert judgment Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H241	Heating may cause a fire or explosion.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

**SECTION 16: Other information**

Acute Tox. 4, H302 Aquatic Chronic 1, H410 Eye Irrit. 2, H319 Org. Perox. B, H241 Org. Perox. E, H242 Skin Sens. 1, H317 STOT RE 2, H373	ACUTE TOXICITY (oral) - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 ORGANIC PEROXIDES - Type B ORGANIC PEROXIDES - Type E SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
--	---

**Date of printing** : 18-6-2019

**Date of issue/ Date of revision** : 18-6-2019

**Date of previous issue** : 24-12-2018

**Version** : 13

**Notice to reader**

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

**Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.**

**Head Office**

**AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands**