

#### SAFETY HEALTH AND ENVIRONMENTAL INFORMATION:

- No added Lead, Mercury & chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million
- Treatments such as sanding, burning off etc of paint films may generate hazardous dust and other fumes. Wet sanding/flaming should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment
- Wear eye/hand protection
- Do not breathe gas/fumes/vapour /spray
- Use only in well ventilated areas
- Remove as much paint as possible from brushes and rollers before cleaning
- Keep away from food, drinks and animal feed
- Store in a cool and shaded place
- Container must be in a secure, upright position and be tightly closed. Do not use empty container for storing food
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Safety data sheet available for professional/user on request
- Do not empty into drains or water course
- Do not eat, drink or smoke when using this product.
- Keep away from combustible material.
- In case of fire use foam, dry powder, AFFF or CO2 fire extinguisher- Never use water jet.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower and soap or a proprietary skin cleanser. Do not use solvents or thinners.
- Lift with care – gross weight may exceed 10 kg



#### WARNINGS:

##### Hazard Statements

- Flammable liquid and vapour.
- May cause an allergic skin reaction.
- Harmful to aquatic life with long lasting effects.



##### Precautionary statements

- Keep out of reach of children
- If medical advice is needed, have product container or label at hand
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not get in eyes, on skin or on clothing
- Keep container tightly closed.
- Call a POISON CENTER or doctor if you feel unwell.
- Keep cool.
- Dispose of contents and container in accordance with all local, regional, national or international regulations.

#### CONTACT US:

In case of any complaints please contact, Complaint Management Cell, ICI India Ltd., Infinily Towers A, 7th floor, DLF Cyber City, Phase II, Gurgaon -122002, Haryana, India, Ph: 0124-326608. For more information on our products, visit us at [www.icidulux.co.in](http://www.icidulux.co.in) Note: The information provided above may change without prior notice.

#### CONTACT US:

Registered office,  
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071  
In case of any complaints please contact Customer care cell,  
Akzo Nobel India Ltd., Infinity Tower A, 7th Floor, DLF Cyber City, Phase 11, Gurgaon-122002, Haryana, India,  
Ph: 0124-3266087  
Note: The information provided above may change without prior notice.



Introducing the all new

# PROMISE ENAMEL

Product Data Sheet



AkzoNobel

## DULUX PROMISE ENAMEL

### PRODUCT DESCRIPTION:


Dulux Promise Enamel is an economy enamel paint recommended for metal, wood. It is especially formulated with Chroma bright technology to give a smooth finish with excellent Colour. It also has good binding ability because of cross linking Alkyd technology. It is ideal for painting household items & furniture like MS, Wood & even walls.

### PRODUCT FEATURES AND BENEFITS:

Dulux Promise Enamel gives a smooth mirror like finish & has good durability & coverage; it is ideal for painting household items & furniture like MS, wood & even walls. For best results relevant proper priming is recommended.



**Chroma Brite Technology**  
for rich and bright shades



**Cross Linking Alkyd Technology**  
for good binding abilities

### PRODUCT RELATED INFORMATION:

#### Film Composition:

**Pigment :** Non-Lead & Chrome Pigments

**Extender Binder:** Oil Modified Polyester

**Solvent :** Mainly White Spirit with other non-toxic solvents

**Color Range:** As per shade card

**Gloss/Sheen Level:** Glossy Finish

**Stability of Thinned Paint:** Can be used within 24 hours of thinning after mixing. After that stir is thoroughly before use.

**Theoretical Coverage:** Under normal condition, it is 80 -100 sq.ft/ltr. for 2 coats. However, this can show wide variation depending on actual type/condition of cement

**Pack Size:** Available in 0.5,1, 4, 10 & 20 litres.

### APPLICATION RELATED INFORMATION:

Before application, read the safety, health and environmental information and the precautions given below.



#### Application Tool:

Can be applied by Brush, Roller & Spray.

**Surface Preparation:** Ensure Surface is dry & free from grime, dust, and grease. Remove loose or flaking particles. Sand the surface by using Emery paper No. 180 & wipe clean. For pre painted surface, where putty application is not expected use Emery paper No. 320 & wipe clean.



#### Thinning:

**Brush or Roller:** For best result, add up to 1 parts White Spirit/ Mineral Turpentine Oil (MTO) to 10 parts of paint by volume



**Conventional Spray:** Add up to 2.0 parts White Spirit/MTO to 10 parts of paint (20%) by volume depending on specification of the gun.



#### GENERAL RECOMMENDATIONS

**Brushing & Conventional Spray:** Very suitable for both type of application.

**Cleaning Up:** Clean all equipment with White Spirit / Mineral Turpentine Oil immediately after use.

#### SYSTEM INFORMATION

**Metal surface:** Primer (1 coat) - Dulux Red Oxide Metal Primer (34-100)  
Finish (2 coats) - Dulux Promise Enamel

**Wood surface:** Primer (1 coat) - Dulux Wood Primer White (34-300)  
or Dulux Wood Primer Pink (32-129)  
Finish (2 coats) - Dulux Promise Enamel

**Masonry surface :** Primer (1 coat) - Dulux Cement Primer (34-1200)  
Finish (2 coats) - Dulux Promise Enamel

**Re painted surface:** Primer (1 coat) - (not required)  
Finish (2 coats) - Dulux Promise Enamel

**Drying Time:** Single coat at standard thickness

Tack Free: Within 4-6 hours

For further details, carefully read the information on containers as well.

#### Post Painting Care:

For removing stains: Use Sponge, clean with a mild soap solution and wipe clean. Ensure a cleaning after 1 week of application.

