

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION:

- No added Lead, Mercury & chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million.
- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- No Known significant effects or critical hazards.
- Keep out of the reach of children
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin or on clothing.
- Call a POISON CENTER or physician if you feel unwell.
- Dispose of contents and containers in accordance with all local, regional, national and international regulations
- Remove as much paint as possible from brushes and rollers before cleaning.
- Safety data sheet available for professional/ user on request.
- Lift with care – gross weight may exceed 10 kg for 10 lit and above.

PRECAUTIONS:

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not apply on damage surface.
- Do not over thin or overextend the brush.
- Stir thoroughly before use.
- Tinted paint must be thoroughly mixed/shake immediate after the tinter addition.
- It is recommended to use Dulux colorants only for making the shades.

CONTACT US:

Registered office,
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071
In case of any complaints please contact Customer care cell,
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,
Haryana, India

Note: The information provided above may change without prior notice.



PROMISE

SHEEN

INTERIOR

PRODUCT DATA SHEET




PRODUCT DESCRIPTION :


Dulux Promise Sheen Interior Emulsion is a high quality, water based acrylic emulsion paint which provides high sheen to your walls. Its Chroma Brite Glow Technology keeps the interior wall Colour brighter for longer. It is equipped with good coverage and good opacity formula which gives a rich finish to walls and its unique Anti Chalking properties prevents the paint film from chalking giving a fresh & bright look to your walls for many years to come.




PRODUCT FEATURES AND BENEFITS :




Rich & soothing sheen finish gives the walls a premium look




Chroma Brite technology ensures bright colors for a fresh look



Advance Anti chalking formula provides excellent resistance against chalking



Good Coverage and Good Opacity
Good coverage formula helps to provide better coverage than any standard exterior emulsions.



Smooth Finish
Good flow & levelling ensures the proper, rich finish over the wall

PRODUCT RELATED INFORMATION :

Film Composition:

Pigment : Light fast Non-Lead/Chrome pigment
Binder : Acrylic Co-polymer Emulsion
Solvent : Water
Colour Range : As per AkzoNobel shade offering

Volatile organic compound (VOC) level in White & bases : <50 gm/litre (Excluding tinter).

Gloss/Sheen Level : High sheen

Flash Point (IS 101/1987, Part 1, Sec 6) : Non-Flash

Stability of Thinned Paint : Can be used within 24 hours of thinning after mixing

Dry Film Thickness (Calculated) : 30-35 microns at coverage of 80-100 sqft / litre for 2 coats.

Theoretical Coverage : 80-100 sqft / litre/2 coats
(The Spreading capacity/coverage of this product will vary considerably according to the roughness and porosity of the surface also the surface preparation)

Shelf Life:

- 3 years from the Date of Manufacturing in the original sealed condition.
- Store under cover, away from direct sunlight and protect from extreme temperature.
- In hot temperature conditions, it must be stored in a temperature-controlled environment i.e. less than 30 Deg c.

Number of shades offered : 1200+

Pack Size : Available in 1,4, 10 & 20 liters

APPLICATION RELATED INFORMATION:

Before application, read the safety, health and environmental information and the precautions given below.



Application Tool :
Suitable for application by brush or roller.



Surface Preparation :

- Freshly Plastered surfaces must be allowed to cure completely.
- Ensure surface is thoroughly clean, dry and free from all loose dirt, chalk, grease, fungi, wax and flaking paint.
- All surfaces should be thoroughly rubbed down using a suitable abrasive paper and thereafter wiped off.
- For areas severely affected by fungus application of Dulux Aquatech Pre-Treatment coat is recommended.
- In case of areas having dampness use Dulux Aquatech Interior Waterproof Basecoat on the bare surface as per recommendation.
- Fill up all minor cracks and defects with Dulux Aquatech Range of crack fillers as per requirement / cement and sand mixture in the ratio 1:3.
- Dulux Promise Interior Sheen should not be applied to the surfaces or substrates which are exposed to continuous seepage or dampness.



Priming coat Application :

- Prime surface with a coat of Dulux Water Based Cement Primer or Dulux Acrylic Primer and dry for 4-6 hrs.



Putty Application:

- Smoothen the surface by filling dents with thin coats of any suitable putty. Allow drying for 6-8 hours. Sand with Emery paper 180 and wipe clean



Priming coat Application :

- Prime surface with a coat of Dulux Water Based Cement Primer or Dulux Acrylic Primer and dry for 4-6 hrs.



Finishing :

- Dilute 1 lit of paint with 400-450 ml of water,give 3-4 hours interval between the coats. Normally two coats of paints are sufficient for opacity and desired finish. However extra may be required in case of change in Colour of the pre painted substrate.
- Do not over dilute and shake the paint well before use.



Drying Time: (Single coat at standard thickness) :

- Touch Dry: Upto 30 Mins.
- Recoat: 3-4 hours.
- Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and humid conditions.



Post Application Instructions
For best performance of paint ensure proper washing and cleaning of all algal and fungal growth at regular interval of six months.