



# ACRYLIC WALL PUTTY

Dulux Acrylic Wall putty is formulated for filling cracks, joints, leveling uneven and rough masonry and plasterwork upto 3-4mm. It is also used for filling defective cement surfaces to give a smooth and excellent finish.

## FEATURES AND BENEFITS



Suitable for interiors • Easy to spread • Superior Whiteness • Excellent Filling Properties

## PRODUCT RELATED DATA

COMPOSITION	COLOUR RANGE	GLOSS/SHEEN LEVEL
<b>PIGMENT</b> Non-Lead Chrome Pigments <b>BINDER</b> Acrylic Copolymer Emulsion <b>SOLVENT</b> Water	White	N/A Used as an Undercoat
<b>COVERAGE</b> 20 sq.ft./kg @ 200 micron thickness  <small>Please Note: Values may vary from surface to surface and also based on method of application</small>	<b>PACK SIZES</b> 5 Kg 20 Kg	<b>FLASH POINT</b> (IS 101/1987, Part 1, Sec 6) Non-Flash

## APPLICATION RELATED DATA

DILUTION	APPLICATION TOOL
 No Dilution Required	 Trowel / Putty Knife / Leveler
<b>DRYING TIME</b>  Touch Dry : 30 min. Recoat : 4 hrs. <small>Drying time may vary according to the temperature, humidity and thickness.</small>	

## APPLICATION RELATED INFORMATION

Before application, read the safety, health and environmental information and the precautions given below.

### SURFACE PREPARATION

• New concrete/plaster surface should be allowed to mature properly. • Ensure that the surface is clean, dry, free from all loose particles, dust, dirt, greases, wax etc. before application. • All surfaces should be thoroughly rubbed down using a suitable abrasive paper and thereafter, wiped off. • Suitable remedial measures should be taken in case of water seepage/leakage problems. • Fungus affected areas need separate treatment.

### PRIMING

Prime surface with a coat of Dulux Solvent Bases Cement primer or Dulux Water Based Cement Primer and dry overnight.

### APPLICATION

Smoothen the surface by using Dulux Acrylic Wall Putty to fill cracks and dents. Allow drying for 4-6 hours. Sand the surface with Emery paper no. 180. Wipe off loose particles. Apply another coat of primer and allow drying for 4-6 hours. Sand the surface Emery Paper no. 380 and wipe clean. Primer-Putty-Primer is a must to get the desired effect of the topcoat.

### CLEANING UP

Clean all equipment with clean water immediately after use.

**STIR THOROUGHLY BEFORE USE.**

## HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

• No added Lead, Mercury & chromium compounds • Lead content in dried paint film does not exceed 90 parts per million • Treatments such as sanding, burning off etc of paint films may generate hazardous dust and other fumes. • Wet sanding/flaming should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment • Do not breathe gas/fumes/vapour/ spray • Remove as much paint as possible from brushes and rollers before cleaning • Avoid release to the environment • Collect spillage • Keep away from food drinks and animal feed • Store in a cool and shaded place • Container must be in a secure, upright position and be tightly closed • Do not use container for storing food. • In case of contact with eyes, rinse immediately with plenty of water and seek medical advice • In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners • Do not empty into drains or water course • Safety data sheet available for professional/user on request • Use only in well ventilated areas.

## WARNING

### HAZARD STATEMENT

• May cause an allergic skin irritation.

### PRECAUTIONARY STATEMENT

• Keep out of reach of children • If medical advice is needed, have product container or label at hand • Wear eye or face protection • Wash hands thoroughly after handling • IF IN EYES: Immediately call a POISON CENTER or doctor • Call a POISON CENTER or physician if you feel unwell • Dispose of contents and containers in accordance with all local, regional, national and international regulations

**Note: The information provided above may change without prior notice.**

**In case of any complaints please contact Customer care cell, Ph: 1800 3000 4455**

Registered Office:

Akzo Nobel India Limited, Geetanjali Apartment,  
1st Floor, 8B Middleton Street, Kolkata 700 071

Corporate Office:

Akzo Nobel India Ltd, 9th floor, Magnum  
Towers, Golf Course Ext Rd, Sector 58,  
Gurugram -122011, Haryana