



PROMISE

EXTERIOR PRIMER

Dulux Promise Exterior Primer is a good quality, water based primer for external surfaces. Its unique Anti-Peel formulation ensures superior adhesion for the paint film, thereby resisting peeling or flaking of the topcoat.

FEATURES AND BENEFITS



PRODUCT RELATED DATA

COMPOSITION

- Pigment : Light Fast Non-Lead/Chrome pigment
- Binder : Acrylic copolymer Emulsion

COLOUR RANGE

White

GLOSS/SHEEN LEVEL

Matt Finish

COVERAGE

100-130
sq.ft./lit./coat

Please Note: Values may vary from surface to surface and also based on method of application

PACK SIZES

FLASH POINT
(IS 101/1987, Part 1, Sec 6)

Non-Flash

APPLICATION RELATED DATA

DILUTION

50%
with Clean Water

For best performance it is recommended to apply 1 coat of Dulux Promise Exterior Primer after thinning with water in the ratio of 1:1 by volume

APPLICATION TOOL

Roller, Brush

STABILITY OF THINNED PAINT

Can be used within 24 hours of thinning after mixing.

DRYING TIME

4-6 hrs.

Dulux Promise Exterior Primer is normally surface dried in 20-30 minutes and recoatable after 4-6 hours.

APPLICATION RELATED INFORMATION

Before application, read the safety, health and environmental information and the precautions given below.

SURFACE PREPARATION

Ensure surface is thoroughly clean, dry and free from all loose dirt, chalk, grease, fungi, algae and flaking paint. This can be achieved by brushing with a wire/stiff coir brush, followed by water jetting if required. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. For areas that are severely affected by algae or fungus, application of Pre-Treatment coat is recommended. Avoid application of putty or filling compound while painting an exterior surface.

PRIMING

On horizontal surfaces, self-priming of the topcoat material is suggested with additional coats of the same. For surfaces that remain powdery, friable or chalky even after thorough preparation, application of top coat material as primer with 1:1 dilution in water is recommended.

TOPCOAT APPLICATION

Any topcoat can be applied as per the recommended application procedure with a brush or roller. The topcoat should be applied after hard drying of Dulux Polyputty. Topcoat coverage should be maintained as per the particular product data sheet to obtain the desired features.

CLEANING UP

Clean all equipment with clean water immediately after use.

STIR THOROUGHLY BEFORE USE.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

• No added Lead, Mercury & chromium compounds. • Lead content in dried paint film does not exceed 90 parts per million. • Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and other fumes. Wet sanding/flaming should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment. • Wear eye/hand protection. • Do not breathe vapour/spray. • Remove as much paint as possible from brushes and rollers before cleaning. • Avoid release to the environment. • Collect spillage. • Keep away from food drinks and animal feed. • Store in a cool and shaded place. • Container must be in a secure, upright position and be tightly closed. • In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. • In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. • Do not empty into drains or water course. • Safety data sheet available for professional/user on request. • Do not use empty container for storing food. • Use only in well ventilated areas. • Lift with care - gross weight may exceed 10 kg.



WARNING

HAZARD STATEMENT

• May cause an allergic skin reaction.



PRECAUTIONARY STATEMENT

• Keep out of reach of children • If medical advice is needed, have product container or label at hand • Wear eye or face protection • Wash hands thoroughly after handling • IF IN EYES: Immediately call a POISON CENTER or doctor • Call a POISON CENTER or physician if you feel unwell • Dispose of contents and containers in accordance with all local, regional, national and international regulations

Note: The information provided above may change without prior notice.

In case of any complaints please contact Customer care cell, Ph: 1800 3000 4455

Registered Office:

Akzo Nobel India Limited, Geetanjali Apartment,
1st Floor, 8B Middleton Street, Kolkata 700 071

Corporate Office:

Akzo Nobel India Ltd, 9th floor, Magnum
Towers, Golf Course Ext Rd, Sector 58,
Gurugram -122011, Haryana