



PROMISE

All new promise Range

WE'LL KEEP YOUR HOME SMILING FOR YEARS. PROMISE.

THE DULUX PROMISE PAINT WITH ANTI CHALK TECHNOLOGY



AkzoNobel

PRODUCT DESCRIPTION:

Dulux Promise Interior is water based acrylic emulsion paint for decoration for your walls and ceilings and other surfaces like particle board fiber insulation board etc.

Dulux Promise Interior has a wide range of richer & brighter colours that makes your walls beautiful.

PRODUCT FEATURES AND BENEFITS:



- Beautiful finish
- Richer and brighter colours
- Better Scrub resistance



- Low VOC

PRODUCT RELATED INFORMATION:

Film Composition:

Pigment : Light fast non – Lead /Chrome pigment

Binder : Acrylic copolymer Emulsion

Solvent : Water

Colour Range:

As per shade card & colour solution fan deck, more than 3000 shades are available

Gloss/Sheen Level:

Matt Paint

Dry Film Thickness (Calculated):

Dry film thickness 30-35 micron at 100-120 Sq. ft. /liter for two coats

Pack Size:

Available in 1, 4, 10 and 20 liters.

APPLICATION RELATED INFORMATION:

Before application read the safety, health and environmental information and the precautions given below



Application Tool:

Suitable for application by brush and roller



Surface Preparation:

- New concrete / Plaster surface should be allowed to mature properly.
- Ensure that the surface is clean, dry, free from all loose particles, dust, dirt, grease, wax etc. before application
- All surfaces should be thoroughly rubbed down using a suitable abrasive paper and thereafter wiped off.
- Suitable remedial measures should be taken in case of water seepage/leakage problems.
- Fungus affected areas need separated treatment.
- For previously painted surface strip all the paint before starting the above process.



Priming:

- Prime surface with a coat of Duwel water based cement primer or Duwel Acrylic primer and allow drying for 6 – 8 hours.
- Rectify and smoothen the surface with Duwel Acrylic Putty and allow drying for 4-6 hours. A second coat of putty may be applied if necessary and allow to dry further for 4-6 hours.
- Sand the surface with Emery paper 180. Wipe off loose particles. Apply another coat of primer on the puttied surface and allow drying for 6 – 8 hours. Sand the surface with emery paper 320 and wipe clean.
- Primer putty primer is a must to get desired effect of the top coat.

Finishing Time:

- Stir thoroughly before use.
- Apply 2 coats of Dulux Promise Interior, thinned with 500 – 600 ml of water for 1 liter of paint (Recommended for dark colours 300 – 400 ml of water for 1 liter). Give 3-4 hours interval between the coats. Normally two coats of paints are sufficient for opacity and desired finish. However extra may be required in case of change in colour.
- Do not over Dilute.

Drying Time:

- Touch Dry : 30 Min
- Recoat : 3 -4 hours

Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and damp condition.

POST APPLICATION INSTRUCTIONS:

For best of the paints, ensure proper washing and cleaning for fungal growth at regular intervals of six months.

HEALTH, SAFETY AND ENVIRONMENTAL SECUTIRY:

- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Store in cool, dry, well-ventilated place away from sources of heat, ignition, and direct sunlight. Keep the container tightly closed. Keep out of the reach of children and away from food, drinks and animal feed.
- If swallowed seek medical advice immediately and show this container or label.
- Avoid contact with Skin or Eyes. Wear suitable gloves.
- After contact with skin, wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Use only in well ventilated areas. Do not breathe gas/fumes/vapour/spray.
- Remove as much paint as possible from brushes and rollers before cleaning.
- May cause an allergic skin reaction. May cause sensitisation by skin contact.
- Contain spillages using earth or sand.
- Do not empty into drains. Dispose of contents and container in accordance with all local, regional, national or international regulations.
- Avoid release to the environment. Refer to special instructions/Safety data sheet.
- No added Lead, Mercury or Chromium compounds.

PRECAUTIONS:

- Avoid application during extreme temperature.
- Do not apply on damage surface.
- Do not over thin.
- Use only Akzo Nobel colorant for tinting.
- Stir well before use.
- Tinted paints need thoroughly shaking immediately after tinter addition as well as before use.
- Wear eye protection when applying.
- Avoid inhalation of dust by wearing a suitable nose pad during sanding.
- In case of eye contact, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, remove splashes from skin with soap and water or a recognized skin cleaner.
- In case of ingestion seek medical attention.

CONTACT US:

Registered office

Akzo Nobel India Limited
Geetanjali Apartment, 1st floor, 8B Middleton Street,
Kolkata 700 071

In case of any complaints please contact Customer care cell

Akzo Nobel India Ltd., Infinity Tower A, 7th Floor, DLF Cyber
City, Phase 11, Gurgaon-122002, Haryana, India, Ph:
0124-3266087

Note: The information provided above may change without prior notice.

