



Super Satin

Soft Sheen Enamel

Dulux Super Satin is a premium soft sheen enamel paint for interior and exterior wooden, metal and masonry surfaces. Dulux Super Satin gives a luxurious satin like smooth finish and comes in a range of rich & clean colours. Its Duratough technology imparts toughness and durability to the paint film. It also gives long lasting sheen and resists fungal attack, keeping the paint looking as good as new for a long time.

Product Features & Benefits

Dulux Super Satin is a premium quality solvent based enamel paint which gives a high quality satin like smooth finish and long lasting sheen to wooden, metal and masonry surfaces. It is specially formulated to provide:

-  Super Tough Film
-  Super Rich & Clean Colors
-  Fungal Resistant

- High Coverage
- Washable
- Available in 4400 Shades



Product Related Information

| | FILM COMPOSITION |
|---------|---|
| PIGMENT | Light fast Non-Lead Pigment |
| BINDER | Modified Alkyd |
| SOLVENT | Mainly White Spirit with other non-toxic solvents |
| COLOUR | See appropriate Shade Card/Fan deck |

Flash Point (IS 101/1987, Part 1, Sec 6) : 36 °C

STABILITY OF THINNED PAINT:

24 Use within 24 hours of thinning after mixing


COVERAGE

Under normal conditions it is 110-120 sq.ft/ltr for 2 coats. However this can show wide variation depending on actual type/ Condition of substrate.






Volume Solids : 55-60% (nominal)

VOC LEVEL

 **VOC (Theoretical) ASTM D-3960**
Varies from 350-400 gm/ltr. depending on the shades


GLOSS/SHEEN LEVEL

LOW 
MID 
HIGH 


FILM THICKNESS

Dry Film Thickness
25-30 microns

Wet Film Thickness
50-60 microns

WOOD / METAL 

PACK SIZE



APPLICATION RELATED INFORMATION

Before application, read the safety, health and environmental information and the precautions given below.

SURFACE PREPARATION

- Ensure surface is dry & free from grime, dust and grease.
- Remove loose or flaking particles.
- Sand the surface by using Emery paper No. 180 & wipe clean.
- For pre-painted surface, where putty application is not expected use Emery paper No. 320 & wipe clean.

THINNING



Brush or Roller: Brush or Roller: For best result, add up to 1 parts Duwel Thinner (61-33) or White Spirit/ Mineral Turpentine Oil (MTO) to 10 parts of paint by volume.



Conventional Spray: Add upto 2.5 parts Duwel Thinner (61-33) or White Spirit/ MTO to 10 parts of paint (25%) by volume depending on specification of the gun.

SYSTEM INFORMATION

| | |
|--------------------|---|
| Metal Surface | Primer - 1 coat Duwel Red Oxide Metal Primer (34-0100) Finish - 2 coats Dulux Super Satin (28- Line) |
| Wood Surface | Primer - 1 coat Duwel Wood Primer White (34-0300)/ Duwel Wood Primer Pink (32-0129) Finish - 2 coats Dulux Super Satin (28- Line) |
| Masonry Surface | Primer - 1 coat Duwel Cement Primer (34-1200) Finish - 2 coats Dulux Super Satin (28- Line) |
| Re-Painted Surface | Primer - 1 coat Not Required Finish - 2 coats Dulux Super Satin (28- Line) |

PRECAUTIONARY STATEMENTS

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Wear protective gloves. Wear eye or face protection.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF IN EYES: Immediately call a POISON CENTER or doctor.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Keep cool
- Dispose of contents and container in accordance with all local, regional, national or international regulations.

For further details, carefully read the information on containers as well.

CONTACT US:

Registered Office:

Akzo Nobel India Limited

Geetanjali Apartment, 1st Floor, 8B Middleton Street, Kolkata 700 071

In case of any complaints please contact Customer care cell,

Ph : 1800 3000 4455, or write to Customer Care Manager,

Email : customercare.india@akzonobel.com

Akzo Nobel India Limited, Building No. 5, Tower A , 20th Floor

DLF Cyber City, Phase III, Gurgaon, India, Ph: 0124 - 4528400

Note: The information provided above may change without prior notice.

APPLICATION TOOLS

Suitable for application by brush, roller & Spray



DRYING TIME



Single coat at standard thickness

TOUCH DRY: Upto 60 Mins.

TACK FREE: Within 2-4 hours

CLEANING UP

Clean all equipment with Duwel Thinner (61-33) or White Spirit / Mineral Turpentine Oil immediately after use.

HEALTH SAFETY AND ENVIRONMENTAL INFORMATION

DANGER

- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Keep away from sources of ignition – no smoking
- Do not breathe gas / fumes /vapour / spray
- Use only in well ventilated areas
- Keep out of the reach of children
- If swallowed seek medical advice immediately and show this container or label
- Do not empty into drains
- Avoid contact with skin or eyes. After contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- Remove as much paint as possible from brushes and rollers before cleaning
- Safety data sheet available for professional users on request
- No added Lead, Mercury & chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million
- Lift with care – gross weight may exceed 10 kg.

DANGER

- Flammable liquid and vapour
- Harmful if swallowed
- Causes serious eye damage
- Causes skin irritation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled
- May cause an allergic skin reaction
- Toxic to aquatic life with long lasting effects.



Let's create together a brighter future for our planet.

Find out how at www.dulux.in