



SUPERGLOSS
HIGH PERFORMANCE ENAMEL PAINT
5in1

Dulux Supergloss 5in1 is a super-premium enamel paint that delivers high end performance in a mirror-like finish with a rich, deep and long lasting shine for wood and metal surfaces. Because of its unique resin system, its white and color finishes are beautifully bright and clean, and stay as good as new for a longer time without yellowing or losing shine. Dulux Supergloss 5in1 also has special link-bond technology makes the paint film more crack-resistant than ordinary enamel paints.

Product Features & Benefits

Dulux Supergloss 5in1 is formulated to give five unique benefits.

- Super Glossy Finish
- Super Anti yellowing
- Super Clean Colours
- Super Long Life
- Super Coverage



Mirror Finish



Long Lasting White



Available in more than 1650 shades



Product Related Information

FILM COMPOSITION	
PIGMENT	Light Fast Non-Lead Pigment
BINDER	Modified Alkyd
SOLVENT	Mainly white Spirit with other non-toxic solvents
COLOUR	Available in more than 1650 shades

VOC LEVEL	
	VOC (Theoretical) ASTM D-3960 Varies from 350-450 gm/ltr. depending on the shades

Flash Point (IS 101/1987, Part 1, Sec 6) : 36 °C

STABILITY OF THINNED PAINT:
 Use within 24 hours of thinning after mixing

COVERAGE
 Under normal conditions it is 125-130 sq.ft/ltr for 2 coats. However this can show wide variation depending on actual type/ Condition of substrate.



Volume Solids : 50-60% (nominal)

GLOSS/SHEEN LEVEL	
LOW	
MID	
HIGH	

FILM THICKNESS	
Dry Film Thickness	30-40 microns
Wet Film Thickness	50-60 microns
WOOD /METAL	

PACK SIZE	
	500ml
	1 litre
	4 litres
	10 litres
	20 litres

APPLICATION RELATED INFORMATION

Before application, read the safety, health and environmental information and the precautions given below.

SURFACE PREPARATION

For Smooth surface: Ensure Surface is dry & free from grime, dust & grease. Remove loose or flaking particles. Sand the surface by using Emery paper No. 180 & wipe clean. For pre-painted surface, where putty application is not expected, use Emery paper No. 320 & wipe clean.

For minor cracks and uneven surface: Rectify and smoothen the surface by applying solvent-based putty after sanding the first coat of primer. Repeat putty application if required. Do light sanding for final surface smoothening.

THINNING



Brush or Roller: For best result, add up to 2.5 parts Duwel Thinner (61-33) or White Spirit/ Mineral Turpentine Oil (MTO) to 10 parts of paint by volume.



Conventional Spray: Add up to 3.0-3.5 parts Duwel Thinner (61-33) or White Spirit/ MTO to 10 parts of paint (30-35%) by volume depending on specification of the gun.

SYSTEM INFORMATION

Metal Surface	Primer - 1 coat Duwel Red Oxide Metal Primer (34-0100) Finish - 2 coats Dulux Supergloss 5in1 Finish (56- Line)
Wood Surface	Primer - 1 coat Duwel Wood Primer White (34-0300)/ Duwel Wood Primer Pink (32-0129) Finish - 2 coats Dulux Supergloss 5in1 Finish (56- Line)
Masonry Surface	Primer - 1 coat Duwel Cement Primer (34-1200) Finish - 2 coats Dulux Supergloss 5in1 Finish (56- Line)
Re-Painted Surface	Primer - 1 coat Not Required Finish - 2 coats Dulux Supergloss 5in1 Finish (56- Line)

PRECAUTIONARY STATEMENTS

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Wear protective gloves. Wear eye or face protection.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF IN EYES: Immediately call a POISON CENTER or doctor.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Keep cool
- Dispose of contents and container in accordance with all local, regional, national or international regulations.

For further details, carefully read the information on containers as well.

CONTACT US:

Registered Office:

Akzo Nobel India Limited

Geetanjali Apartment, 1st Floor, 8B Middleton Street, Kolkata 700 071

In case of any complaints please contact Customer care cell,

Ph : 1800 3000 4455, or write to Customer Care Manager,

Email : customercare.india@akzonobel.com

Akzo Nobel India Limited, Building No. 5, Tower A , 20th Floor

DLF Cyber City, Phase III, Gurgaon, India, Ph: 0124 - 4528400

Note: The information provided above may change without prior notice.

APPLICATION TOOLS

Suitable for application by brush, roller & Spray



DRYING TIME



Single coat at standard thickness
TOUCH DRY: Upto 60 Mins.
TACK FREE: Within 4-6 hours

CLEANING UP

Clean all equipment with Duwel Thinner (61-33) or White Spirit / Mineral Turpentine Oil immediately after use.

HEALTH SAFETY AND ENVIRONMENTAL INFORMATION

DANGER

- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Keep away from sources of ignition – no smoking
- Do not breathe gas / fumes /vapour / spray
- Use only in well ventilated areas
- Keep out of the reach of children
- If swallowed seek medical advice immediately and show this container or label
- Do not empty into drains
- Avoid contact with skin or eyes. After contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- Remove as much paint as possible from brushes and rollers before cleaning
- Safety data sheet available for professional users on request
- No added Lead, Mercury & chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million
- Lift with care – gross weight may exceed 10 kg.

DANGER

- Flammable liquid and vapour
- Harmful if swallowed
- Causes serious eye damage
- Causes skin irritation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled
- May cause an allergic skin reaction
- Toxic to aquatic life with long lasting effects.



Let's create together a brighter future for our planet.

Find out how at www.dulux.in