

## HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION:

- No added Lead, Mercury & chromium compounds
- Lead content in dried paint film does not exceed 90 parts per million
- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and other fumes. Wet sanding/flaming should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment
- Do not get in eyes, on skin or on clothing
- Call a POISON CENTER or physician if you feel unwell
- Do not breathe vapour/spray
- Remove as much paint as possible from brushes and rollers before cleaning
- Keep away from food drinks and animal feed
- Store in a cool and shaded place
- Container must be in a secure, upright position and be tightly closed
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.
- Do not empty into drains or water course
- Safety data sheet available for professional/user on request
- Do not use empty container for storing food
- Use only in well ventilated areas

### Warning

#### HAZARD STATEMENTS:



- May cause an allergic skin reaction.
- Very toxic to a aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS:

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Wear protective gloves
- Avoid release to the environment
- Avoid breathing vapour
- Collect spillage
- Take off contaminated clothing and wash it before resuse
- IF ON SKIN: Wash with plenty of water
- If skin irritation or rash occurs : Get medical advice or attention
- Dispose of contents and containers in accordance with all local, regional, national and international regulations.

#### CONTACT US:

Registered office,  
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071  
In case of any complaints please contact Customer care cell,  
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,  
Haryana, India

Note: The information provided above may change without prior notice.



# VelvetTouch PLATINUM GLO



## FEELS LIKE HOME



PRODUCT DATA SHEET

**AkzoNobel**

PRODUCT DESCRIPTION :

**Dulux Velvet Touch Platinum Glo** a super-premium interior emulsion which gives rich matt finish on the walls. It is exquisite, exclusive and the ultimate expression of class. It brings out the subtle glow of platinum onto your walls coupled with platinum like resistance that protects your wall from fungus, bacteria and molds.



PRODUCT FEATURES AND BENEFITS :



**Give your interior walls the ultra luxurious look with Velvet Touch Platinum Glo.**  
Made with finest ingredients and colour pigments, Velvet Touch Platinum Glo delivers intense rich colours with an ultra smooth finish.



**Rich Matt Finish**  
Provides platinum like subtle sheen that lends it a rich and classy look.



**Dirt and Dust Resistance**  
Special dirt and dust resistance formulation that allows easy wash-ability against all common stains.



**Superior Opacity and Scrub**  
Provides superior opacity and excellent scrub resistance.



**Anti-Bacterial & Anti-Fungal**  
Protects from bacteria, fungus and molds

PRODUCT RELATED INFORMATION :

Film Composition:

Pigment	: Non-lead pigment
Binder	: Acrylic copolymer emulsion
Solvent	: Water
Bases	: Br.White + 3 Bases (White Base (90), Intermediate (92), Accent (94))
Gloss/Sheen level	: Matt Finish
Flash Point (IS101/1987, Part1, sec 6)	: Non-Flash
Stability of Thinned Paint	: Should be used within 24 hours of thinning after mixing
Dry Film Thickness (Calculated)	: 20-25microns at coverage of 130-150 sq. ft./litre
Coverage	: The Spreading capacity/coverage of this product will vary considerably according to the surface preparation, roughness and porosity of the surface and change in color on the wall <ul style="list-style-type: none"><li>• On smooth surface of low porosity: Range 130-150 sqft/litre/2 coats</li><li>• On high porous absorbent surface: Range 110-130 sqft/litre/2 coats</li></ul>
Pack Size Available	: 1,4, 10 & 20 liters

APPLICATION RELATED INFORMATION:



PREPARE

Application Tool:

Suitable for application by brush or Roller.



Surface Preparation:

- Ensure that the surface is clean, dry and free from all lose particles, paint film, dirt, dust, mould, fungal growth etc. before application. Surface should be thoroughly rubbed down using suitable abrasive paper and thereafter wiped off. For new concrete or plaster surface should be allowed to mature properly. Use suitable Dulux Aquatech range of products to fix the dampness issue in wall. Proper surface preparation is must to get the desired effect and finish.



PAINT



Priming:

- Prime surface with a coat of Water Based Cement Primer or Solvent Based Cement Primer. Allow drying 4-6 hrs.



Putty:

- Smoothen the surface by filling dents with thin coat of Dulux Acrylic Wall Putty. Allow drying for 3-4 hrs. Sand with emery paper 180 and wipe clean.



Priming:

- Apply another coat of primer & allow drying for 4 hrs. Primer-Putty-Primer is must to get the desired effect to topcoat.



Dilution:

- Use 35-40% of clean water for Br. White and pastel shades. For dark shades use 30% of clean water. Do not over dilute and shake the paint well before use.



Finishing:

- Stir thoroughly before use. Apply 2-3 coats of Dulux Velvet Touch Platinum Glo with minimum 4 hrs gap between the coats. Normally two coats of paint are sufficient for opacity and the desired finish. However, an extra coat may be required for change of colour and deep base shades.



CLEAN

Cleaning:

Clean all equipment with clean water immediately after use. Refer to Dulux Product Data Sheet for further details.

Drying Time:

- Touch Dry : Upto 1 hour.
- Recoat : 5-6 hours (Single coat at standard thickness)

POST APPLICATION INSTRUCTIONS

For best performance of the paint, ensure proper washing and cleaning of regular intervals of six months