

# FIX & GROUTS

Dulux Simply Refresh Fix & Grouts is a ready to use repair agent specially designed to fix gaps on joints between tiles. It has excellent adhesion to different substrates & can be used on a wide variety of tiles. It is extremely resistant to water & fungal attacks.





HAND APPLIED

REPAIR AGENT



ANTI-FUNGAL



**Application Tool** Suitable for application by hand or spatula

Pack Sizes 300 gms





## **Surface Preparation**

• Ensure that the surface to be applied is clean & dry. Any fungal growth should be removed thoroughly.

# **Ready to Use**

Product is supplied in ready to use condition



## Application

- Massage the tube gently before use.
- Remove the cap & cut the nozzle. Gently squeeze the tube into the joints and smooth with a spatula or putty knife or moistened fingers.
- Wait for 30 minutes to remove excess material with a moist cloth.

#### **Finishing**

Allow the material to dry completely for 24 hours before exposing to damp or wet conditions. Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and damp conditions.

Drying Time*	Stability of paste	VOC Level
Hard Dry : 24 hours	Use within 24 hrs. of taking out from the tube	< 50 gm/lit
Coverage	Flash Point	Shelf Life



- No added Lead, Mercury & chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million.
- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and other fumes. Wet sanding/flaming should be used wherever possible.
- Work in well ventilated areas. Use suitable personal protection equipment.
- Wear eye/hand protection.
- Do not breathe vapour/spray.
- Remove as much paint as possible from brushes and rollers before cleaning.
- Do not get in eyes, on skin or on clothing.
- Do not empty into drains or water course.
- Call a POISON CENTER or physician if you feel unwell.
- Keep away from food drinks and animal feed.

#### WARNING

HAZARD STATEMENTS



• Very toxic to a aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not apply on wet substrates.
- Do not use to fix joints/gaps above 5 mm.
- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Avoid release to the environment.
- Avoid breathing vapour.
- Collect spillage.
- Get medical advice/attention if you feel unwell.
- Dispose of contents and containers in accordance with all local, regional, national and international regulations.