

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION:

- **No added Lead. Mercury or Chromium compounds.**
- **Lead content in dried paint film does not exceed 90 parts per million.**
- Treatments such as sanding, burning off etc. of paints films may generate hazardous dust and/or fumes. Wet sanding/flaming should be used whenever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Wear eye/hand protection.
- Do not breathe vapour/spray.
- Remove as much paint is possible from brushes and rollers before cleaning.
- Avoid release to the environment.
- Keep away from food, drinks and animal feed.
- Store in a cool and shaded place.
- Container must be in a secure, upright and tightly closed. Do not use empty container for storing food.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent or thinners.
- Do not empty into the drains or water course.
- Safety data sheet available for professional/user on request.
- Use only in well ventilated areas.

PRECAUTIONS:

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin or on clothing.
- Call a POISON CENTER or Doctor/Physician if you feel unwell.
- Dispose of contents and containers in accordance with all local, regional, national and international regulations.
- Avoid extreme temperature.
- Do not apply on damp surface.
- Do not over thin.
- Use only AkzoNobel colorants.
- Stir well before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.



CONTACT US:

Registered office,
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071
In case of any complaints please contact Customer care cell,
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,
Haryana, India

Note: The information provided above may change without prior notice.



NO BACTERIA, ONLY COLOURFUL WALLS.



Now with
Anti-Bacterial[^]
properties




[^] Anti-Bacterial property means that Dulux SuperCover is >99% effective in reducing microbial count against 4 types of household bacteria on the treated surface as tested using most acclaimed international test method (JIS Z 2801:2010 (E))

PRODUCT DESCRIPTION :


Dulux SuperCover is a smooth premium interior emulsion for walls & ceilings that enables you to bring home the **Colours of the World** from your favourite destinations. Its **ColourGuard technology** ensures that these colours are protected from daily wear & tear and last longer. Its **ProCoat Technology** gives unmatched opacity & good coverage. And now with added benefit of **Anti-Bacterial***, Dulux SuperCover helps to inhibit growth of bacteria on the painted surface.




PRODUCT FEATURES AND BENEFITS :




Anti-Bacterial*
Resistant to certain harmful bacteria
* Anti-Bacterial property means that Dulux SuperCover is >99% effective in reducing microbial count against below listed 4 types of household bacteria on the treated surface as tested using most acclaimed international test method (JIS Z 2801:2010 (E)). - • Escherichia coli • Staphylococcus aureus • Bacillus subtilis • Candida albicans




Colours of the World
Inspired by colours & moods of beautiful places around the world that bring special atmosphere from your dream destination to your home




ProCoat Technology
Unmatched Opacity and Coverage




Colourguard Technology
Long Lasting Colours



Fungal Guard
Fungus Guard technology helps to keep the walls free from Fugal growth & black patches



Super Smooth & Rich Matt Finish



Superior Hiding
Premium emulsion with superior opacity that leaves no trace of patchiness

PRODUCT RELATED INFORMATION :

Film Composition:	
Pigment	: Non-lead/Chromite pigment
Binder	: Acrylic co-polymer emulsion
Solvent	: Water
Colour	: As per AkzoNobel shade offering
VOC level in White & bases	: <50 gm/litre (Excluding tinter)
Gloss/Sheen Level	: Rich Matt
Flash Point (IS 101/1987, Part 1, Sec 6)	: Non-Flash
Stability of Thinned Paint	: Can be used within 24 hours of thinning after mixing
Dry Film Thickness (Theoretical)	: 30-40 microns at coverage of 120-140 sqft/litre.
Theoretical Coverage	: The Spreading capacity/coverage of this product will vary considerably according to the surface preparation, roughness and porosity of the surface and change in color on the wall <ul style="list-style-type: none">• On smooth surface of low porosity: Range 120-140 sqft/litre/2 coats• On high porous absorbent surface: Range 100-120 sqft/litre/2 coats
Pack Size Available	: 1, 4, 10 & 20 litres

APPLICATION RELATED INFORMATION:

Before application, read the safety, health and environmental information and the precautions given below.



Application Tool :
Suitable for application by brush and roller.



Surface Preparation :

- Ensure that the surface is clean, dry, free from all loose particles, paint film, dust, dirt, mould, fungal growth etc. before application.
- Surface should be thoroughly rubbed down using a suitable abrasive paper and thereafter wiped off.
- For New concrete / plaster, surface should allow to mature properly.
- For area severely affected by Fungus application of Dulux Aquatech Pre-treatment coat is recommended.
- Fill up all minor cracks and defects with Dulux Aquatech range of Crack fillers as per requirement / cement and sand mixture in the ration 1:3.
- In case of areas having dampness use Dulux Aquatech Interior Waterproof Basecoat on the bare surface as per recommendation.
- Proper surface preparation is must to get the desired effect and finish.
- Dulux SuperCover should not be applied to the surfaces or substrates which are exposed to continuous seepage or dampness.



Priming :

- Prime surface with a coat of Dulux Water Based Cement Primer or Dulux Interior Acrylic Primer and allow drying for 4-6 hours.
- Rectify and smoothen the surface with Dulux Acrylic Putty and allow drying for 4-6 hours. A second coat of Putty may be applied if necessary and allow to dry further 4-6 hours.
- Sand the surface with Emery Paper 180. Wipe off loose particles. Apply another coat of primer on the puttied surface and allow drying for 4-6 hours. Sand the surface with Emery Paper 320 and wipe clean.
- Primer Putty Primer is a must to get desired effect of the top coat.



Finishing :

- Stir thoroughly before use.
- Apply 2 coats of Dulux Super Cover thinned from 400- 600 ml of water for 1 liter of paint (recommended thinning for dark colours is 250 - 400 ml/liter) with 3-4 hours interval between the coats. Normally two coats of paint are sufficient for opacity and desired Finish. However, an extra coat may be required for change of colour & deep base shades.
- Do not over dilute.



Drying Time (Single coat at standard thickness) :

- Touch Dry : 30 Mins.
- Recoat : 4-6 hours.
- Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and damp conditions.