

SAFETY HEALTH AND ENVIRONMENTAL INFORMATION:

- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Do not breathe gas / fumes / vapour / spray
- Use only in well ventilated areas
- Keep out of the reach of children
- If swallowed seek medical advice immediately and show this container or label.
- Do not empty into drains.
- Avoid contact with skin or eyes. After contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove as much paint as possible from brushes and rollers before cleaning.
- Safety data sheet available for professional users on request
- No added Lead, Mercury & Chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million
- Lift with care – gross weight may exceed 10 kg.

PRECAUTIONS:

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin, or on clothing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Dispose of contents and container in accordance with all local, regional, national or international regulations.

CONTACT US:

Registered office,
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071
In case of any complaints please contact Customer care cell,
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,
Haryana, India

Note: The information provided above may change without prior notice.



Dulux **AMBIANCE**[™]
Velvet Touch
PERSONALISE YOUR WORLD

AkzoNobel

AMBIANCE[™]
Velvet Touch
ELASTOGLO

ELASTOGLO
3X ELASTICITY



PRODUCT DESCRIPTION:

Dulux Ambiance Velvet Touch Elastoglo is a super premium interior emulsion with advanced **Elastomeric Technology**, which stretches the paint film as much as **3X** more than other premium paints. This helps in covering hairline cracks and providing best-in-class finish.

PRODUCT FEATURES AND BENEFITS:



LONG LASTING ELASTOGLO FINISH



2000 SCRUB CYCLE RESISTANT



PROTECTION FROM FINGER MARKING



SUPERIOR OPACITY

PRODUCT RELATED INFORMATION:

Film Composition:

Pigment : Non-lead pigment
Binder : Acrylic copolymer emulsion
Solvent : Water

Colour Range : 7000 shades

Volatile Organic Compound (VOC) level as per EU directive: LOW VOC

Gloss/Sheen Level : Mid Sheen

Flash Point (IS 101/1987, Part 1, Sec 6): Non-Flash

Stability of Thinned Paint :

Use within 24 hours of thinning after mixing

Dry Film Thickness (Calculated) :

20-25 microns at coverage of 140-160 sq. ft./litre

Theoretical Coverage :

The spreading capacity/coverage of this product will vary considerably according to the surface preparation, roughness and porosity of the surface and change in color on the wall

- On smooth surface of low porosity: 140-160 sqft/litre/2 coats
- On high porous absorbent surface: 120-140 sqft/litre/2 coats

Pack Size : Available in 1 L, 4 L, 10 L and 20 L



APPLICATION RELATED INFORMATION:

Before application, read the safety, health and environmental information and the precautions given below.

Application Tool:

Suitable for application by brush or roller.

Surface Preparation:



- New concrete / plaster surface should allow to mature properly. Ensure that the surface is clean, dry, free from all loose particles, dust, dirt, grease, wax, mould, fungal growth etc before application. Surface should be thoroughly rubbed down using a suitable abrasive paper and thereafter wiped off.



- Suitable remedial measures should be taken in case of water seepage/leakage problems. Fungus affected areas need separate treatment. Proper surface preparation is must to get the desired effect and finish.

Priming:



- Prime surface with a coat of Duwel Water Based Cement Primer or Duwel Acrylic Primer and dry overnight.

Putty:



- Smoothen the surface by filling dents with thin coats of Duwel Acrylic Putty. Allow drying for 4-6 hours. Sand with emery paper 180 and wipe clean.

Priming:



- Prime surface with a coat of Duwel Water Based Cement Primer or Duwel Acrylic Primer and dry overnight.

Dilution:


- 300 ml of clean water for White and Pastel shades. For Dark shades 250 ml of clean water. Do not over dilute and shake the paint well before use.

Finishing:



- Stir thoroughly before use. Apply 2 coats of Dulux Ambiance VT Elastoglo Emulsion with minimum 4-6 hours between the coats. Normally two coats of paint are sufficient for opacity and the desired finish. However an extra coat may be required for change of colour.

Drying Time: (Single coat at standard thickness):



- Touch Dry: Upto 30 Mins.
- Recoat: 4-6 hours.

Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and damp conditions.

Top Coat:



- Apply 2-3 coats by diluting 1 lit of a Dulux Ambiance Velvet Touch Elastoglo as per recommended dilution with water. A gap of 4-6 hours should be given between two coats. For Horizontal surfaces, once additional coat should be applied for better protection.