



**Colourland<sup>®</sup>  
paints**


**COLOURLAND PAINTS SDN. BHD.** (Co.No.483545-K)

Lot 729, 15 ½ Miles, Jalan Sungai Tiram, P.O.Box 46,

81800 Ulu Tiram, Johor Bahru, Malaysia.

Tel : 607-861 1555 Fax : 607-861 1777 / 9089

## Wood



### COLOURLAND SOLAR SEAL Product Code: SS – 00

Colourland Solar Seal is a special modified alkyd based air drying formulation, exclusively formulated to protect outdoor exposed wooden surfaces against wood rot and mould growth by its penetrative properties, which ensure the introduction of preservatives into the wood cell. It is suitable for use on all types of new or previously treated exterior and interior hard and soft woods, will not peel, crack or blister on exposure to weather. Its extremely durable, hard and flexible finish with excellent abrasion resistance is highly recommended for use on cane or wooden furniture and fixtures, door panelings, partition and parquet flooring. Its water resistant and transparent finishes will enhance the natural beauty of wood.

|                  |  |
|------------------|--|
| <b>Usage</b>     | For decoration and protection of exterior exposed wooden and rattan surfaces; including parquet flooring, cane, wooden furniture, gymnasium and wood paneling. |
| <b>Pack Size</b> | 500 ml, 1 Lt and 5 Lt  |

| Composition              |   |
|--------------------------|---|
| <b>Pigment</b>           | Lightfast Non Lead Translucent Pigment. |
| <b>Binder</b>            | Modified Alkyd.                         |
| <b>Volume Solids</b>     | 36%                                     |
| <b>Thinner / Cleaner</b> | White Spirit.                           |

| Properties                  |  |
|-----------------------------|--|
| <b>Texture</b>              | Smooth Glossy Finish   |
| <b>Colour</b>               | A wide range of translucent pigmented colours. Please refer Colourland Solar Seal Colour Card. |
| <b>Theoretical Coverage</b> | 12 – 14 m <sup>2</sup> /Litre.   |
| <b>Drying Time</b>          | Touch Dry – 2 hours. Hard Dry – 6 hours.   |
| <b>Recoating Interval</b>   | 3 – 6 hours.   |

| Application Method            |  |
|-------------------------------|--|
| <b>Brush</b>                  | For normal use thinning is not usually necessary.                                    |
| <b>Roller</b>                 | For normal use thinning is not usually necessary.                                    |
| <b>Conventional Air Spray</b> | Thin with 10 – 20% by volume with Colourland Thinner 3040 and adjust to requirement. |

| Surface Preparation       |  |
|---------------------------|--|
| <b>General / New</b>      | Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish, rub down surface in the direction of the grain using suitable abrasive and dust off. If necessary, fill wood grain with Colourland Wood Filler and smoothen with abrasive. Allow paint to dry and lightly dry sand between the 1st and 2nd coat.                        |
| <b>Previously Painted</b> | Remove all loose, defective, unstable and existing paint film to barred wood. Rub down surface in direction of the grain. If necessary, fill wood grain with Colourland Wood Filler and smoothen with abrasive. Seal the timber with Colourland Solar Seal thinned down with 10 – 20% Colourland 3040 thinner. And paint 2 to 3 coat of Colourland Solar Seal, for best effect lightly dry sand between coats. |

| Painting Guide          |  |                            |
|-------------------------|--|----------------------------|
| Surface Condition       | Primer (To Paint 1 Coat)                                       | Finish (To Paint 1-3 Coat) |
| New Wood                | Colourland Solar Seal thin down with 10-20% Colourland Thinner | Colourland Solar Seal      |
| Previously Painted Wood | Colourland Solar Seal thin down with 10-20% Colourland Thinner | Colourland Solar Seal      |

For more information, please visit our website at : [www.colourland.com.my](http://www.colourland.com.my) . Any advice, recommendations, information, assistance or service provided by Colourland Paints Sdn Bhd in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service by Colourland Paints is provided without expressed or implied warranties.  
Product Technical Data • Rev 2 • Sep 2013