



Interior Wall

COLOURLAND EASY CARE ANTI-MOULD WALL FINISH

Product Code: EC – 5XXX



Colourland Easy Care Anti-mould is a modified acrylic emulsion paint, specially formulated for easy care of home owners with Smooth Elegant Classic Matt Finishes for an air of elegance for all wall finishes. It is a premium quality decorative paint with high durability, tough and scrubable, tested and proven with more than 10,000 scrubs with Sheen Wet Abrasion Scrub Tester. It is formulated with anti-mould and anti-fungus properties to inhibit the growth of mould and fungus, creating a healthier living environment. It is for all normal interior wall and ceiling surfaces. Ideal for areas like bathroom, living room, kitchen, bedroom, office partition and decorative glass fiber fabric wall covering. Washable and scrubable.

Usage	For decoration and protection of wall, ceiling, plaster, brickwork and cement board for a Smooth and Elegant Classic Matt finish.
Pack Size	1 Lt and 5 Lt

Composition	
Pigment	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	Acrylic Emulsion.
Volume Solids	White 33% (Nominal), other colours will vary.
Thinner / Cleaner	Water.

Properties	
Texture	Smooth Elegant Classic Matt Finish.
Colour	A wide range of colours. Please refer Colourland Easy Care Anti-mould Colour Card.
Theoretical Coverage	10 – 12 m ² /Litre.
Drying Time	Touch Dry 30 –60 min (Dependent on Temperature and Humidity).
Recoating Interval	1 – 2 hours.

Application Method	
Brush	For normal use thinning is not usually necessary.
Roller	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	Thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.

Surface Preparation	
General / New	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack. For best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).
Previously Painted	Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

Painting Guide

Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Easy Care Anti-mould
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Easy Care Anti-mould
Sound Surface	Colourland Wall Sealer	Colourland Easy Care Anti-mould
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Easy Care Anti-mould