

**Stone / Tiles / Pebble****COLOURLAND ACRYLIC TILE FINISH** Product Code: ACT - 1000

Colourland Acrylic Tile Finish / ACT-1000 is a 100% Acrylic air drying solvent based formulation. No additional of hardener is required. It dries rapidly to an extremely durable, tough and hard finish with excellent abrasion resistance and waterproof properties. Enhances the natural beauty of stone finishes and protect it from premature aging. Highly recommend for car porch and light traffic areas. Suitable for exterior and interior usage on metal, concrete or wood.

Usage	Enhances the natural beauty and protection of Concrete Imprint Flooring, Decorative Brick Works, Slate tiles, Pavers, Pebble Wash, Sand Stone Finish, Shanghai Plaster and Natural Stone Finish. It is also highly recommended for wet area for non slippery properties.
Pack Size	1 Lt and 5 Lt

Composition	
Pigment	None.
Binder	100% Pure Acrylic.
Volume Solids	50%
Thinner / Cleaner	Toluene / Xylene or Aromatic Hydrocarbon.

Properties	
Texture	Clear Glossy wet look that enhances the natural beauty of Stone Finish.
Theoretical Coverage	10 – 15 m ² /Litre.
Drying Time	Touch Dry - 20 mins. Light Traffic - 40 mins. Hard Dry – 2 hours.
Recoating Interval	30 mins

Application Method	
Brush	For normal use thinning is not usually necessary.
Roller	For normal use thinning is not usually necessary.
Conventional Air Spray	Thin 10% - 20% by volume with Colourland ACT 1000 Acrylic Thinner or Aromatic Hydrocarbon and adjust to requirement.

Surface Preparation	
General	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish for Pebble Wash, acid wash the surface to remove excess Ordinary Portland Cement residue and flush with fresh water, leave to dry and paint.

Painting Guide

Substrate	Primer (To Paint 1 Coat)	Finish (To Paint 1-3 Coat)
Concrete & Wood	Colourland ACT 1000 + 15% Thinner as a tie coat	Colourland ACT 1000 Finish