



## Floor Surface



### COLOURLAND AQUA FLOOR PAINT Product Code: PC – 7000

Colourland Aqua Floor Paint is a tough and flexible coating with fungus and algae resistant for the protection and decoration of all concrete surfaces, fair faced bricks, slate tiles, paver, cement cladding and roofing. Aqua Floor Paint is based on Vinyl Acetate – Acrylic Copolymer, which produce a tough, durable and flexible paint film able to withstand the effects of harsh environment with constant climatic and temperature variations.

<b>Usage</b>	For decoration and protection of all concrete surfaces, fair faced bricks, slate tile, cement board, paver and etc, where performance is demanded to be better than that provided by conventional emulsion paint.
<b>Pack Size</b>	5 Lt

Composition	
<b>Pigment</b>	Lightfast Non – Lead Pigments and Mineral Extenders.
<b>Binder</b>	Vinyl Acetate – Acrylic Copolymer
<b>Volume Solids</b>	White 38%
<b>Thinner / Cleaner</b>	Water.

Properties	
<b>Texture</b>	Smooth Sheen Finish.
<b>Colour</b>	Red, Blue, Green, Grey, and Clear. Please refer to Colourland Aqua Floor Paint Colour Card. (special colour under quantity and request).
<b>Theoretical Coverage</b>	10 – 12 m <sup>2</sup> /Litre.
<b>Drying Time</b>	Touch Dry 25 –40 min (Dependent on Temperature and Humidity). Hard Dry 1 hour.
<b>Recoating Interval</b>	1 – 2 hours.

Application Method	
<b>Brush</b>	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
<b>Roller</b>	Thin with 15 – 20% by volume with water dependent on surface porosity.
<b>Conventional Air Spray</b>	Thin with 20% by volume with water and adjust to requirement.
<b>Airless Spray</b>	Thin with 20% by volume with water and adjust to requirement.

Surface Preparation	
<b>General / New</b>	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack. For best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).
<b>Previously Painted</b>	Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. High Pressure Water Jet is highly recommended. Treat areas effected by mould, lichens, algae and moss with Colourland Fungi Wash. Make good minor defects and crack with suitable Exterior Grade Filler.

### Painting Guide

Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Aqua Floor Paint
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Aqua Floor Paint
Sound Surface	Colourland Wall Sealer	Colourland Aqua Floor Paint
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Aqua Floor Paint

**Note : If painting Colourland Aqua Floor Paint Clear Coat, no primer is required.**