



**Colourland[®]
paints**

COLOURLAND PAINTS SDN. BHD. (Co.No.483545-K)

Lot 729, 15 ½ Miles, Jalan Sungai Tiram, P.O.Box 46,
81800 Ulu Tiram, Johor Bahru, Malaysia.

Tel : 607-861 1555 Fax : 607-861 1777 / 9089



SIRIM ECO-LABEL
SIRIM CRITERIA 019 : 2012
LICENSE NO : ELC0295001

Interior Wall



COLOURLAND COLORLITE EMULSION PAINT

Product Code: CL – 6000

Colourland Colorlite Emulsion Paint is an economical decorative wall finish with algae and fungus resistance. It is suitable for all normal interior and exterior masonry surfaces and soft wall boards. Colourland Colorlite Emulsion Paint is based on Vinyl Acetate – Acrylic Copolymer which imparts washability and high degree of durability. Recommended for housing scheme and where economy is important. For longer durability of up to 5 years on exterior surfaces, Colourland WeatherFlex Plus Exterior Wall Finish is recommended.

Usage	For decoration and protection of wall, ceiling, plaster, brickwork, cement board, hard and soft board.
Pack Size	1 Lt, 7 Lt and 18 Lt

Composition	
Pigment	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	Vinyl Acetate – Acrylic Copolymer.
Volume Solids	White 43% (Nominal), other colour will vary
Thinner / Cleaner	Water.

Properties	
Texture	Smooth matt finish.
Colour	A wide range of colours. Please refer Colourland Colorlite Emulsion Paint Colour Card.
Theoretical Coverage	12 – 13 m ² /Litre.
Drying Time	Touch Dry, 15 – 30 min (Dependent on Temperature and Humidity). Hard Dry, 1 Hr.
Recoating Interval	1 – 2 hours.

Application Method	
Brush	Thin with 5 – 10% by volume with water dependent on surface porosity.
Roller	Thin with 5 – 10% by volume with water dependent on surface porosity..
Conventional Air Spray	Thin with 10 – 20% by volume with water dependent on surface porosity.
Airless Spray	Thin with 5 – 10% by volume with water dependent on surface porosity..

Surface Preparation	
General / New	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish, rub down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery or suffer from alkali attack, for best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).

Painting Guide		
Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Colorlite
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Colorlite
Sound Surface	Colourland Wall Sealer	Colourland Colorlite
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Colorlite

For more information, please visit our website at : www.colourland.com.my . Any advice, recommendations, information, assistance or service provided by Colourland Paints Sdn Bhd in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service by Colourland Paints is provided without expressed or implied warranties.
Product Technical Data • Rev 2 • Sep 2013