

DULUX PRE-PAINT BRUSH CLEANER/DEGREASER

TECHNICAL DATA SHEET

Version 3 – 2025 AUGUST

THIS ISSUE SUPERSEDES ALL PREVIOUS PUBLICATIONS

PRODUCT DESCRIPTION

Dulux Pre-Paint Brush Cleaner Degreaser is the easiest way to get brushes and rollers really clean with no mess or paint residue. Its powerful paint softening solvents removes all traces of paint without harming the bristles, better than turps or thinners.

PRODUCT USES

- It effectively cleans brushes and rollers used for applying solvent based paints and varnishes, but epoxy and other catalysed paints require a stronger solvent such as **Dulux Trade Heavy Duty Thinners**.
- *NOTE: Brushes and rollers which have been used for water-based paints are cleaned with tap water immediately after use.*
- Restores hardened brushes - **Dulux Pre-Paint Brush Cleaner/Degreaser** is very slow evaporating and can be left in open containers to soften and remove old paint (solvent based or water based) from brushes.
- **Dulux Pre-Paint Brush Cleaner/Degreaser** is also recommended as a general-purpose degreaser for removing oil, wax and grease from floors, driveway paving, wall areas (e.g. before repainting a stoep which has been wax-polished).
- As a degreaser, simply spray or brush onto garage floors etc., leave a while, and then flush off with water.

FEATURES AND BENEFITS

- Ready to use – only two steps – dip the paint brush or roller into **Dulux Pre-Paint Brush Cleaner/Degreaser**, then flush with water.
 - No mess – unique coupling action of **Dulux Pre-Paint Brush Cleaner/Degreaser** allows solvent-based paint to wash easily and cleanly under the tap – no dirty sinks or wash basins.
 - Saves money – very little waste – only small amounts needed to do a perfect cleaning job.
 - Saves time – fast acting – only one treatment required, while conventional thinners such as Turps require at least two treatments.
- Good for brushes – keeps bristles soft because they are thoroughly cleaned.

DULUX PRE-PAINT BRUSH CLEANER/DEGREASER

PRODUCT INFORMATION

Appearance	Clear Liquid
Binder Type	A blend of detergents, wetting agents and high boiling solvents
Density at 23°C	Approx. 0.90
Solids Content	By weight: Approx. 17% By volume: Approx. 15%
Water Miscibility	Yes
Flash Point	42°C

APPLICATION INFORMATION

Before you start

- Ensure workplace is well ventilated, use outdoors where possible.
- Protect furniture, floor coverings, painted surface and all plastic materials from splashes and spillages. Test on an insignificant area to avoid damage to sensitive finishes or substrates.
- Ensure accidental splashes are cleared up immediately.
- Ensure the product is cool before opening. Hold can away from face when removing the cap.

How to use as a Brush Cleaner

- Remove as much paint as possible from the brush or roller by mechanical or other means (scrape off, or use old newspaper, etc.).
- For brushes: Pour a small amount of **Dulux Pre-Paint Brush Cleaner/Degreaser** into a metal container. Work the bristles well into cleaner. Rinse under running water, working the bristles between fingers until clean.
- For rollers: First clean out the paint tray and then pour in a small amount of **Dulux Pre-Paint Brush Cleaner/Degreaser**. Work the roller into liquid, then squeeze out excess, and rinse under running water until clean.
- Hardened brushes or rollers should be soaked in **Dulux Pre-Paint Brush Cleaner/Degreaser** for 1 day or even longer. When softened, remove paint particles by wire brushing, and rinse under running water until clear.

How to use as a General-Purpose Degreaser

- Garage floors and Stoeps: Brush onto contaminated areas work the solution well on the substrate and allow to react for 15 minutes before hose down with running water while scrubbing with a hard bristle brush or broom. Severe or old contamination (e.g. old wax polish) may need scrubbing or prolonged soaking before flushing. Test on an insignificant area to avoid damage to sensitive finishes.
- Walls, Cupboards, Furniture and Windows: Moisten cloth with cleaner, wipe the surface thoroughly and then rinse off with water. Test on an insignificant area to avoid damage to sensitive finishes.

DULUX PRE-PAINT BRUSH CLEANER/DEGREASER

APPLICATION INFORMATION

How to use as a General-Purpose Degreaser - Continue

- Areas to be painted: Ensure that a water break-free surface is achieved after using **Dulux Pre-Paint Brush Cleaner/Degreaser**, rinse thoroughly until the water is clean and no longer milky.
- Carpets, Curtains and other Fabrics: Test an insignificant or hidden area first, especially for synthetic or coloured fabric, and latex-backed carpets. Wet the soiled area with **Dulux Pre-Paint Brush Cleaner/Degreaser** and then rinse with water until the **Dulux Pre-Paint Brush Cleaner/Degreaser** is thoroughly washed out.

HEALTH AND SAFETY INFORMATION

Danger: Flammable liquid and vapor. May be harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. May cause cancer. Toxic to aquatic life with long lasting effects.

Dulux products contain no added lead. Avoid contact with skin or eyes. Keep out of the reach of children. If accidentally swallowed, seek medical advice immediately and show this container to the doctor. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Do not empty into drains or water courses. Ensure good ventilation during application and drying. It is recommended to use suitable protective clothing and equipment.

To avoid the risk of spillage, always store and transport containers in a secure, upright position. Store under ambient conditions.

Safety and Technical Datasheets available on request or visit www.dulux.co.za

ADDITIONAL INFORMATION

Packaging	1L
Storage Conditions	Store under cool dry conditions away from direct sunlight, heat and extreme cold.
Disclaimers	N/A product specific

TDS STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Dulux control.

Important Note; Technology may change with time, necessitating changes to this Technical Data Sheet (TDS).

It is the responsibility of the user to ensure that the latest TDS is being used for reference. Dulux Technical Data Sheets are available on our website www.duluxtrade.co.za or please contact: Dulux On-Line on 0860 330 111. Email ZA.Helpline@akzonobel.com

ICI Dulux (Pty) Ltd is part of AkzoNobel. ICI Dulux (Pty) Ltd Reg No.1946/020769/07