

## DULUX PRE-PAINT QUICK SETTING CEMENT – INTERIOR/EXTERIOR

### TECHNICAL DATA SHEET

Version 4 – 2025 JUNE

THIS ISSUE SUPERSEDES ALL PREVIOUS PUBLICATIONS

### PRODUCT DESCRIPTION

Dulux Pre-Paint Quick Setting Cement is versatile interior or exterior filler that is the quick way to repair any masonry surfaces.

### PRODUCT USES

- **Dulux Pre-Paint Quick Setting Cement** is designed mainly for repairing any masonry surfaces. Due to its ability to resist water permeability, it is perfect for repairing areas constantly affected by water.
- Ideal for outdoor use i.e. masonry, concrete, brickwork, stone, cement rendering, paving and other exterior surfaces.

### FEATURES AND BENEFITS

- It provides a quick way to repair any masonry surfaces, ideal for resetting bolts and brackets.
- Sets rock hard in minutes – level off within 5 minutes
- It also sets underwater, perfect for repairing drains and ponds.
- Easy to use – excellent results are achieved by the average D-I-Y enthusiast.
- Designed to repair or fix up faulty masonry, where obvious structural defects are apparent.

### PRODUCT INFORMATION

<b>Physical State</b>	Powder
<b>Binder Type</b>	Vinyl reinforced cement based filler
<b>Density</b>	N/A
<b>Water Miscibility</b>	Reacts
<b>pH</b>	12 – 13
<b>Odour</b>	N/A
<b>Flash Point</b>	Non-flash

## DULUX PRE-PAINT QUICK SETTING CEMENT – INTERIOR/EXTERIOR

### APPLICATION INFORMATION

Mixing	<p>Add approximately 1 part of water into 3 parts of powder, mix to a stiff but workable paste with a flat paddle. Ensure that the paste is smooth, and that all lumps have been completely dispersed.</p> <p>Do not mix more paste than can be used within about 10 minutes.</p>
Application Surface conditions	Surface Temperature between 10 - 35°C.
Application methods	Apply with a scraper or small trowel, working well into the repair to ensure a good bond. Level off within 5 minutes.
Thinner	Water/ Powder 1:3 ratio add tap water to adjust consistency.
Drying Time	<b>Dulux Pre-Paint Quick Setting Cement</b> sets rock hard in minutes - level off within 5 minutes. For a smooth repair, avoid disturbing <b>Dulux Pre-Paint Quick Setting Cement</b> during setting.
Over Coating Time	Approx. 30 minutes at 23°C (Drying times may be extended during cold, wet or humid conditions.)
Cleaning of equipment	After use remove as much product as possible, and then clean immediately with warm tap water. For best results use <b>Dulux Pre-Paint Sugar Soap</b> .
Substrates	Suitable for masonry, concrete, brickwork, stone, cement rendering, paving and other exterior surfaces
Precautions:	<p>Does not sand easy when set and should therefore be smoothed off within 5 minutes.</p> <p>Clean up any spilled powder immediately.</p> <p>Not suitable as a filler for metal surfaces.</p> <p>Not suitable for direct application to powdery or friable surfaces whether previously painted or not.</p> <p>Always use clean utensils, and ensure that mixing vessel or surface has no residues of old, mixed Cement.</p> <p>To prolong shelf life, reseal packet after use, and store in a cool and dry conditions.</p>
Top Coating	Apply a coat of <b>Dulux Plaster Primer</b> or <b>Dulux Trade Alkali Resistant Primer</b> or <b>Dulux Trade Plaster Primer – Moisture Tolerant</b> over the repaired areas. Allow to dry, and finish with your chosen top coat.

## DULUX PRE-PAINT QUICK SETTING CEMENT – INTERIOR/EXTERIOR

### SURFACE PREPARATION

---

Ensure that surfaces are sound and free from dust, oil, grease, dirt, and debris.

- Remove all loose plaster, flaking paint and all wallpaper by mechanical or chemical means.
- Narrow cracks are best widened into a “V” shape with a sharp tool to allow the **Dulux Pre-Paint Quick Setting Cement** to be pressed into position.

### HEALTH AND SAFETY INFORMATION

---

**DANGER: Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.**

Dulux products contain no added lead. Contains Portland cement. Causes serious eye damage. Causes skin irritation. May cause respiratory irritation. Keep out of the reach of children. If medical advice is needed, have product container or label at hand. Wear eye or face protection. Use only outdoors or in well-ventilated area. IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or doctor/physician. Store locked up. Dispose of contents and container in accordance with all local, regional, national or international regulations. Avoid breathing dust. Special precautions should be taken during surface preparation of pre -1960's paint surfaces over wood and metal as they may contain harmful lead.

**To avoid the risk of spillage, always store and transport containers in a secure and upright position. Store under ambient conditions.**

Safety and Technical Datasheets available on request or visit [www.dulux.co.za](http://www.dulux.co.za)

### ADDITIONAL INFORMATION

---

Packaging	1kg, 2kg
Storage Conditions	To prolong shelf life reseal packet after use, and store in cool and dry conditions away from direct sunlight, heat and extreme cold.
Disclaimers	N/A product specific

### TDS STANDARD DISCLAIMER

---

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Dulux control.

Important Note; Technology may change with time, necessitating changes to this Technical Data Sheet (TDS).

It is the responsibility of the user to ensure that the latest TDS is being used for reference. Dulux Technical Data Sheets are available on our website [www.duluxtrade.co.za](http://www.duluxtrade.co.za) or please contact: Dulux On-Line on 0860 330 111. Email [ZA.Helpline@akzonobel.com](mailto:ZA.Helpline@akzonobel.com)

ICI Dulux (Pty) Ltd is part of AkzoNobel. ICI Dulux (Pty) Ltd Reg No.1946/020769/07