

GLOSS

PREMIUM GLOSS
ENAMEL PAINT



PRODUCT DESCRIPTION

Dulux Gloss is a premium quality enamel paint recommended for the decoration & protection of interior & exterior surfaces where a glossy, durable finish is required.



PRODUCT FEATURES AND BENEFITS

Dulux Gloss finish gives a smooth mirror like finish & has excellent durability & good coverage. It is ideal for painting household items & furniture like steel, wood, aluminium & even walls.

PRODUCT RELATED INFORMATION

Film Composition:

Pigment : Light fast Non-lead Pigment and Mineral
Binder : Oil Modified Alkyd
Solvent : Mainly White Spirit with other non-toxic solvents.

Colour Range:

See appropriate Shade Card/Fan deck

Volatile Organic Compound (VOC) Level (Theoretical): ASTM D-3960
Varies from 400-500 gm/ltr depending on the shades

Gloss/Sheen Level:

Glossy finish

Flash Point (IS 101/1987, Part 1, Sec 6):

36°C

Stability of Thinned Paint:

Can be used within 24 hours of thinning after mixing.

Film Thickness:

Wet : 40-50µ (micro-meters)
Dry : 25-30µ (micro-meters)

Volume Solids :

50-60 % (nominal)

Theoretical Coverage:

Under normal conditions it is 95-100 sq.ft/ltr for 2 coats. However this can show wide variation depending on actual type/condition of cement.

Pack Size:

Available in 1, 4, 10 and 20 litres.

GLOSS

PREMIUM GLOSS
ENAMEL PAINT



APPLICATION RELATED INFORMATION



Before application, read the safety, health and environmental information and the precautions given below.

Application Tool:

- Can be applied by Brush, Roller & Spray



Surface Preparation:

- Ensure Surface is dry & free from grime, dust, and grease.
- Remove loose or flaking particles.
- Sand the surface by using Emery paper No. 180 & wipe clean.
- For pre-painted surface, where putty application is not expected use Emery paper No. 320 & wipe clean.



Thinning

Brush or Roller:

- For best result, add up to 1 parts Dulux Thinner (61-33) or White Spirit/ Mineral Turpentine Oil (MTO) to 10 parts of paint by volume



Conventional Spray:

- Add up to 2.5 parts Dulux Thinner (61-33) or White Spirit/MTO to 10 parts of paint (25%) by volume depending on specification of the gun.

GENERAL RECOMMENDATIONS



Brushing & Conventional Spray:

- Very suitable for both type of application.

CLEANING UP :

- Clean all equipment with Dulux Thinner (61-33) or White Spirit / Mineral Turpentine Oil immediately after use.

SYSTEM INFORMATION

Metal surface

Primer (1 coat)..... Dulux Red Oxide Metal Primer (34-100)

Finish (2 coats)

Dulux Gloss Finish (28-Line)

Wood surface

Primer (1 coat)..... Dulux Wood Primer White (34-300) or

Finish (2 coats)

Dulux Gloss Finish (28-Line)

Masonry surface

Primer (1 coat)..... Dulux Cement Primer (34-200)

Finish (2 coats)

Dulux Gloss Finish (28-Line)

Re painted surface

Primer (1 coat)..... (not required)

Finish (2 coats)

Dulux Gloss Finish (28-Line)



Drying Time :

- Single coat at standard thickness
 - **Touch Dry** : Within 60 minutes.
 - **Tack Free** : Within 4-6 hours
- For further details, carefully read the information on containers as well.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

- Flammable material. Store container in upright position, with lid tightly closed, in a cool, dry place, away from ignition sources. In case of fire, use foam, dry powder, CO₂, never use water.
- Keep out of reach of children and away from combustible material, food, drink and animal feeding stuffs.
- Avoid contact with skin. Remove splashes from skin with soap and water or recognized skin cleanser. If swallowed, seek medical advice immediately and show the container or label.
- Use only in well ventilated areas. Vapours may cause drowsiness and dizziness.
- Repeated exposure may cause skin dryness or cracking.
- Contains Cobalt carboxylate, Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Avoid release to the environment.
- Refer to special instructions/Safety data sheet.
- Do not empty material into drains or in water courses.
- Highly toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
- Contains spillage using sand or earth.
- Safety Data Sheet available for professional user on request
- No added Lead, Mercury or Chromium compounds.

PRECAUTIONS

- Avoid extreme temperature
- Do not apply on damp surface
- Stir well before use
- Wear eye protection when applying
- Avoid inhalation of dust wearing a suitable nose pad during sanding or surface preparation
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of contact with skin, remove splashes from skin with soap and water or a recognized skin cleanser
- In case of ingestion seek medical attention

CONTACT US



Registered office:
ICI India Limited
Genturajil Apartment, 1st Floor, 80 Middleton Street,
Kokkots - 700 071



In case of any complaints please contact, Complaint Management Cell, ICI India Ltd., Infinity Towers A, 7th floor, DLF Cyber City, Phase II, Gurgaon 122002, Haryana, India, Ph: 0124-3266087

For more information on our products, visit us at www.icidulux.co.in

Note: The information provided above may change without prior notice.