

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION:

- No added Lead, Mercury or Chromium compounds
- Lead content in dried paint film does not exceed 90 parts per million
- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and other fumes. Wet sanding/flaming should be used wherever possible. Work in well ventilated areas. Use suitable personal protection Equipment.
- Container must be in a secure, upright position and be tightly closed.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.
- Do not empty into drains or water course.
- Safety data sheet available for professional/user on request.
- Do not use empty container for storing food.
- Use only in well ventilated areas.
- Store in cool dry well-ventilated place away from sources of heat, ignition, and direct sunlight. Keep the container tightly closed. Keep out of the reach of children and away from food, drink and animal feed.
- If swallowed seek medical advice immediately and show this container or label.
- Use only in well ventilated areas. Do not breathe gas/fumes/vapor/spray.
- Remove as much paint as possible from brushes and rollers before cleaning.
- May cause an allergic skin reaction. May cause sensitization by skin contact.
- Contain spillages using earth or sand.
- Do not empty into drains. Dispose of contents and container in accordance with all local, regional, national or international regulations.
- Avoid release to the environment. Refer to special instructions/Safety data sheet.
- Lift with care – gross weight may exceed 10 kg.

PRECAUTIONS:

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not apply during wet weather.
- Never apply over powdery and flaky substrate directly.
- Don't apply over the asphalt or bituminous surfaces.
- Do not over thin or overextend the brush above the recommended dilution
- Do not use Universal stainers or any other colorants.
- Stir thoroughly before use

CONTACT US:

Registered office,
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071
In case of any complaints please contact Customer care cell,
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,
Haryana, India

Note: The information provided above may change without prior notice.



Introducing FloorPlus

Beautifying Your Home



DULUX FloorPlus

PRODUCT DATA SHEET

AkzoNobel

PRODUCT DESCRIPTION :

Dulux Floor Plus is a water based acrylic emulsion exclusively designed to protect and beautify interlock paver blocks, cemented and concrete surfaces, walkways, and terrace floors. It is specially formulated to provide excellent adhesion and superior abrasion resistance which keeps the surface protected for years to come.

PRODUCT FEATURES AND BENEFITS :



High Adhesion



ACTIVE GUARD
technology for superior Algal and fungal resistance



Excellent abrasion resistance



Easy to clean

- **Tough & durable coating**
- **Vibrant and rich shades**
- **Fast drying and cure**
- **High durable pigments** that provides 2X better fading resistance & UV resistance than normal exterior paints

PRODUCT RELATED INFORMATION :

Film Composition:

Pigment	:	Light fast Non-Lead/Chrome pigment.
Binder	:	Pure Acrylic Emulsion
Solvent	:	Water
Color	:	As per AkzoNobel Catalogue (11 Readymade shades)
Finish	:	Smooth
VOC Level	:	White & bases: Low VOC (Theoretical) ASTM D 3960 – 15-45 gm/L.
Gloss/Sheen Level	:	Available in Mid sheen.
Flash Point (IS 101/1987, Part 1, Sec 6)	:	Non-Flash
Stability of Thinned Paint	:	Use within 24 hours of thinning after mixing
Practical Coverage	:	<p>The Spreading capacity of this product will vary considerably according to the roughness and porosity of the surface.</p> <p>On Smooth surface of low porosity: 50-60 sqft/liter/2coats* (Not included the self-priming coat) <i>*subject to the porosity of the substrate.</i></p> <p>These figures are only an approximate guide. Due to variation in different surfaces, the coverage may vary. It is recommended to do a coverage trial before finalizing the paint requirement.</p>
Pack Size	:	Available in 1, 4 & 10 liters.
Shelf Life	:	<ul style="list-style-type: none">• 3 years from the Date of Manufacturing in the original sealed condition.• Store under cover, away from direct sunlight and protect from extreme temperature.• In hot temperature conditions, it must be stored in a temperature-controlled environment i.e. less than 30 Deg C.

APPLICATION RELATED INFORMATION:

Before application, read the safety, health and environmental information and the precautions given below.



Application Tool :
Suitable for application by brush or roller.

Surface Preparation :

- New masonry surfaces must be allowed to completely cure for at least 12 weeks before painting. For all old and new masonry, ensure the surface is thoroughly clean, dry and free from all loose dirt and flaking or chalking paint.
- Old paint should be completely removed. The surface should also be free of grease and other oily material, laitance, organic debris, algae and fungi. This can be achieved by brushing with a wire/stiff coir brush or via a suitable power tool and then apply Dulux Aquatech Pre treatment coat on algae, fungus affected area after cleaning.
- If required, a suitable surface cleaner can be also be used. The surface should then be jet washed. Repeat if required until the surface is sound and clean.
- Any cracks or crevices should be filled with suitable filling compounds/cement sand mixture. Any dampness should be arrested appropriately. Dulux FloorPlus should not be applied to surfaces that are exposed to continuous seepage or dampness.
- Once the preparation is complete, sand the surface to remove any smoothness or glossy areas using a wire brush or power tool sanding. Finally wash with fresh water and allow to dry before painting.

Stir the paint thoroughly before use (Use a flat paddle for homogenous mix)

Self-Priming coat Application:

- Self-priming coat is must for Dulux Floor Plus. Apply a self-priming coat of Dulux Floor Plus to the prepared surface by diluting with 15-20% clean water and allow it to dry for min 5-6 hrs.

Finishing:

- Stir thoroughly before use. Apply 2 coats of Dulux FloorPlus with Max of 5% dilution over the self-priming coat and allow a drying time of 5-6 hours between the coats. Don't over dilute the paint more than the recommended dilution.



Drying Time: (Single coat at standard thickness):

- **Touch Dry** : Upto 30 Mins.
- **Recoat** : 5-6 hours.
- **Curing** : After 72 Hrs of application. (Low Traffic)
- Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and damp conditions.

Note: This product is not intended to use for heavy motor vehicle traffic, water logging of immersion services and where acid/alkali spillages are likely. Care should be taken while moving heavy items over the coated surface.