

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION:

- No added Lead, Mercury & chromium compounds.
- Lead content in dried paint film does not exceed 90 parts per million.
- Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and other fumes. Wet sanding/flaming should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- Wear eye/hand protection.
- Do not breathe vapour /spray.
- Remove as much paint as possible from brushes and rollers before cleaning.
- Avoid release to the environment.
- Collect spillage.
- Keep away from food drinks and animal feed.
- Store in a cool and shaded place.
- Container must be in a secure, upright position and be tightly closed.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.
- Do not empty into drains or water course.
- Safety data sheet available for professional/user on request.
- Do not use empty container for storing food.
- Use only in well ventilated areas.

PRECAUTIONS:

- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin or on clothing.
- Call a POISON CENTER or physician if you feel unwell.
- Dispose of contents and containers in accordance with all local, regional, national and international regulations
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not over thin or overextend the brush.
- Stir thoroughly before use.
- Tinted paint must be thoroughly mixed/shake immediate after the tinter addition.
- It is recommended to use Dulux colorants only for making the shades.

CONTACT US:

Registered office,
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071
In case of any complaints please contact Customer care cell,
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,
Haryana, India

Note: The information provided above may change without prior notice.



Presenting the all new
Dulux SuperClean 3in1
PRODUCT DATA SHEET

PRODUCT DESCRIPTION :

Dulux Superclean 3 in 1 is an interior water based high quality durable smooth emulsion paint developed using the unique **tough stain repellent & Anti-bacterial technology** for decoration and protection purpose. Dulux Superclean 3in1 gives soothing sheen and a rich finish to the walls for beautiful & gorgeous look, also its high Washability gives an easy to maintain and clean walls which have a fresh look for many years to come.



PRODUCT FEATURES AND BENEFITS :



KidProof + technology

Paint film prevents & delays the stains from penetrating further into the wall enabling easy cleaning of walls



Anti-Bacterial technology

The paint film is resistant to certain harmful bacteria[^]



Fungus Guard technology

helps to keep the walls free from Fugal growth & black patches



Sheen Finish

Rich & soothing sheen finish gives the walls a premium & sophisticated look.



Better Coverage

Extra coverage formula helps to provide upto 20% higher coverage than any standard interior emulsions.



Ease of Application

Excellent flow & levelling ensures the proper, rich finish over the wall

PRODUCT RELATED INFORMATION :

Film Composition:

Pigment	: Light fast Non-Lead/Chrome pigment
Binder	: Acrylic co-polymer emulsion
Solvent	: Water
Colour Range	: As per AkzoNobel shade offering

Volatile organic compound (VOC) level in White & bases : <50 gm/litre (Excluding tinter)

Gloss/Sheen Level : Available in Mid sheen

Flash Point (IS 101/1987, Part 1, Sec 6) : Non-Flash

Stability of Thinned Paint : Can be used within 24 hours of thinning after mixing

Dry Film Thickness (Calculated) : 20-25 microns at coverage of 120-140 sqft / litre

Theoretical Coverage : 120-140 sqft / litre/2 coats (The Spreading capacity/coverage of this product will vary considerably according to the roughness and porosity of the surface also the surface preparation)

Pack Size : Available in 1,4, 10 & 20 liters

APPLICATION RELATED INFORMATION:

Before application, read the safety, health and environmental information and the precautions given below.



Application Tool :

Suitable for application by brush or roller.



Surface Preparation :

- Ensure that the surface is clean, dry, free from all loose particles, paint film, dust, dirt, mold, fungal growth etc. before application.
- Surface should be thoroughly rubbed down using a suitable abrasive paper and thereafter wiped off.
- For New concrete / plaster, surface should allow to mature properly.
- For area severely affected by Fungus application of Dulux Aquatech Pre-treatment coat is recommended.
- Fill up all minor cracks and defects with Dulux Aquatech range of Crack fillers as per requirement / cement and sand mixture in the ration 1:3.
- In case of areas having dampness use Dulux Aquatech Interior Waterproof Basecoat on the bare surface as per recommendation.
- Proper surface preparation is must to get the desired effect and finish.
- Dulux superclean 3 in1 should not be applied to the surfaces or substrates which are exposed to continuous seepage or dampness.



Priming coat Application :

- Prime surface with a coat of Dulux Water Based Cement Primer or Dulux Solvent based Cement Primer and dry for 6-8 hrs.



Waterproof Base coat Application (only For Water Proofing Application) :

- Apply 1 coat of Dulux Aquatech interior Waterproof basecoat in the vertical walls. This coat is to be applied undiluted on the masonry surface. Ensure coverage of the water proofing coat as recommended for DFT achievement & good waterproofing.



Putty Application :

- Smoothen the surface by filling dents with thin coats of any suitable putty. Allow drying for 6-8 hours. Sand with Emery paper 180 and wipe clean. (Duwel Acrylic wall putty is recommended for the application).



Priming coat Application :

- Prime surface with a coat of Dulux Water Based Cement Primer or Dulux Solvent based Cement Primer and dry for 6-8 hrs.



Dilution :

- Dilute 1 lit of paint with 400-450 ml of water for Brilliant white & pastel shades. In case of dark colours, dilute 1 lit of paint with a maximum of 300 ml of water (An additional coat may be required for full opacity). Do not over dilute and shake the paint well before use.



Finishing :

- Stir thoroughly before use. Apply 2-3 coats of Dulux Superclean 3in1 and allow a drying time of 4-6 hours between the coats. Normally two coats of paint are enough for opacity and the desired finish. An additional coat might be required for the dark shades to get the desired finish.



Drying Time: (Single coat at standard thickness) :

- Touch Dry : Upto 30 Mins.
- Recoat : 4-6 hours.
- Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool and humid conditions.

For Stain Removal :

Allow the paint to cure for minimum of 7 days and use mild detergent solution to clean stains. Use soft cotton cloth or sponge for cleaning. Stains are best removed when fresh or within 24 hours.

[^] Under test conditions. Tested against 5 types of bacteria as per JIS Z 2801 test method.

*All claims mentioned are subject to compliance with conditions mentioned in the product data sheet.