



▲ PRODUCT DESCRIPTION

Dulux WeatherShield Clear Exterior Wall finish is a premium silicone based product for surfaces like absorbent stone, brick, clay tiles to deliver the natural look over a longer time. It provides excellent water repellency and protection against all adverse weather conditions.

▲ PRODUCT FEATURES AND BENEFITS

- Water-repellant
- Protects against Fungus and Algae growth
- Keeps the surface completely breathable
- Maintains natural look of the surface

▲ PRODUCT RELATED INFORMATION

FILM COMPOSITION (Nominal):
 Silicone based polymer

VOC:
 700 - 800 gm / l

DRY FILM THICKNESS:
 Doesn't form any film but penetrates the absorbent surface upto 1.5 mm depending on the porosity of the surface and coverage

FLASH POINT:
 37° C

COVERAGE:
 The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On surface of average porosity coverage is 30 -60 sq ft/ per litre

FINISHING:
 Retains natural look of the surface

PACK SIZE:
 Available in 1, 4, 20 litres

▲ APPLICATION RELATED INFORMATION

Application tool
 Dulux WeatherShield Clear is suitable for application by brush & spray.

Areas of Application
 Any absorbent surface with porosity e.g. Cement surface, Concrete, Mortar, Clay, Brick, Natural & artificial stone, Mangalore tiles, Corrugated AC sheet etc.

Surface Preparation

- Allow all new surfaces to dry out completely
- Remove all loose dirt, debris, powdery residue, oil, grease, wax or any other contamination by thorough brushing and scraping, using a stiff wire or fibre brush followed by water jetting if required
- Anything which prevents penetration should be removed
- Fill up minor cracks and defects with Cement and Sand mixture for larger holes and cracks
- Ensure that the surface is fully dry before application



▲ APPLICATION METHOD

For surfaces with normal porosity apply one liberal coat of Dulux WeatherShield Clear by brushing evenly on the prepared surface. Allow the surface to dry overnight. Ensure that no small patches are being left out without the coating.

* Repeated brush strokes with heavy brush loading to ensure that the entire area is covered fully.



Thinning:
 No thinning required.



Drying time:
 Leave overnight for complete drying.



Cleaning up:
 Clean brush and other equipments with MTO immediately after use.

Note:
 Before starting application of Dulux WeatherShield Clear its advisable to check the performance of the product on a relatively small area.

▲ POST APPLICATION INSTRUCTIONS

For best performance of the paint, ensure proper washing and cleaning of any dirt, black patches, etc. with water/brush at regular intervals of six months.

▲ SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

- Flammable material
- Store container in an upright position, with lid tightly closed, in a cool, dry place, away from ignition sources
- In case of fire, use foam, dry powder, CO₂, never use water
- Keep out of reach of children and away from combustible material, food, drink and animal feed
- Avoid contact with skin
- Remove splashes from skin with soap and water or recognised skin cleanser
- Harmful: may cause lung damage if swallowed
- If swallowed, do not induce vomiting, seek medical advice immediately and show the container or label
- Use only in well-ventilated areas
- Repeated exposure may cause skin dryness or cracking
- Avoid release to the environment
- Refer to special instructions/Safety Data Sheet
- Do not empty into drains
- Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment
- Contain spillage using sand or earth
- Safety Data Sheet available for professional user on request

No Added Lead, Mercury or Chromium compounds.

▲ PRECAUTIONS

- Do not use over any non-porous smooth surface like Glaze tiles, Vitrified tiles etc.
- Do not thin or overextend the brush.
- Do not use any universal stainers or any other colourants.
- Do not use it on any powdery surface/chalky surface and/or damp surface.
- Refer to Safety, Health and Environmental information before you start painting.

▲ CONTACT US

ICI Paints

Registered office:
 ICI India Limited
 Geetanjali Apartment, 1st Floor, 8B Middleton Street,
 Kolkata - 700 071



Flammable

In case of any complaints please contact, Complaint Management Cell, ICI India Ltd., Infinity Towers A, 7th floor, DLF Cyber City, Phase II, Gurgaon 122002, Haryana, India, Ph:0124-3266087
 For more information on our products, visit us at www.icidulux.co.in
Note: The information provided above may change without prior notice.