



WoodGuard

Interior Putty

PRODUCT DESCRIPTION

Dulux Advanced Water Based Wood putty is a clear putty that fills the pores and grains of wood, thereby producing a smooth surface. It provides a clean and uniform finish to the wood surface and adds richness & depth to the finished coat.

TECHNICAL DATA

Type:	Acrylic emulsion
Flash Point:	12°C
Specific Gravity:	1.31 ± 0.02wt
Solids By Weight:	51.85± 2.0 %
Storage Temperature:	5 - 40°C
Relative humidity:	Optimum range 40-75%



PRODUCT DATA SHEET

AkzoNobel



WoodGuard

Interior Putty

APPLICATION RELATED INFORMATION

Application Tool: Use Spatula or putty knife

APPLICATION PROCEDURE

Surface Preparation: Ensure surface is dry & free from grime, dust, and grease. Remove loose or flaking particles. Sand the surface by using emery paper no. 180 followed by 320. Wipe the surface clean.

Putty: Smoothen the wooden surface by applying Dulux Water Based Wood Putty. Allow wood putty to dry. Lightly sand using Emery Paper 320 and wipe clean.

Stains application: Apply Dulux Wood Stains by rag/brush/ spray. Allow it to dry for upto 30 minutes. Do not sand the stain coat. Staining is optional. Follow regular sealer and topcoat application.

Drying Time:	At 25 °C	At 45 °C
	Touch Dry : 1 hour	- mins
	Recoating Time: 12 hours	2 hours

Above drying time is based on 25 micron (1 mil) wet film thickness.

SHELF LIFE

6 months in sealed container.



AkzoNobel

PRODUCT DATA SHEET