



WoodGuard

Interior Sealer

PRODUCT DESCRIPTION

Dulux Advanced Water Based Sealer is a high build sealer that completely seals and retains the natural look of wood. Apart from offering excellent sealing properties, it is easy to sand and provides a good base for the top coat. It is a water-based sealer for indoor furniture and can be cured in oven with air movement.



PRODUCT DATA SHEET

AkzoNobel



WoodGuard

Interior Sealer

APPLICATION RELATED INFORMATION

- Application Tool:** Can be applied by stainless steel spray gun/brush/roller.
- Direction:** Stir well before using. Film build for the entire finishing system including repairs should not exceed 100 microns (4 dry mils).

APPLICATION PROCEDURE

- Surface Preparation:** Ensure surface is dry & free from grime, dust, and grease. Remove loose or flaking particles. Sand the surface by using emery paper no. 180 followed by 320. Wipe the surface clean.
- Putty:** Smoothen the wooden surface by applying Dulux Water Based Wood Putty. Allow wood putty to dry. Lightly sand using emery paper no. 320 and wipe clean.
- Stains application:** Apply Dulux Wood Stains by rag/brush/spray. Allow it to dry for upto 30 minutes. Do not sand the stain coat.
- Dry Schedule:** Normal drying : Drying time of 3-4 hours between successive coats under standard drying conditions.
Oven drying : 5-10 minutes air flash followed by 30 minutes oven at 40-50 °C and 10 minutes cooling time before sanding.

SHELF LIFE

6 months in sealed container under shelter.



AkzoNobel