



DULUX AMBIANCE™ VELVET

DESCRIPTION

Dulux Ambiance™ Special Effects Paints include the finest featured finishes and textures to create endless unique combinations to personalise your world. Dulux Ambiance™ Velvet is inspired by smooth and sleek fabrics, draping your walls with a rich velvet finish to give them a timeless look and feel.

BENEFITS

- Ready-to-use, trowel applied emulsion paint
- Velvety finish, colour changing effect, textile effect depending on required effect and angle of light incident, way of application.
- Optimized rheology and open time for better application and flow & levelling

USAGE

Ideal for new and previously painted interior masonry, plaster and building boards surfaces.

PACK SIZE

Available only in 1 Liter pack (refer to the pack for the fill volume)

COLOUR RANGE

See appropriate Colour Card.

PHYSICAL FILM PROPERTIES

WATER RESISTANCE

Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

PRODUCT DATA

COMPOSITION

Pigment : Light-fast Non-Lead/Chrome pigment
Binder : Waterborne Polymer
Solvent : Water

DRYING TIMES

Single coat at standard thickness:
Touch Dry : 1-2 hour
Hard Dry : 4-6 hours
Drying time may vary according to temperature and humidity

THEORETICAL COVERAGE

The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity up to 6 m² / L / coat

TYPE OF FINISHING

Velvety finish

APPLICATION GUIDE

SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. Remove all loose and defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush. Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Treat any areas affected mould, lichens, algae and moss with fungicidal treatment/ Dulux Fungicidal Wash. Repair any surface defects with an appropriate filler. Surfaces that remain powdery, friable or chalky after

	thorough preparation should be sealed with one coat of an appropriate Primer (see below System Recommendation). Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust. Do not paint if the wall is saturated with dampness. (Protimeter reading higher than 16%). Allow excess moisture to evaporate.														
APPLICATION TOOLS	Trowel or roller along with trowel														
DILUTION	Ready to use. No dilution														
RECOMMENDED APPLICATION CONDITION	<ul style="list-style-type: none">Dulux Ambiance™ Velvet is recommended for interior walls only.Avoid windy conditions in the room.Room temperature should ideally be between 20°C and 35°C.Very hot, dry conditions are to be avoided.Use of any other paint apart from the specially formulated Dulux Ambiance™ Velvet may deviate from the desired finish and make it hard to recondition.														
PRIME	Prime surface with a coat of appropriate Dulux Sealer first														
TOPCOAT	Apply 2 coats of Dulux Ambiance™ tinted in required colour. Please ensure 2-4 hours drying time between coats.														
DULUX AMBIANCE™ VELVET	Apply 1st coat of Dulux Ambiance™ Velvet in required colour with roller and then use trowel to smoothen out the paint. For the 2nd coat, apply a thin layer of paint in waves by trowel. Ensure 4 -6 hours drying time between coats. This effect finish is not washable. Please use dry cloth to clean the wall if needed.														
SYSTEM RECOMMENDATION	<table><tr><th>System Information</th><th>Sealer (1 coat)</th><th>Topcoat (2 coats)</th><th>Special Effect (2 coats)</th></tr><tr><td><i>Powdery and Alkaline Surfaces</i></td><td><i>Dulux Sealer (solvent-based)</i></td><td rowspan="3">Dulux Ambiance™</td><td rowspan="3">Dulux Ambiance™ Velvet</td></tr><tr><td><i>New Surfaces</i></td><td><i>Dulux Sealer (water-based)</i></td></tr><tr><td><i>Normal, Sound Surfaces</i></td><td><i>No sealer required</i></td></tr></table> <p><i>For alternative coating systems, please refer to our Sales Representative</i></p>			System Information	Sealer (1 coat)	Topcoat (2 coats)	Special Effect (2 coats)	<i>Powdery and Alkaline Surfaces</i>	<i>Dulux Sealer (solvent-based)</i>	Dulux Ambiance™	Dulux Ambiance™ Velvet	<i>New Surfaces</i>	<i>Dulux Sealer (water-based)</i>	<i>Normal, Sound Surfaces</i>	<i>No sealer required</i>
System Information	Sealer (1 coat)	Topcoat (2 coats)	Special Effect (2 coats)												
<i>Powdery and Alkaline Surfaces</i>	<i>Dulux Sealer (solvent-based)</i>	Dulux Ambiance™	Dulux Ambiance™ Velvet												
<i>New Surfaces</i>	<i>Dulux Sealer (water-based)</i>														
<i>Normal, Sound Surfaces</i>	<i>No sealer required</i>														
CLEANING UP	Clean all equipment with clean water immediately after use.														
HEALTH, SAFETY & ENVIRONMENT INFORMATION	Please refer to Product Safety Data Sheet														
<p>For further information or if you have any concerns about using this product contact the Customer Care Hotline at the address below:</p> <p>PT. ICI Paints Indonesia, Jl. Jababeka IV Blok V No. 64 Cikarang Industrial Estate, Bekasi 17530 Tel: 0-800-11-38589 (Bebas Pulsa) Web: www.dulux.co.id</p>															
<p>Any advice, recommendations, information, assistance or service provided by PT ICI Paints Indonesia in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by PT ICI Paints Indonesia is provided without expressed or implied warranties.</p>															
March 2019															

