



Dulux EasyClean

A937 Line

USAGE	Dulux EasyClean is high quality water-based interior emulsion specially made with KidProof Technology™* so everyday stains on the wall paints is easily cleaned without damaging the paint coating. Dulux EasyClean with good scrubability and low odour. It is suitable for all normal interior masonry surfaces incl. brickwork, cement, plaster and wallboards
PACK SIZE	2.5L and 20L
COLOUR RANGE	See appropriate Colour card and Master Palette
FILM PROPERTIES	<i>Water Resistance:</i> Will tolerate the levels of atmospheric humidity presents in normal interior environments and will withstand moderately vigorous washing. Not suitable where frequent heavy condensation is likely, as in some kitchens and bathrooms
COMPOSITION	<i>Pigment:</i> Lightfast Non Lead Pigment <i>Binder:</i> Acrylic Copolymer Emulsion <i>Solvent:</i> Water
VOLUME SOLIDS	White 41% (nominal), other colours will vary
POT LIFE	
DRYING TIMES	<i>Single coat at standard thickness:</i>
TOUCH DRY	Dependent on temperature and humidity
RECOAT DRY	1-2 hours
2-PACK PRODUCTS	-
CURING TIMES	
RECOAT AT 30°C	-
FULL CURE	-
FILM THICKNESS	30 – 40 microns dry film thickness
THEORETICAL SPREADING	Theoretical spreading under normal conditions is 11-13 m ² /litre
APPLICATION METHOD	Apply with roller, brush and spray
MIXING RATIO	
THINNING	<i>Brush or Roller:</i> For sealing new or bare surfaces thin with up to 1 part of clean water to 10 parts of paint (10%) For normal use thinning should not exceed 1 part of clean water to 10 parts of paint (10%) <i>Conventional spray:</i> Add up to 1 part clean water to 10 parts of paint (10%)
SPRAY RECOMMENDATION	<i>Conventional spray:</i> Satisfactory through most equipment <i>Airless Spray:</i> A typical set up for airless spray application would be a minimum working pressure on paint of 140 Kg/cm ² with a spray tip size

	0.38mm and a spray tip angle 65°
CLEANING UP	Clean all equipment with clean water immediately after use
SURFACE PREPARATION	Surfaces must be sound, clean, dry, free from all defective or poorly adhering material, dirt, grease, wax, and be rubbed down thoroughly using a suitable abrasive paper and dusted off. If after thorough preparation surfaces remain powdery or suffer from alkali attack, seal with one coat of an appropriate Primer (see below)
FLASH POINT	
SYSTEM INFORMATION:	<p>Powdery Surfaces: <i>Primer (1 coat):</i> Dulux Alkali Killer <i>Finish (2-3 coats):</i> Dulux EasyClean</p> <p>Alkaline and New Surfaces: <i>Primer (1 coat):</i> Dulux Cat Dasar Alkali Resisting Interior or Dulux Alkali Killer <i>Finish (2-3 coats):</i> Dulux EasyClean</p> <p>Normal, Sound Surfaces: <i>Finish (2-3 coats):</i> Dulux EasyClean</p>
SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION	<p>Based on GHS criteria, this product is not classified as hazardous. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Don't get in eyes, on skin, or on clothing. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Avoid release to the environment. Wear eye/ hand protection. Do not breathe vapour/ spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Dispose of contents and used container in accordance with local regulation. Safety data sheet available for professional user on request to toll free 0-800-11-DULUX 38589 Or download at www.dulux.co.id.</p>
For further information or if you have any concerns about using this product contact the Sales Department at the address below:	

**PT. ICI Paints Indonesia,
Jababeka Industrial Estate,
Jl. Jababeka IV Blok V No.64,
Cikarang Bekasi 17530 - Jawa Barat
Tel: (6221) 893 4767/87, Fax: (6221) 893 5079**

Any advice, recommendations, information, assistance or service provided by PT ICI Paints Indonesia in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by PT ICI Paints Indonesia is provided without expressed or implied warranties.

June 2014