



DULUX INSPIRE EXTERIOR

A1530154 LINE (WATERBASED)

PRODUCT INFORMATION

Product Name	Dulux Inspire Exterior
Product Code	A1530154
DESCRIPTION	Dulux Inspire Exterior Finish is quality acrylic based emulsion paint with advanced Chroma Brite Technology that keeps your house looks fresh and new for a longer period of time. It has durable paint film that provides resistance from damage caused by water, algae and fungus, and peeling off. In compliance to SIRIM Eco Label and Singapore Green Label.
USAGE	Suitable for newly painted or previously painted exterior masonry surface such as brickwork, plaster, cement, rendering and asbestos
BENEFITS	Provides protection against fungus and algae growth. Good alkali resistance, adhesion properties, and durability.
PACK SIZE	1, 5 and 18 litres
COLOR RANGE	See Dulux Inspire Colour Catalogue

PERFORMANCE GUIDE

FILM PROPERTIES	
Chemical Resistance	Resistant to mild atmospheric fume attack and to the salts in new mortar, rendering and similar surfaces.
Water Resistance	Resistant to the levels of atmospheric humidity present in normal exterior environments.
THEORETICAL COVERAGE	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 10 - 11 m ² /L.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
VOLUME SOLIDS	White 37% (nominal), other colours will vary.

APPLICATION

THINNING	
Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 10 parts of paint (10%).
Conventional Spray	For normal use thinning is usually not necessary.
Airless Spray	Add up to 1 part of clean water to 3 parts of paint (30%). Ready for use. Thinning is usually not required.
DRYING TIMES	
Touch Dry	Single coat at standard thickness:
Recoat	Dependant on temperature and humidity. 2-3 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. Remove all loose or defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush and high pressure water jet. Treat any areas affected mould, lichens, algae and moss with Dulux Fungicidal Wash. Make good minor defects with a suitable exterior grade Filler. Surfaces that remain powdery, friable or chalky after thorough preparation should be sealed with one coat of an appropriate Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These wall should be left to dry further.	
SYSTEM INFORMATION Powdery Surfaces	PRIMER (1 COAT) Dulux Weathershield Primer (A579-15222)	FINISH (2 COATS) * Vibrant/ deep shade may require additional coats
Alkaline and New Surfaces	Dulux Exterior & Interior Wall Sealer (A1290013 0015527)	Dulux Inspire Exterior
Normal, Sound Surfaces	No Primer Required	

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Contains 3-iodo-2-propynyl-n-butylcarbamate. May produce an allergic reaction. • Store in a cool and shaded place. • Container must be in a secure, upright position and be tightly closed. • Keep away from the reach of children and away from food, drinks and animal feed. • If swallowed seek medical advice immediately and show this container or label. • Avoid contact with skin or eyes. • In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. • In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvent thinners or white spirits. • Wear eye/face protection. • Do not breathe vapour/spray. • Use only in well ventilated areas. • Do not empty into drains or watercourses. • Avoid release to environment. Refer to special instructions/safety data sheet. • Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. • Dispose of used container in compliance with local regulation. • Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. • Do not use empty container for storing food. • Remove as much paints as possible from brushes and rollers before cleaning. • Refer to Dulux Product Safety Data Sheet for further details. • In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187
---	--

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com