



DULUX ALUMINIUM WOOD PRIMER SEALER

A519-3697 (SOLVENTBASED)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Aluminium Wood Primer Sealer
Product Code	A519-3697
DESCRIPTION	Dulux Aluminium Wood Primer Sealer is a solvent based primer for wood.
USAGE	Suitable for use on all types of soft and hard woods, inside and outside, especially those which are highly resinous. It can also be used as a sealer for aged creosoted or bitumen coated surfaces.
BENEFITS	Good penetration and wetting properties. Contains aluminium pigment which helps prevent migration of wood sap to the surface.
PACK SIZE	5 and 20 litres only
COLOR RANGE	Aluminium.

PERFORMANCE GUIDE

FILM PROPERTIES	
Heat Resistance	Resistant up to 120°C.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 12 m ² /L.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Non-leafing Aluminium. Binder : Alkyd. Solvent : White Spirit.
VOLUME SOLIDS	38% (nominal).
FLASH POINT	32-55 °C.

APPLICATION

THINNING	
Brush	Ready for use, thinning is usually not necessary.
DRYING TIMES	Single coat at standard thickness:
Touch Dry	3-4 hours.
Recoat	16-24 hours.
FILM THICKNESS	Wet : 80 micro-metres. Dry : 30 micro-metres.
CLEANING UP	Clean all equipment with Dulux Thinner 850-41 or white spirit immediately after use.

PRE-APPLICATION

SURFACE PREPARATION	Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. All surfaces should be thoroughly rubbed down in the direction of the grain, using a suitable abrasive paper and then dusted off. It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These substrate should be left to dry further.		
SYSTEM INFORMATION Wood	PRIMER (1 COAT) Dulux Aluminium Wood Primer Sealer (A519-3697) 2 coats are recommended for highly resinous wood and bituminous surfaces. Allow 48 hours between coats for best results.	UNDERCOAT (1 COAT) Dulux Speed Undercoat (A545-101)	FINISH (2 COATS) Dulux Gloss Finish (A365) Or Satinwood (A345) may also be used on interior surfaces only.

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION

FLAMMABLE

- Toxic to aquatic organisms may cause long-term adverse side effects in the aquatic environment.
- Repeated exposure may cause skin dryness or cracking.
- Avoid contact with skin.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- To remove splashes of paint from skin, use soap and water or a recognized cleanser.
- Keep away from food, drinks, animal feed and out of reach of children.
- Keep away from combustible material.
- Container must be stored in a cool and shaded place.
- It must be tightly closed in a secure, upright position.
- Work in a well-ventilated area and do not breathe in vapor or spray.
- A suitable mask should be worn during sanding.
- When applying paint, it is advisable to wear eye protection and suitable gloves.
- In case of fire use foam, dry powder, AFFF, CO2- Never use water.
- In case of spillage, contain and collect spillage using sand or earth and do not empty into water courses, drains or environment.
- Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.
- Refer to Dulux Product Safety Data Sheet for further details.
- In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187

3Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com

A BRAND FROM
AkzoNobel