



DULUX WATER-BASED GLOSS

A908 Line (WATERBASED)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Water-Based Gloss
Product Code	A908 Line
DESCRIPTION	Dulux Water-Based Gloss is a high quality water-based Gloss.
USAGE	Dulux Water-Based Gloss is a high quality non-yellowing high gloss finish suitable for use on interior and exterior metal and wood surfaces, both new and previously painted. It has excellent adhesion, colour retention, good durability and is low odour compared to conventional solvent based gloss finish.
BENEFITS	<ul style="list-style-type: none"> • Fast dry. Back in service rapidly and less disruption • Low odour • Low VOC • Non yellowing • Good application properties • Easier clean-up of painting tools
PACK SIZE	1 & 5 litres
COLOR RANGE	See appropriate colour card
TINTING OR READY MIX	Tinting and Ready Mix (only for Black 10125)
VOC Limit	< 50 grams/litre

PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Will tolerate with a slightly damp surface but is not suitable where the surface is saturated.
THEORETICAL COVERAGE	Theoretical coverage which can be achieved under normal conditions is 10-12 m ² /litre.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
VOLUME SOLIDS	White 45% (nominal).

APPLICATION

THINNING Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (5%). For normal use, thinning is usually not necessary.
Conventional Spray Airless Spray	Add up to 1 part of clean water to 5 parts of paint (5%). Ready for use.
SPRAY RECOMMENDATIONS Conventional spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: 30 to 40 microns 1 hour under normal conditions. 3 hours under normal conditions.
CLEANING UP	Clean all equipment with clean water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. If after thorough preparation, surfaces remain powdery, or suffer from alkali attack seal with one coat of an appropriate Primer (see below). Note: Even though this primer facilitates painting on damp walls, it should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 22%. These walls should be left to dry further. However, if painted, the moisture will build up behind this waterproof primer and cause blisters to emerge on the paint film on aging.	
SYSTEM INFORMATION	PRIMER (1 COAT)	FINISH (2 COATS)
Wood	Dulux Water-Based Gloss Primer (A931-15480)	Dulux Water-Based Gloss A908
Metal	Dulux Water-Based Gloss Primer (A931-15480)	

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION	<ul style="list-style-type: none">• Keep out of the reach of children• Do not breathe vapour/ spray• Use only in well ventilated areas• Safety data sheet available for professional user on request.• Avoid contact with skin or eyes• If swallowed seek medical advice immediately and show this container or label.• Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used• Do not use empty container for storing food.• Remove as much paint as possible from brushes and rollers before cleaning.• Keep away from food, drinks and animal feed.• Store in a cool and shaded place.• Container must be in a secure, upright position and be tightly closed.• In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.• In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.• Wear eye/hand protection.• Avoid release to environment. Refer to special instructions/Safety data sheet.• Do not empty into water course.• Dispose of used container in compliance with local regulation.• Refer to Dulux Product Safety Data Sheet for further details.• In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187
---	---

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com