



DULUX TIMBERCOLOUR ACRYLIC WOOD FINISH

A926 LINE (WATERBASED)

PRODUCT INFORMATION

PRODUCT NAME	Timbercolour Acrylic Wood Finish
Product Code	A926 Line
DESCRIPTION	Timbercolour Acrylic Wood Finish from Dulux is a full acrylic, high quality, durable emulsion ideal for direct application to exterior wood surfaces.
USAGE	Timbercolour Acrylic Wood Finish is ideal for direct application to exterior wood surfaces including fences, barge-boards, fascias, exposed balconies and wood walls and cladding. This can also be used direct onto galvanised iron such as gutters and roof sheets.
BENEFITS	Excellent adhesion properties and durability. Contains light-fast pigments which give a good colour fastness. Works as an effective mould control.
PACK SIZE	5 litres only.
COLOR RANGE	Refer to Colour Inspirations.

PERFORMANCE GUIDE

FILM PROPERTIES	
Water Resistance	Will tolerate the levels of atmospheric humidity present in normal exterior environments.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10 m ² /litre

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
VOLUME SOLIDS	35% (nominal), other colours will vary.

APPLICATION

THINNING	
Brush or Roller	For normal use, thinning is usually not necessary. If required, add up to 1 part of clean water to 10 parts of paint (10%).
Conventional Spray	Add up to 1 part of clean water to 3 parts of paint (30%).
SPRAY RECOMMENDATIONS	Satisfactory through most equipment.
DRYING TIMES	
Touch Dry	Single coat at standard thickness: Dependant on temperature and humidity.
Recoat	2-3 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION	Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. All surfaces should be thoroughly rubbed down in the direction of the grain, using a suitable abrasive paper and then dusted off. It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These substrate should be left to dry further. Clean all of dirt, mould, algae, lichen or moss with a wire brush. On badly affected areas treat with Dulux Fungicidal Wash.	
SYSTEM INFORMATION	PRIMER N/A.	FINISH (1-2 COATS) Timbercolour Acrylic Wood Finish (A926)

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION

- Keep out of the reach of children
- Do not breathe vapour/ spray
- Use only in well ventilated areas
- Safety data sheet available for professional user on request.
- Avoid contact with skin or eyes
- If swallowed seek medical advice immediately and show this container or label.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used
- Do not use empty container for storing food.
- Remove as much paints as possible from brushes and rollers before cleaning.
- Keep away from food, drinks and animal feed.
- Store in a cool and shaded place.
- Container must be in a secure, upright position and be tightly closed.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.
- Wear eye/hand protection.
- Avoid release to environment. Refer to special instructions/Safety data sheet.
- Do not empty into water course.
- Dispose of used container in compliance with local regulation.
- Refer to Dulux Product Safety Data Sheet for further details.
- In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com

A BRAND FROM
AkzoNobel