



# DULUX WEATHERSHIELD ROOF MID-SHEEN ROOFTILE FINISH

**A968 LINE (WATERBASED)**

## PRODUCT INFORMATION

<b>PRODUCT NAME</b>	Dulux Weathershield Roof
<b>Product Code</b>	A968-Line
<b>DESCRIPTION</b>	Dulux Weathershield Roof is a high quality, highly durable 100% acrylic based emulsion with a smooth finish and mid sheen.
<b>USAGE</b>	It is specially designed for the protection and the decoration of old and new roofs such as cement fiber sheet and unglazed roof tiles. It may also be used on concrete or cement fiber pipes. Note: Dulux Weathershield Roof paint system is not recommended for glazed tiles. However, it can be used on old glazed tiles which have lost the glazed film.
<b>BENEFITS</b>	Excellent colour fastness properties. Colourlock technology to ensure colour stay looking new for longer Keep Cool heat reflective technology - Savings of up to 15% per annum on the energy used to cool your home and reduce exterior surface temperature by up to 5°C. Excellent alkali resistance. Effective mould control. Singapore Green Label certified Sirim Eco-Label certified
<b>PACK SIZE</b>	5 litres
<b>COLOR RANGE</b>	Refer to Colour Inspirations.

## PERFORMANCE GUIDE

<b>FILM PROPERTIES</b>	
Water Resistance	Will tolerate the levels of atmospheric humidity present in exterior environments.
<b>THEORETICAL COVERAGE</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 20 m <sup>2</sup> /5 litre

## PRODUCT DATA

<b>COMPOSITION</b> (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
<b>VOLUME SOLIDS</b>	50% (nominal), some colours will vary.

## APPLICATION

<b>THINNING</b>	
Brush or Roller	On cool tiles, add up to 1 part of clean water to 10 parts of paint (10%). On hot tiles, add up 1 part of clean water to 5 parts of paint (20%).
Conventional Spray	Add up to 1 part of clean water to 5 parts of paint (20%).
Airless Spray	Ready for use.
<b>SPRAY RECOMMENDATIONS</b>	
Conventional spray	Satisfactory through most equipment.
Airless Spray	A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
<b>DRYING TIMES</b>	
Touch Dry	Single coat at standard thickness: 1 hour.
Recoat	2-3 hours.
<b>CLEANING UP</b>	Clean all equipment with clean water immediately after use.

## PRE-APPLICATION

<b>SURFACE PREPARATION</b>	Surfaces to be painted must be thoroughly cleaned to ensure good adhesion. Remove all loose or defective paint or powdery residues by thorough brushing or scraping, using a stiff fiber brush with running water or high pressure water jet. Treat any areas affected by mould, lichens, algae, and moss with Dulux Fungicidal Wash. Repair minor cracks before painting. Use a sand and cement mix for larger holes and cracks. Allow to dry before priming with Dulux Weathershield Roof Primer. Note: Paint will not adhere on dirty and powdery substrates which are not thoroughly cleaned. Do not apply Dulux Weathershield Roof during wet weather.	
<b>SYSTEM INFORMATION</b> Cleaned weathered roof tiles.	<b>PRIMER (1 COAT)</b> Dulux Weathershield Roof Primer (A579-10611)	<b>FINISH (1-2 COATS)</b> Dulux Weathershield Roof (A968)

## PRECAUTION

<b>HEALTH, SAFETY AND ENVIRONMENT INFORMATION</b>	<ul style="list-style-type: none"><li>• Keep out of the reach of children</li><li>• Do not breathe vapour/ spray</li><li>• Use only in well ventilated areas</li><li>• Safety data sheet available for professional user on request.</li><li>• Avoid contact with skin or eyes</li><li>• If swallowed seek medical advice immediately and show this container or label.</li><li>• Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used</li><li>• Do not use empty container for storing food.</li><li>• Remove as much paints as possible from brushes and rollers before cleaning.</li><li>• Keep away from food, drinks and animal feed.</li><li>• Store in a cool and shaded place.</li><li>• Container must be in a secure, upright position and be tightly closed.</li><li>• In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li><li>• In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.</li><li>• Wear eye/hand protection.</li><li>• Avoid release to environment. Refer to special instructions/Safety data sheet.</li><li>• Do not empty into water course.</li><li>• Dispose of used container in compliance with local regulation.</li><li>• Refer to Dulux Product Safety Data Sheet for further details.</li><li>• In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187</li></ul>
---	--

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

### Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: [www.dulux.com.my](http://www.dulux.com.my) Email: [customercare.my@akzonobel.com](mailto:customercare.my@akzonobel.com)